

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

1 Identification

- **Product identifier**
- **Trade name:** *Aliquat 336/MIBK*
10% v/v Soln., ASTM D3237-02
- **Article number:** *INS010*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 2

H351 Suspected of causing cancer.



GHS05 Corrosion

Eye Damage 1

H318 Causes serious eye damage.



GHS07

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Skin Irritation 2

H315 Causes skin irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 1)

· **Hazard pictograms**



GHS02 GHS05 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Methyl Isobutyl Ketone (4-Methyl-2-pentanone)
methyltrioctylammonium chloride

· **Hazard statements**

Highly flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO₂, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 3

Fire = 3

Reactivity = 0

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 2)

· **HMIS-ratings (scale 0 - 4)**

HEALTH	3	Health = 3
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	89.075%
CAS: 5137-55-3	methyltriocetylammmonium chloride	10.925%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
 Immediately remove any clothing soiled by the product.
 Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
 Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.
 In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
 · **Most important symptoms and effects, both acute and delayed** No further relevant information available.
 · **Indication of any immediate medical attention and special treatment needed**
 No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
 CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 3)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 Use neutralizing agent.
 Dispose contaminated material as waste according to section 13.
 Ensure adequate ventilation.
- **Reference to other sections**
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	75 ppm
CAS: 5137-55-3	methyltriocylammonium chloride	0.67 mg/m ³

· PAC-2:

CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	500 ppm
CAS: 5137-55-3	methyltriocylammonium chloride	7.4 mg/m ³

· PAC-3:

CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	3000* ppm
CAS: 5137-55-3	methyltriocylammonium chloride	44 mg/m ³

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 Ensure good ventilation/exhaustion at the workplace.
 Open and handle receptacle with care.
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
 Keep receptacle tightly sealed.
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 4)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

PEL Long-term value: 410 mg/m³, 100 ppm

REL Short-term value: 300 mg/m³, 75 ppm
 Long-term value: 205 mg/m³, 50 ppm

TLV Short-term value: 75 ppm
 Long-term value: 20 ppm
 BEI, A3

· **Ingredients with biological limit values:**

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

BEI 1 mg/L
 LD50 Intraperitoneal: urine
 Time: end of shift
 LD50: MIBK

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Clear

· **Odor:** Distinct

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 114 °C (237.2 °F)

· **Flash point:** 14 °C (57.2 °F)

· **Flammability (solid, gaseous):** Highly flammable.

· **Auto igniting:** 460 °C (860 °F)

· **Decomposition temperature:** Not determined.

· **Ignition temperature:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 1.7 Vol %

Upper: 9 Vol %

· **Vapor pressure at 20 °C (68 °F):** 8 hPa (6 mm Hg)

· **Density at 20 °C (68 °F):** 0.80912 g/cm³ (6.75211 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 6)

Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	89.1 %
VOC content:	89.07 %
	720.7 g/l / 6.01 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral	LD50	2,041 mg/kg (rat)
Inhalative	LC50/4h	12.3 mg/l (ATE)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	2B
---------------	---	----

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 7)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Must not reach bodies of water or drainage ditch undiluted or unneutralized.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|-------------------------------------|---|
| · UN-Number | UN3286 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Flammable liquid, toxic, corrosive, n.o.s. (Methyl Isobutyl Ketone (4-Methyl-2-pentanone), methyltrioctylammonium chloride) |
| · DOT | FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (Methyl Isobutyl Ketone (4-Methyl-2-pentanone), methyltrioctylammonium chloride), MARINE POLLUTANT |
| · IMDG | |
| · IATA | FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (Methyl Isobutyl Ketone (4-Methyl-2-pentanone), methyltrioctylammonium chloride) |
| · Transport hazard class(es) | |
| · DOT | |
| | |
| · Class | 3 Flammable liquids |

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 8)

· **Label** 3, 6.1, 8

· **IMDG**



· **Class** 3 Flammable liquids
· **Label** 3/6.1/8

· **IATA**



· **Class** 3 Flammable liquids
· **Label** 3 (6.1, 8)

· **Packing group**

· **DOT, IMDG, IATA** II

· **Environmental hazards:** Product contains environmentally hazardous substances: methyltrioctylammonium chloride

· **Marine pollutant:** Symbol (fish and tree)

· **Special precautions for user** Warning: Flammable liquids

· **Hazard identification number (Kemler code):** 336

· **EMS Number:** F-E,S-C

· **Stowage Category** B

· **Stowage Code** SW2 Clear of living quarters.

· **Segregation Code** SG5 Segregation as for class 3

SG8 Stow "away from" class 4.1

· **Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**

· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 1 L
On cargo aircraft only: 5 L

· **IMDG**

· **Limited quantities (LQ)** 1L

· **Excepted quantities (EQ)** Code: E2

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 3286 FLAMMABLE LIQUID, TOXIC, CORROSIVE, N.O.S. (METHYL ISOBUTYL KETONE (4-METHYL-2-PENTANONE), METHYLTRIOCTYLAMMONIUM CHLORIDE), 3 (6.1+8), II

US

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 9)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

· **TSCA (Toxic Substances Control Act):**

Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

ACTIVE

methyltriocetylammmonium chloride

ACTIVE

· **Hazardous Air Pollutants**

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

· **Proposition 65**

· **Chemicals known to cause cancer:**

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

I

· **TLV (Threshold Limit Value)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS05

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Methyl Isobutyl Ketone (4-Methyl-2-pentanone)

methyltriocetylammmonium chloride

· **Hazard statements**

Highly flammable liquid and vapor.

Harmful if inhaled.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 10)

Causes skin irritation.

Causes serious eye damage.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

*

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:**

Date of Preparation / Last Revision:

· **Date of preparation / last revision**

Revision 1.2 05-14-2024: Reviewed SDS for accuracy. GW/STN

Revision 0.0, 12-28-2015: creation date for SDS. STN

05/14/2024

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

(Contd. on page 12)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/14/2024

Reviewed on 05/14/2024

Trade name: Aliquat 336/MIBK
10% v/v Soln., ASTM D3237-02

(Contd. of page 11)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Inhalation 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Damage 1: Serious eye damage/eye irritation – Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

· *** Data compared to the previous version altered.**

US