Printing date 06/13/2024

Reviewed on 06/13/2024

1 Identification

- · Product identifier
- Trade name: <u>GC Calibration Standard Level 5</u> 10,000 ppm w/w IPA:TAA:VA:TBA
- · Article number: HON184
- Details of the supplier of the safety data sheet • Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225

DEER PARK, TX 77536 USA 800-256-2586

- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org • Emergency telephone number:
- *Chemtrec:* 800-424-9300 *Canutec:* 613-996-6666

2 *Hazard*(*s*) *identification*

· Classification of the substance or mixture



GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer.



Skin Irritation 2 H315 Causes skin irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Warning

Hazard-determining components of labeling: Vinyl Acetate, Reagent Grade
Hazard statements Causes skin irritation. Suspected of causing cancer.
Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. If on skin: Wash with plenty of water.

(Contd. on page 2)

US

Printing date 06/13/2024

Reviewed on 06/13/2024

Trade name: GC Calibration Standard Level 5 10,000 ppm w/w IPA:TAA:VA:TBA

(Contd. of page 1)

IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)

1 0 Health = 1Fire = 0 Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH1Health = 1FIRE0Fire = 0REACTIVITY0Reactivity = 0

• Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous com	ponents:	
CAS: 67-63-0	Isopropanol	1.0%
CAS: 75-65-0	tert-Butyl Alcohol	1.0%
CAS: 75-85-4	2-methyl-2-butanol	1.0%
CAS: 108-05-4	Vinyl Acetate, Reagent Grade	1.0%
•	zardous Ingredients	
CAS: 7732-18-5	Water	96.0%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

(Contd. on page 3)

Printing date 06/13/2024

Reviewed on 06/13/2024

Trade name: GC Calibration Standard Level 5 10,000 ppm w/w IPA:TAA:VA:TBA

(Contd. of page 2)

5 *Fire-fighting measures*

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions:
- Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

• **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

Protective Action Criteria for Chemicals

• Protective Actio	on Criteria for Chemicals		
· PAC-1:			
CAS: 67-63-0	Isopropanol		400 ppm
CAS: 75-65-0	tert-Butyl Alcohol		150 ppm
CAS: 108-05-4	Vinyl Acetate, Reagent Grade		6.7 ppm
· PAC-2:			
CAS: 67-63-0	Isopropanol	2	2000* ppm
CAS: 75-65-0	tert-Butyl Alcohol	-	1,300 ppm
CAS: 108-05-4	Vinyl Acetate, Reagent Grade		36 ppm
· PAC-3:			
CAS: 67-63-0	Isopropanol	120	000** ppm
CAS: 75-65-0	tert-Butyl Alcohol	800	00* ppm
CAS: 108-05-4	Vinyl Acetate, Reagent Grade	180	О ррт

7 Handling and storage

· Handling:

- Precautions for safe handling Open and handle receptacle with care.
- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

US

Printing date 06/13/2024

Trade name: GC Calibration Standard Level 5 10,000 ppm w/w IPA:TAA:VA:TBA

(Contd. of page 3)

Reviewed on 06/13/2024

• *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

	: 67-63-0 Isopropanol	
	Long-term value: 980 mg/m ³ , 400 ppm	
	Short-term value: 1225 mg/m ³ , 500 ppm	
	Long-term value: 980 mg/m ³ , 400 ppm	
TLV	Short-term value: 400 ppm	
	Long-term value: 200 ppm	
	BEI, A4	
CAS	75-65-0 tert-Butyl Alcohol	
PEL	Long-term value: 300 mg/m ³ , 100 ppm	
REL	Short-term value: 450 mg/m ³ , 150 ppm	
	Long-term value: 300 mg/m ³ , 100 ppm	
TLV	Long-term value: 100 ppm	
	A4	
CAS	: 108-05-4 Vinyl Acetate, Reagent Grade	
REL	Ceiling limit value: 15* mg/m ³ , 4* ppm	
	*15-min	
TLV	Short-term value: 15 ppm	
	Long-term value: 10 ppm	
	A3	
· Ingr	edients with biological limit values:	
CAS	: 67-63-0 Isopropanol	
	40 mg/L	
	LD50 Intraperitoneal: urine	
	Time: end of shift at end of workweek	
	LD50: Acetone (background, nonspecific)	
· Addi	itional information: The lists that were valid during the creation were used as basis.	
· Expa	osure controls	
	onal protective equipment:	
	eral protective and hygienic measures:	
	o away from foodstuffs, beverages and feed.	
	ediately remove all soiled and contaminated clothing.	
	h hands before breaks and at the end of work.	
	e protective clothing separately.	
	d contact with the skin.	
	d contact with the eyes and skin.	
• Drea	athing equipment: Not required.	(Contd. on page 5)
		(puge b)

US

Printing date 06/13/2024

Reviewed on 06/13/2024

Trade name: GC Calibration Standard Level 5 10,000 ppm w/w IPA:TAA:VA:TBA

(Contd. of page 4)

US

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection: Goggles recommended during refilling.

· Body protection: Protective work clothing

9 Physical and chemical properties

 Information on basic physical and c General Information 	chemical properties	
· Appearance:		
Form:	Liquid	
Color:	Colorless	
· Odor:	Characteristic	
• Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	0 °C (32 °F)	
Boiling point/Boiling range:	100 °C (212 °F)	
· Flash point:	Not applicable.	
· Flammability (solid, gaseous):	Not applicable.	
· Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Danger of explosion:	Product does not present an explosion hazard.	
· Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	0.99298 g/cm³ (8.28642 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
	(Contd. on p	page

Printing date 06/13/2024

Reviewed on 06/13/2024

Trade name: GC Calibration Standard Level 5 10,000 ppm w/w IPA:TAA:VA:TBA

		(Contd. of page
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octan	ol/water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	1.0~%	
Water:	96.0 %	
VOC content:	1.00 %	
	9.9 g/l / 0.08 lb/gal	
Solids content:	1.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

 Oral
 LD50
 100,000 mg/kg (rat)

Inhalative LC50/4h 367 mg/l

• Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Resea	irch on Cancer)
CAS: 67-63-0 Isopropanol	3
CAS: 108-05-4 Vinyl Acetate, Reagent	t Grade 2B
· · · · ·	(Contd. on page 7

Printing date 06/13/2024

Reviewed on 06/13/2024

Trade name: GC Calibration Standard Level 5 10,000 ppm w/w IPA:TAA:VA:TBA

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- $\cdot \textit{Recommendation: Disposal must be made according to official regulations.}$
- Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, IMDG, IATA	Not regulated	
UN proper shipping name		
DOT, IMDG, IATA	Not regulated	
Transport hazard class(es)		
DOT, ADN, IMDG, IATA		
Class	Not regulated	
Packing group		
DOT, IMDG, IATA	Not regulated	
Environmental hazards:	Not applicable.	

US

Printing date 06/13/2024

Reviewed on 06/13/2024

		(Contd. of page
· Special precautions for user	Not applicable.	
• Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.	
· UN "Model Regulation":	Not regulated	
5 Regulatory information		
Safety, health and environmental regu- No further relevant information availate Sara	lations/legislation specific for the substa ole.	ance or mixture
• Section 355 (extremely hazardous sub	stances):	
CAS: 108-05-4 Vinyl Acetate, Reagent	,	
· Section 313 (Specific toxic chemical li	stings):	
CAS: 67-63-0 Isopropanol	·····o-/·	
CAS: 75-65-0 tert-Butyl Alcohol		
CAS: 108-05-4 Vinyl Acetate, Reagent	Grade	
• TSCA (Toxic Substances Control Act)		
Water		ACTIV
Isopropanol		ACTIV
tert-Butyl Alcohol		ACTIV
2-methyl-2-butanol		ACTIV
Vinyl Acetate, Reagent Grade		ACTIV
· Hazardous Air Pollutants		
CAS: 108-05-4 Vinyl Acetate, Reagent	Grade	
· Proposition 65		
· Chemicals known to cause cancer:		
None of the ingredients is listed.		
· Chemicals known to cause reproductiv	ve toxicity for females:	
None of the ingredients is listed.		
• Chemicals known to cause reproductiv	e toxicity for males:	
None of the ingredients is listed.		
· Chemicals known to cause developme	ntal toxicity:	
None of the ingredients is listed.		
· Carcinogenic categories)	
• EPA (Environmental Protection Agen	cy)	
CAS: 75-65-0 tert-Butyl Alcohol		S
• TLV (Threshold Limit Value)		
CAS: 67-63-0 Isopropanol		A
CAS: 75-65-0 tert-Butyl Alcohol CAS: 108-05-4 Vinyl Acetate, Reagent		A
LAN' IUX-UN-4 VINVI Acetate Reagent	(TRAAP	

Printing date 06/13/2024

Reviewed on 06/13/2024

Trade name: GC Calibration Standard Level 5 10,000 ppm w/w IPA:TAA:VA:TBA

(Contd. of page 8)

\cdot NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



- · Signal word Warning
- *Hazard-determining components of labeling: Vinyl Acetate, Reagent Grade*
- Hazard statements Causes skin irritation.

Suspected of causing cancer. • **Precautionary statements**

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of Preparation / Last Revision:
- \cdot Date of preparation / last revision
- *Revision 1.2, 06/13/2024: Reviewed SDS for accuracy. MH/STN 06/13/2024 / 1.0*
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 10)

[–] US

Printing date 06/13/2024

Reviewed on 06/13/2024

Trade name: GC Calibration Standard Level 5 10,000 ppm w/w IPA:TAA:VA:TBA

(Contd. of page 9)

NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Skin Irritation 2: Skin corrosion/irritation – Category 2 Carcinogenicity 2: Carcinogenicity – Category 2 • * Data compared to the previous version altered.