Printing date 03/17/2021 Reviewed on 03/17/2021

1 Identification

· Product identifier

· Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

· Article number: AM455

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300

Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

Eye Irrit. 2A H319 Causes serious eye irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Warning
- · Hazard statements

Harmful if swallowed.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear eye protection / face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

(Contd. on page 2)

Printing date 03/17/2021 Reviewed on 03/17/2021

Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 1)

Rinse mouth.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 1Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 105-59-9	N-Methyldiethanolamine, 99%	40.0%	
CAS: 124-38-9	Carbon Dioxide Gas	2.054%	
CAS: 7783-06-4	Hydrogen Sulfide	2.054%	
· Table of Nonhazardous Ingredients			
CAS: 7732-18-5	Water	55.892%	

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 03/17/2021 Reviewed on 03/17/2021

Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 2)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

1 Totalite Action	i Crueria for Chemicais		
· PAC-1:			
CAS: 7783-06-4	Hydrogen Sulfide	0.51 ppm	
· PAC-2:			
CAS: 7783-06-4	Hydrogen Sulfide	27 ppm	
· PAC-3:			
CAS: 7783-06-4	Hydrogen Sulfide	50 ppm	

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

Printing date 03/17/2021 Reviewed on 03/17/2021

Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 3)

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

	is time, the remaining constituent has no morn exposure times.
CAS	: 124-38-9 Carbon Dioxide Gas
PEL	Long-term value: 9000 mg/m³, 5000 ppm
REL	Short-term value: $54,000 \text{ mg/m}^3$, $30,000 \text{ ppm}$ Long-term value: 9000 mg/m^3 , 5000 ppm
TLV	Short-term value: $54,000 \text{ mg/m}^3$, $30,000 \text{ ppm}$ Long-term value: 9000 mg/m^3 , 5000 ppm
CAS	: 7783-06-4 Hydrogen Sulfide
PEL	Ceiling limit value: 20; 50* ppm *10-min peak; once per 8-hr shift
REL	Ceiling limit value: 15* mg/m³, 10* ppm *10-min
TLV	Short-term value: 7 mg/m³, 5 ppm Long-term value: 1.4 mg/m³, 1 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- $\cdot \ General \ protective \ and \ hygienic \ measures:$

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

Printing date 03/17/2021 Reviewed on 03/17/2021

Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 4)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Phys	ical and	l chemi	cal pro	nerties
- I Ivys	icui unu	CITCHILL	cut pro	periods

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Liquid Color: Colorless

· Odor: Like rotten eggs (mercaptans)

· Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:Undetermined.

• Flash point: $260 \, ^{\circ}C \, (500 \, ^{\circ}F)$

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 265 °C (509 °F)
• Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

· Explosion limits:

Lower:Not determined.Upper:Not determined.

• Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

Density: Not determined.
 Relative density Not determined.
 Vapor density Not determined.
 Evaporation rate Not determined.

· Solubility in / Miscibility with

Water: Fully miscible.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. **Kinematic:** Not determined.

(Contd. on page 6)

Printing date 03/17/2021 Reviewed on 03/17/2021

Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 5)

	(Contd. of page
· Solvent content:	
Water:	55.9 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4h 4,869 mg/l

CAS: 7783-06-4 Hydrogen Sulfide

Inhalative LC50/4h 100 mg/l (ATE)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

Printing date 03/17/2021 Reviewed on 03/17/2021

Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

	UN	-N	umb	er
--	----	----	-----	----

· **DOT, IMDG, IATA** UN3287

· UN proper shipping name

• **DOT** Toxic liquid, inorganic, n.o.s. (Hydrogen sulfide)

· IMDG, IATA TOXIC LIQUID, INORGANIC, N.O.S. (HYDROGEN SULPHIDE)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 6.1 Toxic substances

· Label 6.1

(Contd. on page 8)

Printing date 03/17/2021 Reviewed on 03/17/2021

Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 7) · IMDG, IATA 6.1 Toxic substances · Class · Label · Packing group · DOT, IMDG, IATA II· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Toxic substances · Stowage Category · Stowage Code SW2 Clear of living quarters. · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L · IMDG · Limited quantities (LQ) 100 ml · Excepted quantities (EQ) Code: E4 Maximum net quantity per inner packaging: 1 ml Maximum net quantity per outer packaging: 500 ml UN 3287 TOXIC LIQUID, INORGANIC, N.O.S. (HYDROGEN · UN "Model Regulation": SULPHIDE), 6.1, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

CAS: 7783-06-4 Hydrogen Sulfide

· Section 313 (Specific toxic chemical listings):

CAS: 7783-06-4 Hydrogen Sulfide

· TSCA (Toxic Substances Control Act):

· ISCA (TOXIC Substances Control Act).	
Water	ACTIVE
N-Methyldiethanolamine, 99%	ACTIVE
Carbon Dioxide Gas	ACTIVE
Hydrogen Sulfide	ACTIVE

(Contd. on page 9)

Printing date 03/17/2021 Reviewed on 03/17/2021

Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 8)

· Hazardous Air Pollutants

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 7783-06-4 Hydrogen Sulfide

I

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

· Signal word Warning

· Hazard statements

Harmful if swallowed.

Causes serious eye irritation.

May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear eye protection / face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Get medical advice/attention if you feel unwell.

If eye irritation persists: Get medical advice/attention.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 03/17/2021 Reviewed on 03/17/2021

Trade name: 1200 grains/gal CO2

1200 grains/gal H2S in 40% v/v MDEA

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 0.0, 03-17-2021 Creation date for SDS. STN 03/17/2021 / 1.0

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Acute Tox. 4: Acute toxicity - Category 4

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

* * Data compared to the previous version altered.

US