Printing date 07/25/2024 Reviewed on 07/25/2024

1 Identification

· Product identifier

· Trade name: OH lvl 4

· Article number: HON195

Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

• Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 2 H341 Suspected of causing genetic defects.

Carcinogenicity 2 H351 Suspected of causing cancer.



Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3

H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Isopropanol

Acetaldehyde, Reagent ACS Grade

(Contd. on page 2)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

(Contd. of page 1)

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing genetic defects.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

US

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous con	•	
CAS: 67-63-0	Isopropanol	90.0%
CAS: 75-65-0	tert-Butyl Alcohol	5.0%
CAS: 75-85-4	2-methyl-2-butanol	1.5%
CAS: 625-23-0	2-Methyl-2-Hexanol	1.5%
CAS: 75-07-0	Acetaldehyde, Reagent ACS Grade	1.0%
CAS: 79-10-7	Acrylic Acid	1.0%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · **Protective equipment:** No special measures required.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:	
CAS: 67-63-0 Isopropanol	400 ppm
CAS: 75-65-0 tert-Butyl Alcohol	150 ppm
CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade	45 ppm
CAS: 79-10-7 Acrylic Acid	1.5 ppm
PAC-2:	
CAS: 67-63-0 Isopropanol	2000* ppn
CAS: 75-65-0 tert-Butyl Alcohol	1,300 ppm
CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade	270 ppm
CAS: 79-10-7 Acrylic Acid	46 ppm
PAC-3:	
CAS: 67-63-0 Isopropanol	12000** ppn
CAS: 75-65-0 tert-Butyl Alcohol	8000* ppm
CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade	840 ppm
CAS: 79-10-7 Acrylic Acid	180 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

(Contd. of page 4)

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At th	is time, the other constituents have no known exposure limits.
CAS	: 67-63-0 Isopropanol
PEL	Long-term value: 980 mg/m³, 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4
CAS.	: 75-65-0 tert-Butyl Alcohol
PEL	Long-term value: 300 mg/m³, 100 ppm
REL	Short-term value: 450 mg/m³, 150 ppm Long-term value: 300 mg/m³, 100 ppm
TLV	Long-term value: 100 ppm A4
CAS.	: 75-07-0 Acetaldehyde, Reagent ACS Grade
PEL	Long-term value: 360 mg/m³, 200 ppm
REL	See Pocket Guide Apps. A and C
TLV	Ceiling limit value: 25 ppm A2
CAS.	79-10-7 Acrylic Acid
REL	Long-term value: 6 mg/m³, 2 ppm Skin
TLV	Long-term value: 2 ppm Skin, A4
·Ingr	edients with biological limit values:
CAS	· 67_63_0 Isopropanal

CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

· Protection of hands:



The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information

· Appearance:

Form: Liquid
Color: Clear

Odor: CharacteristicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:82 °C (179.6 °F)

• Flash point: 11 °C (51.8 °F)

· Flammability (solid, gaseous): Highly flammable.

Auto igniting: 425 °C (797 °F)
 Decomposition temperature: Not determined.

• Ignition temperature: Product is not selfigniting.

• **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

 Lower:
 2 Vol %

 Upper:
 12 Vol %

(Contd. on page 7)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

		(Contd. of page
· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)	
Density at 20 °C (68 °F):	0.78767 g/cm³ (6.57311 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	90.0 %	
VOC content:	90.00 %	
	708.9 g/l / 5.92 lb/gal	
Solids content:	6.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 1	values tha	t are relevant for classification:
ATE (Acut	te Toxicity	y Estimate)
	LD50	14,324 mg/kg (rat)
Dermal	LD50	28,000 mg/kg (rabbit)
Inhalative	LC50/4h	147 mg/l

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

(Contd. on page 8)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

Carcinogenic categories

IARC (International Agency for Research on Cancer)

CAS: 67-63-0 | Isopropanol | 3 |
CAS: 75-07-0 | Acetaldehyde, Reagent ACS Grade | 2B |
CAS: 79-10-7 | Acrylic Acid | 3 |

NTP (National Toxicology Program)

CAS: 75-07-0 | Acetaldehyde, Reagent ACS Grade | R |

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	1311003
DOT, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Isopropanol
	, tert-Butyl Alcohol, Acetaldehyde, Reagent ACS Grade)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Isopropanol
•	, tert-Butyl Alcohol, Acetaldehyde, Reagent ACS Grade)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

(Contd. of page 8) · Transport hazard class(es) $\cdot DOT$ · Class 3 Flammable liquids ·Label · IMDG, IATA · Class 3 Flammable liquids · Label · Packing group · DOT, IMDG, IATA II· Environmental hazards: Not applicable. Warning: Flammable liquids · Special precautions for user · Hazard identification number (Kemler code): 33 F-E,S-D· EMS Number: · Segregation groups (SGG1) Acids · Stowage Category В · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ On passenger aircraft/rail: 5 L · Quantity limitations On cargo aircraft only: 60 L \cdot IMDG · Limited quantities (LQ) 5LCode: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL , TERT-BUTYL ALCOHOL, ACETALDEHYDE, REAGENT ACS

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

GRADE), 3, II

- Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.


(Contd. on page 10)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

(Contd. of page 9) · Section 313 (Specific toxic chemical listings): CAS: 67-63-0 Isopropanol CAS: 75-65-0 tert-Butyl Alcohol CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade CAS: 79-10-7 Acrylic Acid · TSCA (Toxic Substances Control Act): *ACTIVE* Isopropanol tert-Butyl Alcohol ACTIVE 2-methyl-2-butanol *ACTIVE* Acetaldehyde, Reagent ACS Grade ACTIVE**ACTIVE** Acrylic Acid · Hazardous Air Pollutants CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade CAS: 79-10-7 Acrylic Acid · Proposition 65 · Chemicals known to cause cancer: CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: None of the ingredients is listed. · Chemicals known to cause developmental toxicity: None of the ingredients is listed. · Carcinogenic categories · EPA (Environmental Protection Agency) CAS: 75-65-0 tert-Butyl Alcohol SCCAS: 75-07-0 Acetaldehyde, Reagent ACS Grade *B2* · TLV (Threshold Limit Value) CAS: 67-63-0 Isopropanol A4CAS: 75-65-0 tert-Butyl Alcohol A4CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade A3CAS: 79-10-7 Acrylic Acid A4· NIOSH-Ca (National Institute for Occupational Safety and Health) CAS: 75-07-0 Acetaldehyde, Reagent ACS Grade

· GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).









GHS02 GHS07

GHS08

· Signal word Danger

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

(Contd. of page 10)

Hazard-determining components of labeling:

Isopropanol

Acetaldehyde, Reagent ACS Grade

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing genetic defects.

Suspected of causing cancer.

May cause drowsiness or dizziness.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 07-25-2024: Reviewed SDS for accuracy. STN/GW 07/25/2024 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 12)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: OH lvl 4

(Contd. of page 11)

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Germ Cell Mutagenicity 2: Germ cell mutagenicity – Category 2

Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

* Data compared to the previous version altered.

US