Printing date 06/29/2021 Reviewed on 06/29/2021

1 Identification

· Product identifier

· Trade name: Solvent-100, Light aromatic

· Article number: S4200

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

H351 Suspected of causing cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom.

1,2,4-Trimethylbenzene

(Contd. on page 2)

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

(Contd. of page 1)

cumene

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eve irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2

Fire = 2

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2

Fire = 2Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 3)

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

· vPvB: Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	90-100%
CAS: 95-63-6	1,2,4-Trimethylbenzene	30-50%
CAS: 108-67-8	mesitylene	10-20%
CAS: 98-82-8	cumene	1-5%
CAS: 526-73-8	1,2,3-Trimethylbenzene	1-5%
CAS: 1330-20-7	Xylene (Xylol)	1-5%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
CAS: 95-63-6	1,2,4-Trimethylbenzene	140 ppn
CAS: 108-67-8	mesitylene	140 ppn
CAS: 98-82-8	cumene	50 ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	140 ppn
CAS: 1330-20-7	Xylene (Xylol)	130 ppn
PAC-2:		
CAS: 95-63-6	1,2,4-Trimethylbenzene	360 ppm
CAS: 108-67-8	mesitylene	360 ppm
CAS: 98-82-8	cumene	300 ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	360 ppm
CAS: 1330-20-7	Xylene (Xylol)	920* ppr
PAC-3:		
CAS: 95-63-6	1,2,4-Trimethylbenzene	480 ppm
CAS: 108-67-8	mesitylene	480 ppm
CAS: 98-82-8	cumene	730 ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	480 ppm
CAS: 1330-20-7	Xylene (Xylol)	2500* ppi

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

(Contd. of page 4)

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

At this time, the remaining constituent has no known exposure limits.
CAS: 95-63-6 1,2,4-Trimethylbenzene
REL Long-term value: 125 mg/m³, 25 ppm
TLV Long-term value: 123 mg/m³, 25 ppm
CAS: 108-67-8 mesitylene
REL Long-term value: 125 mg/m³, 25 ppm
TLV Long-term value: 123 mg/m³, 25 ppm
CAS: 98-82-8 cumene
PEL Long-term value: 245 mg/m³, 50 ppm Skin
REL Long-term value: 245 mg/m³, 50 ppm Skin
TLV Long-term value: (246) NIC-25 mg/m³, (50) NIC-5 ppm NIC-A3
CAS: 526-73-8 1,2,3-Trimethylbenzene
REL Long-term value: 125 mg/m³, 25 ppm
TLV Long-term value: 123 mg/m³, 25 ppm
CAS: 1330-20-7 Xylene (Xylol)
PEL Long-term value: 435 mg/m³, 100 ppm
REL Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV Short-term value: 651 mg/m³, 150 ppm Long-term value: 434 mg/m³, 100 ppm BEI
· Ingredients with biological limit values:
CAS: 1330-20-7 Xylene (Xylol)
BEI 1.5 g/g creatinine

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:

Time: end of shift

· General protective and hygienic measures:

LD50 Intraperitoneal: urine

LD50: Methylhippuric acids

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 6)

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Clear

Odor: Aromatic

Odor threshold: Not determined.

· pH-value:
· Change in condition

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 148-185 °C (298.4-365 °F)

• Flash point: >38 °C (>100.4 °F)

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 420 °C (788 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

Not determined.

· Explosion limits:

 Lower:
 0.7 Vol %

 Upper:
 7.5 Vol %

(Contd. on page 7)

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

		(Contd. of page
· Vapor pressure at 20 °C (68 °F):	5 hPa (3.8 mm Hg)	
· Density at 20 °C (68 °F):	0.87-0.88 g/cm³ (7.26015-7.3436 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	er): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	133-185 %	
VOC content:	0-100 %	
	1,609.5-1,628 g/l / 13.43-13.59 lb/gal	
Solids content:	0.0 %	
	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects

· Acute toxi	city:	
· LD/LC50	values tha	t are relevant for classification:
ATE (Acu	te Toxicity	Estimate)
Oral	LD50	28,000-140,000 mg/kg (rat)
Dermal	LD50	40,000-200,000 mg/kg
Inhalative	LC50/4h	>6.75-8.59 mg/l
CAS: 6474	12-95-6 Sa	olvent naphtha (petroleum), light arom.
Inhalative	LC50/4h	11 mg/l (ATE)
CAS: 95-6	3-6 1,2,4-	Trimethylbenzene
Inhalative	LC50/4h	11 mg/l (ATE)
CAS: 98-8	2-8 cume	ne
Oral	LD50	500 mg/kg (ATE)
		(Contd. on page

(Contd. on page 8)

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

(Contd. of page 7)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (Interna	tional Agency for Research on Cancer)	
CAS: 98-82-8	cumene	2 <i>B</i>
CAS: 1330-20-	7 Xylene (Xylol)	3
· NTP (National	Toxicology Program)	
CAS: 98-82-8	cumene	R
· OSHA-Ca (Oco	cupational Safety & Health Administration)	
None of the ing	redients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN1268

(Contd. on page 9)

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

	(Contd. of pag
UN proper shipping name	
DOT	Petroleum distillates, n.o.s.
IMDG, IATA	PETROLEUM DISTILLATES, N.O.S.
Transport hazard class(es)	
DOT	
RAMABLE LOUIS	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: 1,2 Trimethylbenzene
	<u> </u>
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code): EMS Number:	50 F-E,S-D
Stowage Category	A A
	71
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	approace.
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
2	On cargo aircraft only: 220 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
Little qualities (LQ)	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN ''Model Regulation'':	UN 1268 PETROLEUM DISTILLATES, N.O.S., 3, III

15 Regulatory information

 $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture}} \\ \textit{No further relevant information available}.$

(Contd. on page 10)

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

Section 355 (extremely ho	zardous substances):	
None of the ingredients is		
Section 313 (Specific toxi	c chemical listings):	
	imethylbenzene	
CAS: 98-82-8 cumene	<u> </u>	
CAS: 1330-20-7 Xylene (Xylol)	
TSCA (Toxic Substances	Control Act):	
Solvent naphtha (petroleu	,	ACTIVI
1,2,4-Trimethylbenzene	<i>7</i> . 0	ACTIVI
mesitylene		ACTIVI
cumene		ACTIVI
1,2,3-Trimethylbenzene		ACTIVI
Xylene (Xylol)		ACTIVI
Hazardous Air Pollutants		
CAS: 98-82-8 cumene		
CAS: 1330-20-7		
Proposition 65		
Chemicals known to caus	e cancer:	
CAS: 98-82-8 cumene		
Chemicals known to caus	e reproductive toxicity for females:	
None of the ingredients is	listed.	
Chemicals known to caus	e reproductive toxicity for males:	
None of the ingredients is		
Chemicals known to caus	e developmental toxicity:	
None of the ingredients is		
Carcinogenic categories EPA (Environmental Pro	taction Agancy)	
CAS: 95-63-6 1,2,4-Tr		II
CAS: 108-67-8 mesityle		II II
CAS: 98-82-8 cumene		D, CBI
	imethylbenzene	II
	•	I I
CAS: 1330-20-/ Xylene (.	* '	
CAS: 1330-20-7 Xylene (
TLV (Threshold Limit Va CAS: 1330-20-7 Xylene (A

(Contd. of page 10)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

· Hazard pictograms







· Signal word Danger

· Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom.

1,2,4-Trimethylbenzene

cumene

· Hazard statements

Flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of causing cancer.

May cause drowsiness or dizziness.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 06/29/2021 Reviewed on 06/29/2021

Trade name: Solvent-100, Light aromatic

(Contd. of page 11)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 0.0, 06-29-2021 Creation date for SDS. STN 06/29/2021 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

US