Printing date 07/19/2024

Reviewed on 07/19/2024

1 Identification

- · Product identifier
- · Trade name: <u>Solvent-100, Light aromatic</u>
- Article number: S4200
- Details of the supplier of the safety data sheet • Manufacturer/Supplier:
- Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586
- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org
- *Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666*

2 Hazard(s) identification

· Classification of the substance or mixture



Flammable Liquids 3

GHS08 Health hazard

Carcinogenicity 2 H351 Suspected of causing cancer. Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard 1



Skin Irritation 2 Eye Irritation 2A Specific Target Organ Toxicity - Single Exposure 3 H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H226 Flammable liquid and vapor.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

(Contd. on page 2)

US –

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Solvent-100, Light aromatic

(Contd. of page 1)
· Hazard-determining components of labeling:
Solvent naphtha (petroleum), light arom.
Xylene (Xylol)
1,2,4-Trimethylbenzene
Cumene
· Hazard statements
Flammable liquid and vapor.
Causes skin irritation.
Causes serious eye irritation.
Suspected of causing cancer.
May cause drowsiness or dizziness.
May cause damage to organs through prolonged or repeated exposure.
May be fatal if swallowed and enters airways.
· Precautionary statements
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat/sparks/open flames/hot surfaces No smoking.
Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dust/fume/gas/mist/vapors/spray.
Wash thoroughly after handling.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Immediately call a poison center/doctor.
Specific treatment (see on this label).
Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· Classification system:
· NFPA ratings (scale 0 - 4)
Health = 2
$\frac{2}{Fire = 2}$
$\frac{2}{Reactivity} = 0$
\checkmark \checkmark Reactivity = 0
· HMIS-ratings (scale 0 - 4)
HEALTH *2 $Health = *2$
FIRE 2 $Fire = 2$
$\frac{1}{\text{REACTIVITY}[0]} Reactivity = 0$

(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Solvent-100, Light aromatic

• Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

· L	Dungerous components.		
(CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	90-100%
(CAS: 95-63-6	1,2,4-Trimethylbenzene	30-50%
(CAS: 108-67-8	mesitylene	10-20%
(CAS: 98-82-8	Cumene	1-5%
(CAS: 526-73-8	1,2,3-Trimethylbenzene	1-5%
(CAS: 1330-20-7	Xylene (Xylol)	1-5%

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• *Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.*

(Contd. on page 4)

US

Printing date 07/19/2024

Trade name: Solvent-100, Light aromatic

Reviewed on 07/19/2024

		(Contd. of page
Environmental p	recautions:	
Do not allow pro	duct to reach sewage system or any water course.	
	e authorities in case of seepage into water course or sewage system.	
Dilute with plent		
	enter sewers/ surface or ground water.	
	terial for containment and cleaning up:	
	id-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
	nated material as waste according to section 13.	
Ensure adequate Reference to oth		
	information on safe handling.	
	information on personal protection equipment.	
	r disposal information.	
	a Criteria for Chemicals	
PAC-1:		
CAS: 95-63-6	1,2,4-Trimethylbenzene	140 ppr
CAS: 108-67-8	mesitylene	140 ppr
CAS: 98-82-8	Cumene	50 ppm
	1,2,3-Trimethylbenzene	140 ppr
CAS: 1330-20-7	Xylene (Xylol)	130 ppr
<i>PAC-2:</i>		
CAS: 95-63-6	1,2,4-Trimethylbenzene	360 ppm
CAS: 108-67-8	mesitylene	360 ppm
CAS: 98-82-8	Cumene	300 ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	360 ppm
CAS: 1330-20-7	Xylene (Xylol)	920* ppr
<i>PAC-3:</i>		
CAS: 95-63-6	1,2,4-Trimethylbenzene	480 ppm
CAS: 108-67-8	mesitylene	480 ppm
CAS: 98-82-8	Cumene	730 ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	480 ppm
CAS: 1330-20-7	Xylene (Xylol)	2500* ppn

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.

(Contd. on page 5)

US

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Solvent-100, Light aromatic

- Further information about storage conditions: Keep receptacle tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:
- The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

	s time, the remaining constituent has no known exposure limits.
	95-63-6 1,2,4-Trimethylbenzene
REL	Long-term value: 125 mg/m³, 25 ppm
TLV	Long-term value: 10 ppm
	A4
CAS:	108-67-8 mesitylene
REL	Long-term value: 125 mg/m³, 25 ppm
TLV	Long-term value: 10 ppm
CAS:	98-82-8 Cumene
	Long-term value: 245 mg/m³, 50 ppm Skin
	Long-term value: 245 mg/m³, 50 ppm Skin
	Long-term value: 5 ppm A3
CAS:	526-73-8 1,2,3-Trimethylbenzene
REL	Long-term value: 125 mg/m³, 25 ppm
TLV	Long-term value: 10 ppm
CAS:	1330-20-7 Xylene (Xylol)
PEL	Long-term value: 435 mg/m³, 100 ppm
	Short-term value: 655 mg/m³, 150 ppm
	Long-term value: 435 mg/m³, 100 ppm
	Long-term value: 20 ppm
	BEI, A4
· Ingre	dients with biological limit values:
CAS:	1330-20-7 Xylene (Xylol)
	1.5 g/g creatinine
	LD50 Intraperitoneal: urine
	Fime: end of shift
	LD50: Methylhippuric acids
	ional information: The lists that were valid during the creation were used as basis.
	sure controls
	nal protective equipment:
	ral protective and hygienic measures: away from foodstuffs, beverages and feed.
	diately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

(Contd. on page 6)

US

Printing date 07/19/2024

*

Reviewed on 07/19/2024

Trade name: Solvent-100, Light aromatic

Store protective clothing separately. Avoid contact with the eyes and skin. Breathing equipment:			
	In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands:		
Protective gloves			
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation			
 Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. Eye protection: 			
• Body protection: Protective work clo	othing		
9 Physical and chemical proper	tios		
 Information on basic physical and c General Information 	hemical properties		
· Appearance:			
Form:	Liquid		
Color: • Odor:	Clear Aromatic		
• Odor threshold:	Not determined.		
· pH-value:	Not determined.		
· Change in condition			
Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 148-185 °C (298.4-365 °F)		
· Flash point:	>38 °C (>100.4 °F)		
· Flammability (solid, gaseous):	Flammable.		
• Auto igniting:	420 °C (788 °F)		
• Decomposition temperature:	Not determined.		
· Ignition temperature:	Product is not selfigniting.		

(Contd. on page 7)

US

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Solvent-100, Light aromatic

	(Contd. of page
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
· Explosion limits:	
Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	5 hPa (3.8 mm Hg)
· Density at 20 °C (68 °F):	0.87-0.88 g/cm ³ (7.26015-7.3436 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.
· Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	133-185 %
VOC content:	0-100 %
	1,609.5-1,628 g/l / 13.43-13.59 lb/gal
Solids content:	0.0 %
• Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 22,000-110,000 mg/kg

Inhalative LC50/4h >6.75-8.59 mg/l

• Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

• Sensitization: No sensitizing effects known.

(Contd. on page 8)

US

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Solvent-100, Light aromatic

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

CAS: 98-82-8 Cumene

CAS: 1330-20-7 Xylene (Xylol)

· NTP (National Toxicology Program)

CAS: 98-82-8 Cumene

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

· UN-Number		
· DOT, IMDG, IATA	UN1268	
· UN proper shipping name		
$\cdot DOT$	Petroleum distillates, n.o.s.	
· IMDG, IATA	PETROLEUM DISTILLATES, N.O.S.	

(Contd. of page 7)

2B

R

3

Printing date 07/19/2024

24

Trade name: Solvent-100, Light aromatic

92

	(Contd. of pag
Transport hazard class(es)	
DOT	
R.MIJABLE LOUD	
3	
Class	3 Flammable liquids
Label	3
IMDG	
Class	3 Flammable liquids
Label	3
IATA	
Class Label	3 Flammable liquids 3
Packing group DOT, IMDG, IATA	III
Environmental hazards:	Product contains environmentally hazardous substances: 1,2,
Mariana II (and	Trimethylbenzene
Marine pollutant:	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code) EMS Number:	; 50 F-E,S-D
Stowage Category	A
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
	····· <i>TT</i> ······
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 60 L
Quantay annuations	On passenger aircraft only: 220 L
IMDG	~ · ·
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
· · · · · · · · · · · · · · · · · · ·	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml

(Contd. on page 10)

Printing date 07/19/2024

*

Reviewed on 07/19/2024

Trade name: Solvent-100, Light aromatic

(Contd. of page 9)

No further relevant inform	nmental regulations/legislation specific for the s nation available.	
· Sara		
• Section 355 (extremely he		
None of the ingredients is		
• Section 313 (Specific tox		
	imethylbenzene	
CAS: 98-82-8 Cumene		
CAS: 1330-20-7 Xylene (• /	
· TSCA (Toxic Substances		
Solvent naphtha (petroleu	m), light arom.	ACTIV
1,2,4-Trimethylbenzene		ACTIV
mesitylene		ACTIV
Cumene		ACTIV
1,2,3-Trimethylbenzene		ACTIV
Xylene (Xylol)		ACTIV
· Hazardous Air Pollutants		
CAS: 98-82-8 Cumene		
CAS: 1330-20-7 Xylene (Xylol)	
· Proposition 65		
• Chemicals known to caus	e cancer:	
CAS: 98-82-8 Cumene		
· Chemicals known to caus	e reproductive toxicity for females:	
None of the ingredients is	listed.	
· Chemicals known to caus	e reproductive toxicity for males:	
None of the ingredients is	listed.	
· Chemicals known to caus	e developmental toxicity:	
None of the ingredients is		
Caracita cardo car		
· Carcinogenic categories · EPA (Environmental Pro	testion (seven)	
	imethylbenzene	II
CAS: 108-67-8 mesityle	-	
CAS: 98-82-8 Cumene		D, CB
	imethylbenzene	II
CAS: 1330-20-7 Xylene (-	
5 (• /	I
• TLV (Threshold Limit Vo	·	A
CAS: 1330-20-7 Xylene (•	A
	titute for Occupational Safety and Health)	
None of the ingredients is	listed.	Globally Harmonized System (GHS).

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Solvent-100, Light aromatic

(Contd. of page 10)

· Hazard pictograms	(Contd. of page 10)
GHS02 GHS07 GHS08	
· Signal word Danger	
· Hazard-determining components of labeling:	
Solvent naphtha (petroleum), light arom.	
Xylene (Xylol)	
1,2,4-Trimethylbenzene	
Cumene	
· Hazard statements	
Flammable liquid and vapor.	
Causes skin irritation.	
Causes serious eye irritation.	
Suspected of causing cancer.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
• <i>Precautionary statements</i> Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/showe	<i>r</i> .
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if presen	at and easy to do.
Continue rinsing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool.	
Store in a weit-venitiatea place. Keep cool. Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulatio	ns
	(Contd. on page 12)

US

Printing date 07/19/2024

Reviewed on 07/19/2024

Trade name: Solvent-100, Light aromatic

(Contd. of page 11)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision: · Date of preparation / last revision Revision 1.2 07/18/2024: Reviewed SDS for accuracy. MH/STN 07/19/2024 / 1.0 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3

Skin Irritation 2: Skin corrosion/irritation - Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Carcinogenicity 2: Carcinogenicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

• * Data compared to the previous version altered.