Printing date 08/30/2021 Reviewed on 08/30/2021

1 Identification

· Product identifier

· Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

· Article number: HAC633

· Details of the supplier of the safety data sheet

Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



\*

#### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Hydrochloric Acid

Potassium Platinum Chloride

· Hazard statements

Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

(Contd. on page 2)

Printing date 08/30/2021 Reviewed on 08/30/2021

Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

(Contd. of page 1)

#### · Precautionary statements

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

*Specific treatment (see on this label).* 

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 0

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



\*3 *Health* = \*3

Fire = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 7647-01-0	Hydrochloric Acid	11.315%
CAS: 16921-30-5	Potassium Platinum Chloride	0.123%
· Table of Nonhazardous Ingredients		
CAS: 7732-18-5	Water	88.464%
CAS: 7791-13-1	Cobalt Chloride Hexahydrate	0.098%

#### 4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 3)

Printing date 08/30/2021 Reviewed on 08/30/2021

Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

(Contd. of page 2)

- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

Troccure fiction Crucia for Chemicus		
· PAC-1:		
CAS: 7647-01-0	Hydrochloric Acid	1.8 ppm
CAS: 7791-13-1	Cobalt Chloride Hexahydrate	$0.24 \ mg/m^3$
· PAC-2:		
CAS: 7647-01-0	Hydrochloric Acid	22 ppm
CAS: 7791-13-1	Cobalt Chloride Hexahydrate	25 mg/m³
· PAC-3:		
CAS: 7647-01-0	Hydrochloric Acid	100 ppm
CAS: 7791-13-1	Cobalt Chloride Hexahydrate	150 mg/m³

- US

Printing date 08/30/2021 Reviewed on 08/30/2021

Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

(Contd. of page 3)

#### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about protection against explosions and fires: Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- $\cdot$  *Specific end use*(s) *No further relevant information available.*

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:			
CAS: 7647-01-0 Hydrochloric Acid			
NIOSH RECOMENDED EXP LIMI Ceiling limit value: 7.0 mg/m3 mg/m³			
PEL Ceiling limit value: 7 mg/m³, 5 ppm			
REL Ceiling limit value: 7 mg/m³, 5 ppm			
TLV	Ceiling limit value: 2 ppm		
A4			
CAS: 16921-30-5 Potassium Platinum Chloride			
PEL	Long-term value: 0.002 mg/m³ as Pt		
REL	Long-term value: $0.002 \text{ mg/m}^3$ as $Pt$		
TLV	Long-term value: 0.002 mg/m³ as Pt		

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

Printing date 08/30/2021 Reviewed on 08/30/2021

Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

(Contd. of page 4)

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and c	hemical properties	
General Information		
Appearance:		
Form:	Liquid	
Color:	Yellow-brown	
Odor:	Odorless	
Odor threshold:	Not determined.	
pH-value at 20 °C (68 °F):	<2	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	100 °C (212 °F)	
Flash point:	Not applicable.	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	

Printing date 08/30/2021 Reviewed on 08/30/2021

Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

		(Contd. of page
Density at 20 °C (68 °F):	1.01637 g/cm³ (8.48161 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Water:	88.5 %	
VOC content:	0.00 %	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.2 %	
· Other information	No further relevant information available.	

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

	· LD/LC50	values tha	nt are relevant for classification:
	ATE (Acute Toxicity Estimate)		
	Oral	LD50	81,566 mg/kg
- 2			

CAS: 7791	CAS: 7791-13-1 Cobalt Chloride Hexahydrate	
Oral	LD50	500 mg/kg (ATE)
Inhalative	LC50/4h	1.5  mg/l  (ATE)

- · Primary irritant effect:
- · on the skin: Strong caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through inhalation.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 7)

Printing date 08/30/2021 Reviewed on 08/30/2021

Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

(Contd. of page 6)

Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 7791-13-1 Cobalt Chloride Hexahydrate

2B

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

TIC

Printing date 08/30/2021 Reviewed on 08/30/2021

Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

(Contd. of page 7)

Transport information	
· UN-Number	
· DOT, IMDG, IATA	UN3264
UN proper shipping name DOT	Corrosive liquid, acidic, inorganic, n.o.s. (Hydrochloric acid)
IMDG, IATA	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.
	(HYDROCHLORIC ACID)
Transport hazard class(es)	
DOT	
· DOI	
CORROSIVE	
8	
Class	8 Corrosive substances
Label	8
IMDG, IATA	
8	
Class	8 Corrosive substances
Label	8
Packing group	
· DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Corrosive substances
Hazard identification number (Kemler code):	
EMS Number:	F- $A$ , $S$ - $B$
Segregation groups	Acids
Stowage Category	B CHA CL CHAIR
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 30 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

Printing date 08/30/2021 Reviewed on 08/30/2021

Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

(Contd. of page 8)

· UN ''Model Regulation'':

UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S.

(HYDROCHLORIC ACID), 8, II

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 7791-13-1 Cobalt Chloride Hexahydrate

· TSCA (Toxic Substances Control Act):

WaterACTIVEHydrochloric AcidACTIVEPotassium Platinum ChlorideACTIVE

· Hazardous Air Pollutants

CAS: 7647-01-0 Hydrochloric Acid

CAS: 7791-13-1 Cobalt Chloride Hexahydrate

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS05

GHS08

Printing date 08/30/2021 Reviewed on 08/30/2021

Trade name: Color Standard 500 PCU for EZ1008 Colour Analyzer

(Contd. of page 9)

· Signal word Danger

· Hazard-determining components of labeling:

Hydrochloric Acid

Potassium Platinum Chloride

· Hazard statements

Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

· Precautionary statements

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

If experiencing respiratory symptoms: Call a poison center/doctor.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 0.0 08-30-2021: Creation date for SDS. STN

08/30/2021 / 1.0

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

 $DOT: \ US \ Department \ of \ Transportation$ 

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

 $Resp.\ Sens.\ 1: Respiratory\ sensitisation-Category\ 1$ 

\* \* Data compared to the previous version altered.