Printing date 11/20/2017

Reviewed on 11/20/2017

Product identifier		
Trade name: <u>Water St</u>		
<u>in n-But</u> Article number: GEN		
	• of the safety data sheet	
Manufacturer/Supplie		AQUA
Aqua Solutions, Inc. 6913 Highway 225		SOLUTIONS
DEER PARK, TX 7753 USA	36	
800-256-2586		
Information departme		
Technical Coordinator Sherman Nelson sherm	r nan@aquasolutions.org	
Emergency telephone	number:	
Chemtrec: 800-424-93 Canutec: 613-996-666		
Hazard(s) identific	cation	
Classification of the st		
GHS02 Flar	me	
	me Flammable liquid and vapor.	
	Flammable liquid and vapor.	
Flam. Liq. 3 H226	Flammable liquid and vapor.	
Flam. Liq. 3 H226	Flammable liquid and vapor.	
Flam. Liq. 3 H226	Flammable liquid and vapor.	
Flam. Liq. 3 H226 GHS05 Cor Eye Dam. 1 H318 GHS07	Flammable liquid and vapor. rosion Causes serious eye damage.	
Flam. Liq. 3 H226 Flam. Liq. 3 H226 GHS05 Corr Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302	Flammable liquid and vapor. rosion Causes serious eye damage. Harmful if swallowed.	
Flam. Liq. 3 H226 Flam. Liq. 3 H226 GHS05 Cor Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315	Flammable liquid and vapor. rosion Causes serious eye damage.	cause drowsiness or dizziness.
Flam. Liq. 3 H226 Flam. Liq. 3 H226 GHS05 Corr Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315 STOT SE 3 H335-H: Label elements	Flammable liquid and vapor. rosion Causes serious eye damage. Harmful if swallowed. Causes skin irritation. 336 May cause respiratory irritation. May	
Flam. Liq. 3 H226 Flam. Liq. 3 H226 GHS05 Cor Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315 STOT SE 3 H335-H. Label elements GHS label elements T	Flammable liquid and vapor. rosion Causes serious eye damage. Harmful if swallowed. Causes skin irritation. 336 May cause respiratory irritation. May	
Flam. Liq. 3 H226 Flam. Liq. 3 H226 GHS05 Corr Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315 STOT SE 3 H335-H: Label elements	Flammable liquid and vapor. rosion Causes serious eye damage. Harmful if swallowed. Causes skin irritation. 336 May cause respiratory irritation. May	cause drowsiness or dizziness. ing to the Globally Harmonized System (GHS).
Flam. Liq. 3 H226 Flam. Liq. 3 H226 GHS05 Cor Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315 STOT SE 3 H335-H. Label elements GHS label elements T	Flammable liquid and vapor. rosion Causes serious eye damage. Harmful if swallowed. Causes skin irritation. 336 May cause respiratory irritation. May	
Flam. Liq. 3 H226 Flam. Liq. 3 H226 GHS05 Cor Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315 STOT SE 3 H335-H3 Label elements GHS label elements T Hazard pictograms	Flammable liquid and vapor. rosion Causes serious eye damage. Harmful if swallowed. Causes skin irritation. 336 May cause respiratory irritation. May The product is classified and labeled accord.	
Flam. Liq. 3 H226 Flam. Liq. 3 H226 GHS05 Corr Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315 STOT SE 3 H335-H. Label elements GHS label elements T Hazard pictograms	Flammable liquid and vapor. rosion Causes serious eye damage. Harmful if swallowed. Causes skin irritation. 336 May cause respiratory irritation. May	
Flam. Liq. 3 H226 Flam. Liq. 3 H226 GHS05 Corr Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315 STOT SE 3 H335-H3 Label elements GHS label elements T Hazard pictograms	Flammable liquid and vapor. rosion Causes serious eye damage. Harmful if swallowed. Causes skin irritation. 336 May cause respiratory irritation. May The product is classified and labeled accord.	

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name: Water Standard 5% w/w in n-Butanol

	(Contd. of page 1)
	atements
	le liquid and vapor.
	f swallowed.
	in irritation.
	rious eye damage.
	e respiratory irritation. May cause drowsiness or dizziness.
	nary statements
-	y from heat/sparks/open flames/hot surfaces No smoking.
	ond container and receiving equipment.
	sion-proof electrical/ventilating/lighting/equipment.
	non-sparking tools.
	autionary measures against static discharge.
	athing dust/fume/gas/mist/vapors/spray
	roughly after handling.
Do not e	t, drink or smoke when using this product.
	outdoors or in a well-ventilated area.
Wear pi	tective gloves/protective clothing/eye protection/face protection.
If swalle	ved: Call a poison center/doctor if you feel unwell.
If on ski	(or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHA	ED: Remove person to fresh air and keep comfortable for breathing.
	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continu	
	ely call a poison center/doctor.
	reatment (see on this label).
Rinse m	
If skin i	itation occurs: Get medical advice/attention.
	ontaminated clothing and wash it before reuse.
	fire: Use for extinction: CO2, powder or water spray.
	well-ventilated place. Keep container tightly closed.
	well-ventilated place. Keep cool.
Store lo	
	f contents/container in accordance with local/regional/national/international regulations.
	tion system:
	tings (scale 0 - 4)
	Health = 3
3	Fire = 3
3	\mathbf{V} Reactivity = 0
· HMIS-I	tings (scale $0 - 4$)
HEALTH	*3 $Health = *3$
FIRE	3 Fire = 3
REACTIN	
· Other h	
	f PBT and vPvB assessment
	applicable.
· vPvB: N	t applicable.

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 2)

95.0%

5.0%

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 71-36-3 n-Butyl Alcohol

· Table of Nonhazardous Ingredients

CAS: 7732-18-5 Water

4 First-aid measures

· Description of first aid measures

- General information:
- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Wear protective equipment. Keep unprotected persons away.	
· Environmental precautions:	
Dilute with plenty of water.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing agent.	
Dispose contaminated material as waste according to item 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
	(Contd.

on page 4)

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 3)

60 ppm

800 ppm

8000** ppm

• Protective Action Criteria for Chemicals

• PAC-1:

CAS: 71-36-3 n-Butyl Alcohol

· PAC-2:

CAS: 71-36-3 n-Butyl Alcohol

• PAC-3:

CAS: 71-36-3 n-Butyl Alcohol

7 Handling and storage

· Handling:

· Precautions for safe handling No special precautions are necessary if used correctly.

 \cdot Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 71-36-3 n-Butyl Alcohol

PEL Long-term value: 300 mg/m³, 100 ppm

REL Ceiling limit value: 150 mg/m³, 50 ppm Skin

TLV Long-term value: 61 mg/m³, 20 ppm

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

· Personal protective equipment:

General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
Breathing equipment: Not required.

(Contd. on page 5)

us –

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 4)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Distinct
Odor threshold:	Not determined.
<i>pH-value at 20 °C (68 °F):</i>	7
Change in condition	
Melting point/Melting range:	-89 °C (-128.2 °F)
Boiling point/Boiling range:	117 °C (242.6 °F)
Flash point:	35 °C (95 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	340 °C (644 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name: Water Standard 5% w/w in n-Butanol

		(Contd. of page 5
Upper:	9.4 Vol %	
· Vapor pressure at 20 °C (68 °F):	6.7 hPa (5 mm Hg)	
· Density at 20 °C (68 °F):	0.8195 g/cm ³ (6.83873 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water at 20 °C (68 °F):	77 g/l	
· Partition coefficient (n-octanol/wate	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	95.0 %	
Water:	5.0 %	
VOC content:	95.00 %	
	778.5 g/l / 6.50 lb/gl	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

Oral	LD50	832 mg/kg (rat)
Dermal	LD50	3,579 mg/kg (rabbit)

CAS: 71-36-3 n-Butyl Alcohol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)
Inhalative	LC50/4 h	8,000 mg/l (rat)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

(Contd. on page 7)

US

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name: Water Standard 5% w/w

in n-Butanol

(Contd. of page 6)

- \cdot on the eye: Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.
- \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- \cdot Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number · DOT, IMDG, IATA

UN1120

(Contd. on page 8)

US

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name:	Water	Standard	5% w/w
	in n-B	utanol	

	(Contd. of pag
UN proper shipping name	
	Butanols solution
IMDG, IATA	BUTANOLS solution
Transport hazard class(es)	
DOT	
3	
Class	3 Elammable liquide
Label	3 Flammable liquids 3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	III
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	30
EMS Number:	F-E,S-D
Stowage Category	A
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 60 L
	On cargo aircraft only: 220 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
UN "Model Regulation":	UN 1120 BUTANOLS SOLUTION, 3, III

(Contd. on page 9)

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 8)

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 71-36-3 n-Butyl Alcohol

· TSCA (Toxic Substances Control Act):

n-Butyl Alcohol

Water

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

 \cdot Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 71-36-3 n-Butyl Alcohol

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

 Hazard-determining components of labeling: n-Butyl Alcohol
 Hazard statements

Flammable liquid and vapor. Harmful if swallowed.

Causes skin irritation.

Causes serious eye damage.

May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 10)

D

US

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 9) Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Rinse mouth. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

· Date of preparation / last revision 11-20-2017: review SDS for accuracy. STN Creation date for SDS 03-19-2014. STN 11/20/2017 / -· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value

(Contd. on page 11)

US

Printing date 11/20/2017

Reviewed on 11/20/2017

Trade name: Water Standard 5% w/w in n-Butanol

(Contd. of page 10)

US

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3