Printing date 07/25/2024 Reviewed on 07/25/2024

#### 1 Identification

· Product identifier

· Trade name: Mixed Organic Standard

150 mg/kg Each Component

· Article number: COR001

Details of the supplier of the safety data sheet

Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300

Canutec: 613-996-6666



### 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Isopropanol

· Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

(Contd. on page 2)

Reviewed on 07/25/2024 Printing date 07/25/2024

Trade name: Mixed Organic Standard 150 mg/kg Each Component

(Contd. of page 1)

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- Fire = 3
- REACTIVITY 0 Reactivity = 0
- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

#### 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous con	nponents:	
CAS: 67-63-0	Isopropanol	99.835%
· Table of Nonh	azardous Ingredients	
CAS: 71-23-8	n-propanol	0.015%
CAS: 75-65-0	tert-Butyl Alcohol	0.015%
CAS: 75-97-8	3,3-Dimethyl-2-butanone	0.015%
CAS: 78-92-2	sec-Butyl Alcohol 99%	0.015%
CAS: 78-93-3	Methyl Ethyl Ketone	0.015%
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	0.015%

(Contd. on page 3)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard
150 mg/kg Each Component

	(Cor	td. of page 2)
CAS: 108-11-2	4-methylpentan-2-ol	0.015%
CAS: 110-82-7		0.015%
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	0.015%
CAS: 565-61-7	3-Methyl-2-pentanone	0.015%
CAS: 592-76-7	1-Heptene	0.015%

#### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:			
CAS: 67-63-0	Isopropanol	400 µ	рт
CAS: 71-23-8	n-propanol	250 <sub>I</sub>	рт
		(Contd. on	nage 4)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard 150 mg/kg Each Component

CAS: 75-65-0	tout Destril Alachal	(Contd. of pag
	tert-Butyl Alcohol	150 ppi
CAS: 75-97-8	3,3-Dimethyl-2-butanone	0.45 pp
CAS: 78-92-2	sec-Butyl Alcohol 99%	150 ppi
CAS: 78-93-3	Methyl Ethyl Ketone	200 ppi
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	75 ppm
CAS: 110-82-7	Cyclohexane	300 ppi
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	230 ppi
CAS: 592-76-7	I-Heptene	130 ppi
PAC-2:		
CAS: 67-63-0	Isopropanol	2000* pp
CAS: 71-23-8	n-propanol	670 ppm
CAS: 75-65-0	tert-Butyl Alcohol	1,300 ppi
CAS: 75-97-8	3,3-Dimethyl-2-butanone	4.9 ppm
CAS: 78-92-2	sec-Butyl Alcohol 99%	220 ppm
CAS: 78-93-3	Methyl Ethyl Ketone	2700* pp
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	500 ppm
CAS: 110-82-7	Cyclohexane	1700* pp
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	830 ppm
CAS: 592-76-7	I-Heptene	1,400 pp
PAC-3:		
CAS: 67-63-0	Isopropanol	12000** pp
CAS: 71-23-8	n-propanol	4000* ppm
CAS: 75-65-0	tert-Butyl Alcohol	8000* ppm
CAS: 75-97-8	3,3-Dimethyl-2-butanone	30 ppm
CAS: 78-92-2	sec-Butyl Alcohol 99%	10000** pp
CAS: 78-93-3	Methyl Ethyl Ketone	4000* ppm
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	3000* ppm
CAS: 110-82-7	Cyclohexane	10000** pp
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	5000* ppm
CAS: 592-76-7	1-Hentene	8,700 ppm

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 5)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard
150 mg/kg Each Component

(Contd. of page 4)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

#### CAS: 67-63-0 Isopropanol

PEL Long-term value: 980 mg/m³, 400 ppm REL Short-term value: 1225 mg/m³, 500 ppm

Long-term value: 980 mg/m³, 400 ppm

TLV Short-term value: 400 ppm Long-term value: 200 ppm

BEI, A4

#### · Ingredients with biological limit values:

#### CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek

LD50: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

#### Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 6)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard
150 mg/kg Each Component

(Contd. of page 5)

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties	
· Information on basic physical and chemical p	properties

General Information	
· Appearance:	
Form:	Liquid
Color:	Clear
· Odor:	Alcohol-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	-89.5 °C (-129.1 °F)
Boiling point/Boiling range:	82 °C (179.6 °F)
· Flash point:	13 °C (55.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	2 Vol %
Upper:	12 Vol %
· Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
Density at 20 °C (68 °F):	0.785 g/cm³ (6.55083 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Fully miscible.

(Contd. on page 7)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard
150 mg/kg Each Component

		(Contd. of page
Partition coefficient (n-octanol/w	<b>ater):</b> Not determined.	
Viscosity:		
Dynamic at 20 °C (68 °F):	2.43 mPas	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	99.9 %	
VOC content:	99.93 %	
	784.4 g/l / 6.55 lb/gal	
Solids content:	0.0 %	
Other information	No further relevant information available.	

#### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

em emogeme e		
· IARC (Internat	tional Agency for Research on Cancer)	
CAS: 67-63-0	Isopropanol	3
CAS: 108-10-1	Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	2B
· NTP (National	Toxicology Program)	
None of the ing	redients is listed.	
· OSHA-Ca (Occ	cupational Safety & Health Administration)	
None of the ing	redients is listed.	

US -

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard
150 mg/kg Each Component

(Contd. of page 7)

### 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

#### 14 Transport information

· UN-Number · DOT, IMDG, IATA	UN1993
· UN proper shipping name · DOT	Flammable liquids, n.o.s. (Isopropanol
· IMDG, IATA	) FLAMMABLE LIQUID, N.O.S. (Isopropanol )

- · Transport hazard class(es)
- $\cdot DOT$



Class 3 Flammable liquids

(Contd. on page 9)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard 150 mg/kg Each Component

	(Contd. of pag
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user Hazard identification number (Kemler code)	Warning: Flammable liquids
EMS Number:	F-E,S-D
Stowage Category	B 2,5 2
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ISOPROPANOL), 3, II

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- ·Sara

	,	tremely hazardous substances):
	None of the ing	redients is listed.
	· Section 313 (Sp	pecific toxic chemical listings):
	CAS: 67-63-0	Isopropanol
	CAS: 75-65-0	tert-Butyl Alcohol
		sec-Butyl Alcohol 99%
		Methyl Isobutyl Ketone (4-Methyl-2-pentanone)
	CAS: 110-82-7	Cyclohexane
Ī		(Contd. on page 10)

J**u** 10)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard 150 mg/kg Each Component

TSCA (Toxic Substances Control Act):	To an
Isopropanol	ACTIV
n-propanol	ACTIV
tert-Butyl Alcohol	ACTIV
3,3-Dimethyl-2-butanone	ACTIV
sec-Butyl Alcohol 99%	ACTIV
Methyl Ethyl Ketone	ACTIV
Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	ACTIV
4-methylpentan-2-ol	ACTIV
Cyclohexane	ACTIV
2,2,4-Trimethylpentane (Iso-Octane)	ACTIV
3-Methyl-2-pentanone	ACTIV
1-Heptene	ACTIV
Hazardous Air Pollutants	
CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	
CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)	
Proposition 65	
Chemicals known to cause cancer:	
CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
CAS: 75-65-0 tert-Butyl Alcohol	
CAS: 78-93-3 Methyl Ethyl Ketone	1
CAS: 108-10-1 Methyl Isobutyl Ketone (4-Methyl-2-pentanone)	1
CAS: 110-82-7 Cyclohexane	1
CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)	1
TLV (Threshold Limit Value)	<u> </u>
CAS: 67-63-0 Isopropanol	
CAS: 71-23-8 n-propanol	1
CAS: 75-65-0 tert-Butyl Alcohol	
l .	
NIOSH-Ca (National Institute for Occupational Safety and Health)	

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard
150 mg/kg Each Component

(Contd. of page 10)

#### · Hazard pictograms





GHS02 GI

- · **Signal word** Danger
- · Hazard-determining components of labeling:

Isopropanol

· Hazard statements

Highly flammable liquid and vapor.

Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

*In case of fire: Use CO2, powder or water spray to extinguish.* 

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2, 07-25-2024: Reviewed SDS for accuracy. STN/GW 07/25/2024 / 1.1

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

(Contd. on page 12)

Printing date 07/25/2024 Reviewed on 07/25/2024

Trade name: Mixed Organic Standard 150 mg/kg Each Component

(Contd. of page 11)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

\* Data compared to the previous version altered.