Printing date 08/12/2024

Reviewed on 08/12/2024

DNS

# **1** Identification

- · Product identifier
- Trade name: <u>TBN Solvent</u>
- Article number: ND655
- $\cdot$  Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

- SC
- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org
   Emergency telephone number: Chemtrec: 800-424-9300
- Canutec: 613-996-6666

# 2 Hazard(s) identification

H225 Highly flammable liquid and vapor.
H361 Suspected of damaging fertility or the unborn child
H373 May cause damage to organs through prolonged o repeated exposure.
H304 May be fatal if swallowed and enters airways.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H317 May cause an allergic skin reaction.

Printing date 08/12/2024

Reviewed on 08/12/2024

Trade name: TBN Solvent

(Contd. of page 1) · Hazard pictograms GHS05 GHS07 GHS02 · Signal word Danger · Hazard-determining components of labeling: Toluene Acetic Acid, Glacial Acetone · Hazard statements Highly flammable liquid and vapor. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 3)

Printing date 08/12/2024

Reviewed on 08/12/2024

Trade name: TBN Solvent

(Contd. of page 2)

• Classification system: • NFPA ratings (scale 0 - 4)

 $\begin{array}{c} \textbf{Health} = 3\\ \textbf{Health} = 3\\ Fire = 3\\ Reactivity = 0 \end{array}$ 

· HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE3Fire = 3REACTIVITY0Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

· vPvB: Not applicable.

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 108-88-3	Toluene	56.841%
CAS: 64-19-7	Acetic Acid, Glacial	34.525%
CAS: 67-64-1	Acetone	8.634%

#### 4 First-aid measures

#### · Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

• After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 4)

Printing date 08/12/2024

Reviewed on 08/12/2024

### Trade name: TBN Solvent

· Special hazard	ls arising from the substance or mixture	(Contd. of page 3
	g or in case of fire poisonous gases are produced.	
• Advice for fire		
· Protective equi	<i>ipment:</i> Mouth respiratory protective device.	
6 Accidental r	elease measures	
	nutions, protective equipment and emergency procedures	
	ory protective device.	
• Environmental	e equipment. Keep unprotected persons away.	
	roduct to reach sewage system or any water course.	
	ive authorities in case of seepage into water course or sewage system.	
Dilute with plet	nty of water.	
	o enter sewers/ surface or ground water.	
	naterial for containment and cleaning up:	1
Absorb with liq Use neutralizin	nuid-binding material (sand, diatomite, acid binders, universal binders, sa	iwdust).
	ninated material as waste according to section 13.	
Ensure adequa		
· Reference to of		
	or information on safe handling.	
	or information on personal protection equipment.	
	for disposal information.	
· Protective Acti · PAC-1:	on Criteria for Chemicals	
· PAC-1: CAS: 108-88-3	Tolugno	67 ppm
CAS: 64-19-7	Acetic Acid, Glacial	5 ppm
CAS: 67-64-1	Acetone	200 ppm
· PAC-2:		
CAS: 108-88-3		560 ppm
CAS: 64-19-7	Acetic Acid, Glacial	35 ppm
CAS: 67-64-1		3200* ppm
· PAC-3:	Acetone	
CAS: 108-88-3	Acetone	3700* ppm
CAS: 108-88-3 CAS: 64-19-7	Acetone	3700* ppm 250 ppm

# 7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

(Contd. on page 5)

US

(Contd. of page 4)

## Safety Data Sheet acc. to OSHA HCS

Printing date 08/12/2024

Reviewed on 08/12/2024

#### Trade name: TBN Solvent

 $\cdot$  Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: Store in a cool location.

· Information about storage in one common storage facility: Not required.

- Further information about storage conditions:
- *Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.*

• Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

•	Control	parameters
---	---------	------------

· Components with limit values that require monitoring at the workplace:	
CAS: 108-88-3 Toluene	
PEL Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REL Short-term value: 560 mg/m <sup>3</sup> , 150 ppm Long-term value: 375 mg/m <sup>3</sup> , 100 ppm	
TLV Long-term value: 20 ppm BEI, OTO, A4	
CAS: 64-19-7 Acetic Acid, Glacial	
PEL Long-term value: 25 mg/m <sup>3</sup> , 10 ppm	
REL Short-term value: 37 mg/m <sup>3</sup> , 15 ppm Long-term value: 25 mg/m <sup>3</sup> , 10 ppm	
TLV Short-term value: 15 ppm Long-term value: 10 ppm	
CAS: 67-64-1 Acetone	
PEL Long-term value: 2400 mg/m <sup>3</sup> , 1000 ppm	
REL Long-term value: 590 mg/m <sup>3</sup> , 250 ppm	
TLV Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI	
· ·	(Contd. on page 6)

US -

Printing date 08/12/2024

Reviewed on 08/12/2024

#### Trade name: TBN Solvent

	(Contd. of page 5)
· Ingr	edients with biological limit values:
CAS	: 108-88-3 Toluene
BEI	0.02 mg/L
	LD50 Intraperitoneal: blood
	Time: prior to last shift of workweek
	LD50: Toluene
	0.03 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Toluene
	0.3 mg/g creatinine
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: o-Cresol with hydrolysis (background)
CAS	: 67-64-1 Acetone
BEI	25 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Acetone (nonspecific)
· Addi	tional information: The lists that were valid during the creation were used as basis.
	osure controls

ure controls

· Personal protective equipment:

• General protective and hygienic measures: *Keep away from foodstuffs, beverages and feed.* Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes. Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 7)

US

(Contd. of page 6)

# Safety Data Sheet acc. to OSHA HCS

Printing date 08/12/2024

Reviewed on 08/12/2024

Trade name: TBN Solvent

• Eye protection:



\*

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and chemical properties		
General Information		
Appearance:		
Form:	Liquid	
Color:	Clear	
Odor:	Characteristic	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	55.8-56.6 °C (132.4-133.9 °F)	
Flash point:	<-18 °C (<-0.4 °F)	
Flammability (solid, gaseous):	Highly flammable.	
Auto igniting:	465 °C (869 °F)	
Decomposition temperature:	Not determined.	
Ignition temperature:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.	
Explosion limits:		
Lower:	1.2 Vol %	
Upper:	17 Vol %	
Vapor pressure at 20 °C (68 °F):	29 hPa (21.8 mm Hg)	
Vapor pressure at 50 °C (122 °F):	124 hPa (93 mm Hg)	
Density at 20 °C (68 °F):	0.92447 g/cm³ (7.7147 lbs/gal)	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	

US

Printing date 08/12/2024

Reviewed on 08/12/2024

Trade name: TBN Solvent

	(Contd. of page 7
100.0 %	
91.37 %	
844.7 g/l / 7.05 lb/gal	
0.0 %	
No further relevant information available.	
	91.37 % 844.7 g/l / 7.05 lb/gal 0.0 %

### 10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

• *Incompatible materials:* No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

### **11 Toxicological information**

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 3,070 mg/kg (rabbit)

Primary irritant effect:

• on the skin: Caustic effect on skin and mucous membranes.

• on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: Sensitization possible through skin contact.

· Additional toxicological information:

*The product shows the following dangers according to internally approved calculation methods for preparations: Corrosive* 

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 108-88-3 Toluene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 9)

3

US

(Contd. of page 8)

#### Safety Data Sheet acc. to OSHA HCS

Printing date 08/12/2024

Reviewed on 08/12/2024

#### Trade name: TBN Solvent

**12 Ecological information** 

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:

• General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

#### **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Toluene, Acetic Acid, Glacial , Acetone)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Toluene, Acetic Acid, Glacial , Acetone)
Transport hazard class(es)	
DOT	
PLAMMABLE LOUD	
Class	3 Flammable liquids

Printing date 08/12/2024

Reviewed on 08/12/2024

Trade name: TBN Solvent

	(Contd. of page
Label	3
IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	
EMS Number:	F-E,S-C
Segregation groups	(SGG18) Alkalis
Stowage Category	B CHARLES CHAR
Stowage Code	SW2 Clear of living quarters.
Segregation Code	SG35 Stow "separated from" SGG1-acids
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
	On cargo aircraft only: 5 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{E}Q)$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE, ACETI
0	ACID, GLACIAL
	, ACETONE), 3, II

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

 Section 355 (extremely hazardous substances):

 None of the ingredients is listed.

 Section 313 (Specific toxic chemical listings):

 CAS: 108-88-3

 Toluene

 • TSCA (Toxic Substances Control Act):

 Toluene

 Acetic Acid, Glacial

 (Contd. on page 11)

 US

Printing date 08/12/2024

Reviewed on 08/12/2024

#### Trade name: TBN Solvent

Acetone	(Contd. of page 10 ACTIVE
· Hazardous Air Pollutants	
CAS: 108-88-3 Toluene	
· Proposition 65	
• Chemicals known to cause cancer:	
None of the ingredients is listed.	
• Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
• Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
CAS: 108-88-3 Toluene	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
CAS: 108-88-3 Toluene	II
CAS: 67-64-1 Acetone	Ι
· TLV (Threshold Limit Value)	
CAS: 108-88-3 Toluene	A4
CAS: 67-64-1 Acetone	A4
·NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
• <i>GHS label elements</i> The product is classified and labeled according to t • <i>Hazard pictograms</i>	he Globally Harmonized System (GHS).
$\land \land \land \land$	
< <u>⟨₩⟩</u> < <u>√</u> ⊮≥⟩< <u>↓</u> >< <u>↓</u> ><	

GHS02 GHS05 GHS07 GHS08

· Signal word Danger

#### · Hazard-determining components of labeling: Toluene Acetic Acid, Glacial Acetone · Hazard statements Highly flammable liquid and vapor. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment.

(Contd. on page 12)

Printing date 08/12/2024

Reviewed on 08/12/2024

#### Trade name: TBN Solvent

(Contd. of page 11) Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dusts or mists. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. *IF INHALED: Remove person to fresh air and keep comfortable for breathing.* If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

#### · Contact:

Date of Preparation / Last Revision:

 Date of preparation / last revision Revision 1.2, 08-12-2024: Reviewed SDS for accuracy. STN/GW 08/12/2024 / 1.1
 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

*VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent* 

LD50: Lethal dose, 50 percent

*PBT: Persistent, Bioaccumulative and Toxic* 

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

(Contd. on page 13)

US

Printing date 08/12/2024

Reviewed on 08/12/2024

#### Trade name: TBN Solvent

(Contd. of page 12)

US

Skin Corrosion 1B: Skin corrosion/irritation – Category 1B Eye Damage 1: Serious eye damage/eye irritation – Category 1 Sensitization - Skin 1: Skin sensitisation – Category 1 Toxic to Reproduction 2: Reproductive toxicity – Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2 Aspiration Hazard 1: Aspiration hazard – Category 1 • \* Data compared to the previous version altered.