Printing date 12/22/2022 Reviewed on 12/22/2022

1 Identification

· Product identifier

· Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

· Article number: MID033

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300

Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Specific Target Organ Toxicity - Single Exposure 2 H371 May cause damage to the central nervous system and the visual organs.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Methanol

· Hazard statements

Highly flammable liquid and vapor.

May cause damage to the central nervous system and the visual organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

 $Use\ explosion-proof\ electrical/ventilating/lighting/equipment.$

(Contd. on page 2)

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

(Contd. of page 1)

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Call a poison center/doctor.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	89.64%
CAS: 67-56-1	Methanol	4.98%
CAS: 67-63-0	Isopropanol	4.98%
· Table of Nonhazardous Ingredients		
CAS: 7732-18		0.4%
CAS: 7757-82	-6 Sodium Sulfate Anhydrous	0.0004%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 67-63-0	Isopropanol	400 ppm
CAS: 7757-82-6	Sodium Sulfate Anhydrous	9.8 mg/m³
· PAC-2:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppm
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 67-63-0	Isopropanol	2000* ppm
CAS: 7757-82-6	Sodium Sulfate Anhydrous	110 mg/m³
· PAC-3:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 67-56-1	Methanol	7200* ppm
CAS: 67-63-0	Isopropanol	12000** ppm
		(Contd. on page

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

 CAS: 7757-82-6
 Sodium Sulfate Anhydrous
 (Contd. of page 3)

 650 mg/m³
 650 mg/m³

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

BEI, A4

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Control parameters		
Components with limit values that require monitoring at the workplace:		
CAS:	AS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	
PEL	Long-term value: 1900 mg/m³, 1000 ppm	
REL	Long-term value: 1900 mg/m³, 1000 ppm	
TLV	Short-term value: 1000 ppm	
	A3	
CAS:	67-56-1 Methanol	
PEL	Long-term value: 260 mg/m³, 200 ppm	
REL	Short-term value: 325 mg/m³, 250 ppm	
	Long-term value: 260 mg/m³, 200 ppm	
	Skin	
TLV	Short-term value: 250 ppm	
	Long-term value: 200 ppm	
	Skin; BEI	
CAS:	67-63-0 Isopropanol	
PEL	Long-term value: 980 mg/m³, 400 ppm	
REL	Short-term value: 1225 mg/m³, 500 ppm	
	Long-term value: 980 mg/m³, 400 ppm	
TLV	Short-term value: 400 ppm	
	Long-term value: 200 ppm	

(Contd. on page 5)

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

(Contd. of page 4)

· Ingredients with biological limit values:

CAS: 67-56-1 Methanol

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

CAS: 67-63-0 Isopropanol

BEI 40 mg/L

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

- U

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate
4.0 ppm w/w in Denatured Alcohol

(Contd. of page 5)

Physical and chemical propert	ties	
Information on basic physical and chemical properties		
General Information	• •	
Appearance:		
Form:	Liquid	
Color:	Clear water white	
Odor:	Alcohol	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	78.3 °C (172.9 °F)	
Flash point:	11 °C (51.8 °F)	
Flammability (solid, gaseous):	Highly flammable.	
Ignition temperature:	425 °C (797 °F)	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.	
Explosion limits:		
Lower:	3.5 Vol %	
Upper:	19 Vol %	
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)	
Density at 20 °C (68 °F):	$0.79008 \ g/cm^3 \ (6.59322 \ lbs/gal)$	
Relative density	Not determined.	
Vapor density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octanol/wate	r): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	99.6 %	
Water:	0.4 %	
VOC content:	99.60 % 786.9 g/l / 6.57 lb/gal	
Solids content:	89.6 %	
Other information	No further relevant information available.	

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

(Contd. of page 6)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC30 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	2,008 mg/kg
Dermal	LD50	6,024 mg/kg

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.

Inhalative LC50/4h 60.2 mg/l

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

	8	
· IARC (International Agency for Research on Cancer)		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1
CAS: 67-63-0	Isopropanol	3
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

(Contd. on page 8)

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

(Contd. of page 7)

- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN1993 Flammable liquids, n.o.s. (Ethanol, Methanol, Isopropanol)
Flammable liquids, n.o.s. (Ethanol, Methanol, Isopropanol
,
FLAMMABLE LIQUID, N.O.S. (Ethanol, Methanol, Isopropano)
3 Flammable liquids 3
3 Flammable liquids
3 Frammable liquids 3
II
Not applicable.
Warning: Flammable liquids
(e): 33 F-E,S-D
•

(Contd. on page 9)

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot DOT$	
· Quantity limitations	On passenger aircraft/rail: 5 L
~ ,	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANC METHANOL, ISOPROPANOL
), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

Sur u
· Section 355 (extremely hazardous substances):
None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):
CAS: 67-56-1 Methanol

CAS: 67-63-0 Isopropanol	
· TSCA (Toxic Substances Control Act):	
Ethyl Alcohol, Absolute 200 Proof	ACTIVE
Methanol	ACTIVE
Isopropanol	ACTIVE

Water ACTIVE
Sodium Sulfate Anhydrous ACTIVE

· Hazardous Air Pollutants

CAS: 67-56-1 *Methanol*

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

(Contd. on page 10)

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

(Contd. of page 9)

CAS: 67-56-1 Methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof A3

CAS: 67-63-0 Isopropanol A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Methanol

· Hazard statements

Highly flammable liquid and vapor.

May cause damage to the central nervous system and the visual organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Call a poison center/doctor.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

(Contd. on page 11)

Printing date 12/22/2022 Reviewed on 12/22/2022

Trade name: Sodium Sulfate

4.0 ppm w/w in Denatured Alcohol

(Contd. of page 10)

· Date of preparation / last revision

Revision 0.0, 12-22-2022 Creation date for SDS. STN 12/22/2022

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Specific Target Organ Toxicity - Single Exposure 2: Specific target organ toxicity (single exposure) - Category 2

HS