Printing date 05/26/2021 Reviewed on 05/26/2021

1 Identification

· Product identifier

· Trade name: Benzene Std. 1000 ppm

w/w in Methanol

· Article number: BP332

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

STOT SE 1 H370 Causes damage to the central nervous system and the visual organs.



GHS07

Acute Tox. 4 H302 Harmful if swallowed.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Methanol (Methyl Alcohol)

Benzene

(Contd. on page 2)

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

(Contd. of page 1)

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system and the visual organs.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 3

Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 67-56-1 Methanol (Methyl Alcohol)

99.2%

(Contd. on page 3)

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

 CAS: 71-43-2
 Benzene
 (Contd. of page 2)

 0.8%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textit{Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
CAS: 67-56-1 Methanol (Methyl Alcohol)	530 ppm
CAS: 71-43-2 Benzene	52 ppm
·	(Contd. on page 4)

ı. on page 4,

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

	(Contd. of page 3)
· PAC-2:	
CAS: 67-56-1 Methanol (Methyl Alcohol)	2,100 ppm
CAS: 71-43-2 Benzene	800 ppm
· PAC-3:	
CAS: 67-56-1 Methanol (Methyl Alcohol)	7200* ppm
CAS: 71-43-2 Benzene	4000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· *Specific end use(s) No further relevant information available.*

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

· Cont	rol parameters
· Com	ponents with limit values that require monitoring at the workplace:
CAS	: 67-56-1 Methanol (Methyl Alcohol)
PEL	Long-term value: 260 mg/m³, 200 ppm
REL	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
TLV	Short-term value: 328 mg/m³, 250 ppm Long-term value: 262 mg/m³, 200 ppm Skin; BEI
CAS	: 71-43-2 Benzene
PEL	Short-term value: $15* \text{ mg/m}^3$, $5* \text{ ppm}$ Long-term value: $3* \text{ mg/m}^3$, $1* \text{ ppm}$ *table Z-2 for exclusions in $29\text{CFR}1910.1028(d)$
REL	Short-term value: 1 ppm Long-term value: 0.1 ppm See Pocket Guide App. A
	(Contd. on page 5)

(Contd. on page :

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

(Contd. of page 4)

TLV Short-term value: 8 mg/m³, 2.5 ppm Long-term value: 1.6 mg/m³, 0.5 ppm

Skin; BEI

· Ingredients with biological limit values:

CAS: 67-56-1 Methanol (Methyl Alcohol)

BEI 15 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methanol (background, nonspecific)

CAS: 71-43-2 Benzene

BEI 25 µg/g creatinine

LD50 Intraperitoneal: urine Time: end of shift Parameter

LD50: S-Phenylmercapturic acid (background

500 μg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: t,t-Muconic acid (background)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

(Contd. of page 5)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and o	chomical proporties
General Information	пенисы ргорегиез
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Methanol
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-97.8 °C (-144 °F)
Boiling point/Boiling range:	64 °C (147.2 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	455 °C (851 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.
Explosion limits:	
Lower:	5.5 Vol %
Upper:	44 Vol %
Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
Density at 20 °C (68 °F):	0.79158 g/cm³ (6.60574 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

	(Contd. of page 6
· Solvent content: Organic solvents: VOC content:	100.0 % 100.00 % 791.6 g/l / 6.61 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

mg/kg (rat)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· <i>LD/LC50</i>	values	that are	relevant	for ci	lassification:

ATE (Acui	te Toxicity	Estimate)
Oral	LD50	1,197-2,791

Dermal LD50 6,000 mg/kg (mouse)
Inhalative LC50/4h 129 mg/l (rat)

CAS: 67-56-1 Methanol (Methyl Alcohol)

Oral	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4h	3 mg/l (ATE)

CAS: 71-43-2 Benzene

Dermal LD50 5 mg/kg (ATE)

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research o

CAS: 71-43-2 Benzene

(Contd. on page 8)

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

(Contd. of page 7)

· NTP (National Toxicology Program)

CAS: 71-43-2 | Benzene | K

· OSHA-Ca (Occupational Safety & Health Administration)

CAS: 71-43-2 Benzene

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN1993

- · UN proper shipping name
- $\cdot DOT$

Flammable liquids, n.o.s. (Methanol)

· IMDG, IATA

FLAMMABLE LIQUID, N.O.S. (METHANOL)

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

(Contd. on page 9)

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

(Contd. of page 8) · Label 3 · IMDG, IATA 3 Flammable liquids · Class · Label · Packing group · DOT, IMDG, IATA II· Environmental hazards: · Marine pollutant: No · Special precautions for user Warning: Flammable liquids · Hazard identification number (Kemler code): 336 · EMS Number: F-E,S-E· Stowage Category В · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: $\cdot DOT$ · Quantity limitations On passenger aircraft/rail: 1 L On cargo aircraft only: 60 L · IMDG · Limited quantities (LQ) 1LCode: E2 · Excepted quantities (EQ) Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml · UN "Model Regulation": UN 1993 FLAMMABLE LIQUID, N.O.S. (METHANOL), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

All ingredients are listed.

· TSCA (Toxic Substances Control Act):

Methanol (Methyl Alcohol)ACTIVEBenzeneACTIVE

· Hazardous Air Pollutants

All ingredients are listed.

(Contd. on page 10)

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

(Contd. of page 9)

· Proposition 65

· Chemicals known to cause cancer:

CAS: 71-43-2 Benzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

CAS: 71-43-2 Benzene

· Chemicals known to cause developmental toxicity:

All ingredients are listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 71-43-2 Benzene

A, K/L

· TLV (Threshold Limit Value)

CAS: 71-43-2 Benzene

A1

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 71-43-2 Benzene

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

02 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Methanol (Methyl Alcohol)

Benzene

· Hazard statements

Highly flammable liquid and vapor.

Harmful if swallowed.

May cause genetic defects.

May cause cancer.

Causes damage to the central nervous system and the visual organs.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

(Contd. on page 11)

Printing date 05/26/2021 Reviewed on 05/26/2021

Trade name: Benzene Std. 1000 ppm w/w in Methanol

(Contd. of page 10)

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Creation date for SDS 11-18-2015. STN

Revision 1.0 05-07-2021: updated hazard information. STN

05/26/2021 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity - Category 4

Muta. 1B: Germ cell mutagenicity - Category 1B

Carc. 1A: Carcinogenicity - Category 1A

STOT SE 1: Specific target organ toxicity (single exposure) – Category 1