Printing date 08/07/2023

Reviewed on 08/07/2023

Identification	
Identification	
Product identifier	
Trade name: <u>BHT Standard</u>	
100.0 ppm W/V in A	<u>cetone</u>
Article number: FIS017	
Details of the supplier of the safet	ty data sheet
Manufacturer/Supplier:	
Aqua Solutions, Inc.	
6913 Highway 225	SOLUTIONS
DEER PARK, TX 77536 USA	
800-256-2586	
Information department:	
Technical Coordinator	
Sherman Nelson shermann@aquas	<i>solutions.org</i>
Emergency telephone number:	~
Chemtrec: 800-424-9300	
Canutec: 613-996-6666	
Hazard(s) identification	
GHS02 Flame	
GHS02 Flame	
	H225 Highly flammable liquid and vapor
GHS02 Flame Flammable Liquids 2	H225 Highly flammable liquid and vapor.
Flammable Liquids 2	H225 Highly flammable liquid and vapor.
	H225 Highly flammable liquid and vapor.
Flammable Liquids 2	
Flammable Liquids 2 GHS07 Eye Irritation 2A	H319 Causes serious eye irritation.
Flammable Liquids 2 GHS07 Eye Irritation 2A	
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - St Label elements	H319 Causes serious eye irritation. Ingle Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - S. Label elements GHS label elements The product i	H319 Causes serious eye irritation.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - St Label elements	H319 Causes serious eye irritation. Ingle Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - S. Label elements GHS label elements The product i	H319 Causes serious eye irritation. Ingle Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - S. Label elements GHS label elements The product i	H319 Causes serious eye irritation. Ingle Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - St Label elements GHS label elements The product in Hazard pictograms	H319 Causes serious eye irritation. Ingle Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - S. Label elements GHS label elements The product i	H319 Causes serious eye irritation. Ingle Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - St Label elements GHS label elements The product in Hazard pictograms	H319 Causes serious eye irritation. Ingle Exposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - So Label elements GHS label elements The product in Hazard pictograms GHS02 GHS07 Signal word Danger	H319 Causes serious eye irritation. Single Exposure 3 H336 May cause drowsiness or dizziness. This classified and labeled according to the Globally Harmonized System (GF
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - St Label elements GHS label elements The product in Hazard pictograms GHS02 GHS07	H319 Causes serious eye irritation. Single Exposure 3 H336 May cause drowsiness or dizziness. This classified and labeled according to the Globally Harmonized System (GF
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - St Label elements GHS label elements The product in Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components Acetone Hazard statements	H319 Causes serious eye irritation. Tingle Exposure 3 H336 May cause drowsiness or dizziness. Tis classified and labeled according to the Globally Harmonized System (GF of labeling:
Flammable Liquids 2 Flammable Liquids 2 Eye Irritation 2A Specific Target Organ Toxicity - S Label elements GHS label elements The product i Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components Acetone Hazard statements Highly flammable liquid and vapo	H319 Causes serious eye irritation. Tingle Exposure 3 H336 May cause drowsiness or dizziness. Tis classified and labeled according to the Globally Harmonized System (GF of labeling:
Flammable Liquids 2 Flammable Liquids 2 Eye Irritation 2A Specific Target Organ Toxicity - S Label elements GHS label elements The product i Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components Acetone Hazard statements Highly flammable liquid and vapor Causes serious eye irritation.	H319 Causes serious eye irritation. ingle Exposure 3 H336 May cause drowsiness or dizziness. is classified and labeled according to the Globally Harmonized System (GH of labeling: r.
Flammable Liquids 2 Flammable Liquids 2 Eye Irritation 2A Specific Target Organ Toxicity - S. Label elements GHS label elements The product i Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components Acetone Hazard statements Highly flammable liquid and vapor Causes serious eye irritation. May cause drowsiness or dizziness	H319 Causes serious eye irritation. ingle Exposure 3 H336 May cause drowsiness or dizziness. is classified and labeled according to the Globally Harmonized System (GH of labeling: r.
Flammable Liquids 2 Flammable Liquids 2 Eye Irritation 2A Specific Target Organ Toxicity - S. Label elements GHS label elements The product in Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components Acetone Hazard statements Highly flammable liquid and vapor Causes serious eye irritation. May cause drowsiness or dizziness Precautionary statements	H319 Causes serious eye irritation. Ingle Exposure 3 H336 May cause drowsiness or dizziness. is classified and labeled according to the Globally Harmonized System (GF of labeling: r. s.
Flammable Liquids 2 Flammable Liquids 2 Eye Irritation 2A Specific Target Organ Toxicity - S. Label elements GHS label elements The product i Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components Acetone Hazard statements Highly flammable liquid and vapor Causes serious eye irritation. May cause drowsiness or dizziness	H319 Causes serious eye irritation. Single Exposure 3 H336 May cause drowsiness or dizziness. is classified and labeled according to the Globally Harmonized System (GF of labeling: r. s. flames/hot surfaces No smoking.

Printing date 08/07/2023

Reviewed on 08/07/2023

Trade name: BHT Standard 100.0 ppm W/V in Acetone

	(Contd. of page 1)
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling. Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/sho	wer
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	·wcr.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pre	sent and easy to do
Continue rinsing.	sent and easy to do.
Call a poison center/doctor if you feel unwell.	
If eye irritation persists: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regula	ations.
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 2	
$\frac{3}{Fire = 3}$	
$\frac{2}{Reactivity} = 0$	
· HMIS-ratings (scale 0 - 4)	
HEALTH 2 $Health = 2$	
FIRE 3 Fire = 3	
$\begin{array}{c} \text{REACTIVITY} \\ \hline \end{array} \\ \hline $ \\ \hline } \\ \hline \end{array} \\ \hline \\ \\ \hline \end{array} \\ \hline \end{array} \\ \hline \\ \\ \end{array} \\ \hline \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \hline \\ \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \hline \end{array} \\ \\ \\ \hline \end{array} \\ \\ \\ \\	
· Other hazards	
· Results of PBT and vPvB assessment	
• PBT: Not applicable.	
• vPvB: Not applicable.	
2 Composition linformation on incrediente	
3 Composition/information on ingredients	
· Chemical characterization: Mixtures	
• Description: Mixture of the substances listed below with nonhazardous additions.	
· Dangerous components:	
CAS: 67-64-1 Acetone	99.99%
	11.1110
• Table of Nonhazardous Ingredients	

4 First-aid measures

· Description of first aid measures

CAS: 128-37-0 Butylated hydroxytoluene

- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Immediately rinse with water.

(Contd. on page 3)

0.01%

US

Printing date 08/07/2023

Reviewed on 08/07/2023

Trade name: BHT Standard 100.0 ppm W/V in Acetone

(Contd. of page 2)

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• After swallowing: If symptoms persist consult doctor.

• Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- \cdot Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures	
Wear protective equipment. Keep unprotected persons away.	
· Environmental precautions:	
Dilute with plenty of water.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to section 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
· PAC-1:	
CAS: 67-64-1 Acetone	200 ppm
• PAC-2:	
CAS: 67-64-1 Acetone	3200* ppm
• PAC-3:	
CAS: 67-64-1 Acetone	5700* ppm

7 Handling and storage

· Handling:

- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.

(Contd. on page 4)

[·]US

Printing date 08/07/2023

Reviewed on 08/07/2023

Trade name: BHT Standard 100.0 ppm W/V in Acetone

(Contd. of page 3)

Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 67-64-1 Acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 500 ppm Long-term value: 250 ppm A4, BEI

· Ingredients with biological limit values:

CAS: 67-64-1 Acetone

BEI 25 mg/L

LD50 Intraperitoneal: urine Time: end of shift LD50: Acetone (nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes.

Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 5)

Printing date 08/07/2023

Reviewed on 08/07/2023

Trade name: BHT Standard 100.0 ppm W/V in Acetone

(Contd. of page 4)

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Color: Clear · Odor: *Characteristic* · Odor threshold: Not determined. Not determined. · pH-value: · Change in condition Melting point/Melting range: -94.7 °C (-138.5 °F) 55 °C (131 °F) Boiling point/Boiling range: -17 °C (1.4 °F) · Flash point: · Flammability (solid, gaseous): Highly flammable. 465 °C (869 °F) • Auto igniting: · Decomposition temperature: Not determined. · Ignition temperature: Product is not selfigniting. · Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. · Explosion limits: Lower: 2.6 Vol % Upper: 13 Vol % · Vapor pressure at 20 °C (68 °F): 233 hPa (174.8 mm Hg) · Vapor pressure at 50 °C (122 °F): 800 hPa (600 mm Hg) • Density at 20 °C (68 °F): 0.79003 g/cm³ (6.5928 lbs/gal) · Relative density Not determined. · Vapor density Not determined. Not determined. · Evaporation rate (Contd. on page 6)

Printing date 08/07/2023

Reviewed on 08/07/2023

Trade name: BHT Standard 100.0 ppm W/V in Acetone

		(Contd. of page
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol)	'water): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	0.00~%	
	0.0 g/l / 0.00 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: Irritating effect.
- Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 128-37-0 Butylated hydroxytoluene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

3

Printing date 08/07/2023

Reviewed on 08/07/2023

Trade name: BHT Standard

100.0 ppm W/V in Acetone

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, IMDG, IATA	UN1993	
UN proper shipping name		
DOT	Flammable liquids, n.o.s. (Acetone)	
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Acetone)	
• Transport hazard class(es) • DOT		
Class	3 Flammable liquids	
Label	3	

Printing date 08/07/2023

Reviewed on 08/07/2023

Trade name: BHT Standard 100.0 ppm W/V in Acetone

	(Contd. of pag
IMDG, IATA	
A	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Ĥazard identification number (Kemler code)	: 33
EMS Number:	<i>F-E,<u>S-E</u></i>
Stowage Category	В
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities $(\widetilde{E}Q)$	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (ACETONE), 3, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

 • Section 355 (extremely hazardous substances):
 Image: Section 355 (extremely hazardous substances):

 None of the ingredients is listed.
 Image: Section 313 (Specific toxic chemical listings):

 None of the ingredients is listed.
 Image: Section 313 (Specific toxic chemical listings):

 None of the ingredients is listed.
 Image: Section 313 (Specific toxic chemical listings):

 None of the ingredients is listed.
 Image: Section 313 (Specific toxic chemical listings):

 None of the ingredients is listed.
 Image: ACTIVE

 Image: Section 313 (Specific toxic chemical listings):
 Image: ACTIVE

 None of the ingredients is listed.
 Image: ACTIVE

 Image: Section 313 (Specific toxic chemical listings):
 Image: ACTIVE

 Image: Section 313 (Specific toxic chemical listings):
 Image: ACTIVE

 Image: Section 313 (Specific toxic chemical listings):
 Image: ACTIVE

 Image: Section 313 (Specific toxic chemical listings):
 Image: ACTIVE

 Image: Section 313 (Specific toxic chemical listings):
 Image: ACTIVE

 Image: Section 313 (Specific toxic chemical listings):
 Image: ACTIVE

 Image: Section 314 (Specific toxic chemical listings):
 Image: ACTIVE

 Image: Section 314 (Specific toxic chemical listings):
 Image: ACTIVE

 Image: Section 314 (Specific toxic chemical listing

Printing date 08/07/2023

Reviewed on 08/07/2023

Trade name: BHT Standard

100.0 ppm W/V in Acetone

(Contd. of page 8)

I

· Proposition 65

 \cdot Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

 \cdot Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 67-64-1 Acetone

· TLV (Threshold Limit Value)

All components have the value A4.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Acetone · Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/sprav Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish.

(Contd. on page 10)

Printing date 08/07/2023

Reviewed on 08/07/2023

Trade name: BHT Standard 100.0 ppm W/V in Acetone

(Contd. of page 9)

Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

· Date of preparation / last revision Revision 1.0, 08/07/2023: Reviewed SDS for Accuracy.. STN Revision 0.0. 08-04-2016: creation date for SDS. STN 08/07/2023 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 • * Data compared to the previous version altered.