Printing date 08/04/2023

Reviewed on 08/04/2023

Product identifier	
Trade name: n-Butyl Mercaptan	
1000 ppm w/v as S	
Article number: EUR026	
Details of the supplier of the safety data sheet	
Manufacturer/Supplier:	A011A
Aqua Solutions, Inc.	
6913 Highway 225 DEER PARK, TX 77536	3010110113
USA	
800-256-2586	
Information department:	
Technical Coordinator	
Sherman Nelson shermann@aquasolutions.org	
<i>Emergency telephone number:</i> <i>Chemtrec: 800-424-9300</i>	
Canutec: 613-996-6666	
Hazard(s) identification	
Classification of the substance or mixture	
GHS02 Flame	
Flammable Liquids 2	H225 Highly flammable liquid and vapor.
A	H225 Highly flammable liquid and vapor.
Flammable Liquids 2 GHS08 Health hazard	H225 Highly flammable liquid and vapor.
GHS08 Health hazard	
GHS08 Health hazard Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child
GHS08 Health hazard Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged of
<i>GHS08 Health hazard</i> <i>Toxic to Reproduction 2</i> <i>Specific Target Organ Toxicity - Repeated Exposure 2</i>	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged or repeated exposure.
GHS08 Health hazard Toxic to Reproduction 2	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged of
GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged or repeated exposure.
<i>GHS08 Health hazard</i> <i>Toxic to Reproduction 2</i> <i>Specific Target Organ Toxicity - Repeated Exposure 2</i>	H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged or repeated exposure.
GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 GHS07	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways.
GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 Office GHS07 Skin Irritation 2	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.
GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 GHS07	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways.
GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 GHS07 Skin Irritation 2 Specific Target Organ Toxicity - Single Exposure 3 Label elements	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.
GHS08 Health hazardToxic to Reproduction 2Specific Target Organ Toxicity - Repeated Exposure 2Aspiration Hazard 1OutputGHS07Skin Irritation 2Specific Target Organ Toxicity - Single Exposure 3Label elementsGHS07	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.
GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 GHS07 Skin Irritation 2 Specific Target Organ Toxicity - Single Exposure 3 Label elements	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.
GHS08 Health hazardToxic to Reproduction 2Specific Target Organ Toxicity - Repeated Exposure 2Aspiration Hazard 1OutputGHS07Skin Irritation 2Specific Target Organ Toxicity - Single Exposure 3Label elementsGHS07	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.
GHS08 Health hazardToxic to Reproduction 2Specific Target Organ Toxicity - Repeated Exposure 2Aspiration Hazard 1OutputGHS07Skin Irritation 2Specific Target Organ Toxicity - Single Exposure 3Label elementsGHS07	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation.
GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 Image: Comparison of the system of the s	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.
GHS08 Health hazardToxic to Reproduction 2Specific Target Organ Toxicity - Repeated Exposure 2Aspiration Hazard 1OutputGHS07Skin Irritation 2Specific Target Organ Toxicity - Single Exposure 3Label elementsGHS07	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.
GHS08 Health hazard Toxic to Reproduction 2 Specific Target Organ Toxicity - Repeated Exposure 2 Aspiration Hazard 1 Image: Comparison of the system of the s	 H361 Suspected of damaging fertility or the unborn child H373 May cause damage to organs through prolonged orepeated exposure. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H336 May cause drowsiness or dizziness.

Printing date 08/04/2023

Trade name: n-Butyl Mercaptan 1000 ppm w/v as S Reviewed on 08/04/2023

(Contd. of page 1) · Hazard-determining components of labeling: Toluene *n*-*Heptane* · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 1Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE3Fire = 3REACTIVITY0Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

• *PBT:* Not applicable.

(Contd. on page 3)

^{- /}

Printing date 08/04/2023

Reviewed on 08/04/2023

Trade name: n-Butyl Mercaptan

1000 ppm w/v as S

(Contd. of page 2)

55.715% 44.003%

0.282%

· **vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous	components:
-------------	-------------

CAS: 108-88-3	Toluene
CAS: 142-82-5	n-Heptane

· Table of Nonhazardous Ingredients

CAS: 109-79-5 1-Butanethiol

4 First-aid measures

• Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.*
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

US -

Printing date 08/04/2023

Reviewed on 08/04/2023

Trade name: n-Butyl Mercaptan

1000 ppm w/v as S

Absorb with liq Dispose contan Ensure adequat • Reference to ot	her sections	(Contd. of page 3)
	or information on safe handling. or information on personal protection equipment.	
	for disposal information.	
	on Criteria for Chemicals	
· PAC-1:	·	
CAS: 108-88-3	Toluene	67 ppm
CAS: 142-82-5	n-Heptane	500 ppm
CAS: 109-79-5	1-Butanethiol	4.5 ppm
· PAC-2:		
CAS: 108-88-3	Toluene	560 ppm
CAS: 142-82-5	n-Heptane	830 ppm
CAS: 109-79-5	1-Butanethiol	50 ppm
· PAC-3:		
CAS: 108-88-3	Toluene	3700* ppm
CAS: 142-82-5	n-Heptane	5000* ppm
CAS: 109-79-5	1-Butanethiol	2,500 ppm

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
 Protect against electrostatic charges.
 Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities • Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 5)

[·] US ·

Printing date 08/04/2023

Reviewed on 08/04/2023

Trade name: n-Butyl Mercaptan 1000 ppm w/v as S

	(Contd. of page 4
	rol parameters
-	ponents with limit values that require monitoring at the workplace:
	108-88-3 Toluene
	Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift
	Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm
	Long-term value: 20 ppm BEI, OTO, A4
CAS:	142-82-5 n-Heptane
PEL	Long-term value: 2000 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ , 85 ppm Ceiling limit value: 1800* mg/m ³ , 440* ppm *15-min
	Short-term value: 500 ppm Long-term value: 400 ppm
· Ingre	edients with biological limit values:
CAS:	108-88-3 Toluene
BEI	0.02 mg/L
	LD50 Intraperitoneal: blood
	Time: prior to last shift of workweek
	LD50: Toluene
,	0.03 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Toluene
,	0.3 mg/g creatinine
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: o-Cresol with hydrolysis (background)
• Addit	tional information: The lists that were valid during the creation were used as basis.
· Expo	sure controls
	onal protective equipment:
· Gene	ral protective and hygienic measures:
Keep	away from foodstuffs, beverages and feed.
Imme	diately remove all soiled and contaminated clothing.
	hands before breaks and at the end of work.
	protective clothing separately.
	l contact with the skin.
	l contact with the eyes and skin.
	thing equipment:
	se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure us ratory protective device that is independent of circulating air.
	(Contd. on page

Printing date 08/04/2023

Reviewed on 08/04/2023

Trade name: n-Butyl Mercaptan 1000 ppm w/v as S

(Contd. of page 5)

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Sulfur odor
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 98 °C (208.4 °F)
Flash point:	-4 °C (24.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	215 °C (419 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits: Lower:	1.1 Vol %

Printing date 08/04/2023

Reviewed on 08/04/2023

Trade name: n-Butyl Mercaptan 1000 ppm w/v as S

		(Contd. of page 6)
Upper:	7 Vol %	
· Vapor pressure at 20 °C (68 °F):	48 hPa (36 mm Hg)	
· Density at 20 °C (68 °F):	0.77211 g/cm ³ (6.44326 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	99.7 %	
VOC content:	99.72 %	
	769.9 g/l / 6.43 lb/gal	
Solids content:	0.3 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

CAS: 108-88-3 Toluene

(Contd. on page 8)

3

US -

Printing date 08/04/2023

Reviewed on 08/04/2023

Trade name: n-Butyl Mercaptan 1000 ppm w/v as S

(Contd. of page 7)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

- Do not allow product to reach ground water, water course or sewage system.
- Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Toluene, n-Heptane)
IMDG	FLAMMABLE LIQUID, N.O.S. (Toluene, n-Heptane), MARIN
	POLLUTANT
IATA	FLAMMABLE LIQUID, N.O.S. (Toluene, n-Heptane)

Printing date 08/04/2023

Reviewed on 08/04/2023

Trade name: n-Butyl Mercaptan 1000 ppm w/v as S

	(Contd. of page 8)
· Transport hazard class(es)	
·DOT	
RAMMABLE LOUD	
3	
· Class	3 Flammable liquids
·Label	3
·IMDG	
· Class	2 Elammable liquide
· Label	3 Flammable liquids 3
• IATA	
· Class	3 Flammable liquids
· Label	3
· Packing group · DOT, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: n-
· Marine pollutant:	Heptane Yes
	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
• Hazard identification number (Kemler code): • EMS Number:	
· EMIS Number: · Stowage Category	F-E, <u>S-E</u> B
• Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
• Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	
\cdot Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
	(Contd. on page 10)

Printing date 08/04/2023

Reviewed on 08/04/2023

Trade name: n-Butyl Mercaptan 1000 ppm w/v as S

(Contd. of page 9)

· UN ''Model Regulation'':

UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUENE, N-HEPTANE), 3, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara

Sara	
· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
CAS: 108-88-3 Toluene	
· TSCA (Toxic Substances Control Act):	
Toluene	ACTIVE
n-Heptane	ACTIVE
1-Butanethiol	ACTIVE
· Hazardous Air Pollutants	
CAS: 108-88-3 Toluene	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
• Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
CAS: 108-88-3 Toluene	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
CAS: 108-88-3 Toluene	II
CAS: 142-82-5 n-Heptane	D

· TLV (Threshold Limit Value)

CAS: 108-88-3 Toluene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



(Contd. on page 11)

A4

Printing date 08/04/2023

Trade name: n-Butyl Mercaptan 1000 ppm w/v as S Reviewed on 08/04/2023

· Signal word Danger	(Contd. of page 10)
· Hazard-determining components of labeling:	
Toluene	
n-Heptane	
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
· Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/sho	wer.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regula	itions.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

• Department issuing SDS: Environment protection department.

· Contact:

· Date of preparation / last revision

Revision 1.0, 08/04/2023: Reviewed SDS for Accuracy.. STN Revision 0.0, 09-19-2016: creation date for SDS. STN 08/04/2023

• Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 12)

⁻ US

US

Safety Data Sheet acc. to OSHA HCS

Printing date 08/04/2023

Trade name: n-Butyl Mercaptan 1000 ppm w/v as S Reviewed on 08/04/2023

	(Contd. of page 11)
DOT: US Department of Transportation	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
NIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
BEI: Biological Exposure Limit	
Flammable Liquids 2: Flammable liquids – Category 2	
Skin Irritation 2: Skin corrosion/irritation – Category 2	
Toxic to Reproduction 2: Reproductive toxicity – Category 2	
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3	
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2	
Aspiration Hazard 1: Aspiration hazard – Category 1	
• * Data compared to the previous version altered.	
······································	