US

Safety Data Sheet acc. to OSHA HCS

Printing date 10/19/2023

*

Reviewed on 10/19/2023

Product identifier Trade name: <u>Vinyl Acetate 100.0 ppm w/w</u> <u>in Isooctane</u> Article number: SH1019 Details of the supplier of the safety data she Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225	ret	
in Isooctane Article number: SHI019 Details of the supplier of the safety data she Manufacturer/Supplier: Aqua Solutions, Inc.	ret	
Article number: SHI019 Details of the supplier of the safety data she Manufacturer/Supplier: Aqua Solutions, Inc.	ret	
Details of the supplier of the safety data she Manufacturer/Supplier: Aqua Solutions, Inc.	ret	
Manufacturer/Supplier: Aqua Solutions, Inc.	et	
D913 Highway 225		
DEER PARK, TX 77536	SOLUTIONS	
USA		
800-256-2586		
Information department: Technical Coordinator		
Sherman Nelson shermann@aquasolutions.c	org	
Emergency telephone number:	-	
Chemtrec: 800-424-9300 Canutec: 613-996-6666		
Hazard(s) identification		
Classification of the substance or mixture		
GHS02 Flame		
GHISO2 I lume		
Flammable Liquids 2	H225 Highly flammable liquid and vapor.	
		• •
GHS08 Health hazard		
Aspiration Hazard 1	H304 May be fatal if swallowed and enters airways.	
\mathbf{A}		
GHS07		
$\mathbf{\nabla}$		
Skin Irritation 2	H315 Causes skin irritation.	
	osure 3 H336 May cause drowsiness or dizziness.	
Label elements CHS label elements The product is classified	d and labeled according to the Globally Harmonized System (Gi	HS
Hazard pictograms	a una abbiea accoraing to the Otobally Harmonized System (Of	115
$\wedge \wedge \wedge$		
<u><%><!-- --><&></u>		
\checkmark \checkmark \checkmark		
GHS02 GHS07 GHS08		
Signal word Danger		
Hazard-determining components of labeling	g:	
2,2,4-Trimethylpentane (Iso-Octane)		
Hazard statements		

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: Vinyl Acetate 100.0 ppm w/w in Isooctane

Causaa ahin innitation	(Contd. of page 1)
Causes skin irritation.	
May cause drowsiness or dizziness.	
May be fatal if swallowed and enters airways.	
• Precautionary statements Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower	•
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Call a poison center/doctor if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	is.
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 1	
Fire = 3	
$\frac{1}{10} Reactivity = 0$	
· HMIS-ratings (scale 0 - 4)	
HEALTH 1 Health -1	
FIRE 3 Fire = 3	
REACTIVITY 0 Reactivity = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• PBT : Not applicable.	
• vPvB : Not applicable.	
3 Composition/information on ingredients	
· Chemical characterization: Mixtures	
• Description: Mixture of the substances listed below with nonhazardous additions.	
Danagrous components.	

· Dangerous components:

*

CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

(Contd. on page 3)

99.99%

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: Vinyl Acetate 100.0 ppm w/w in Isooctane

(Contd. of page 2)

0.01%

· Table of Nonhazardous Ingredients

CAS: 108-05-4 Vinyl Acetate, Reagent Grade

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- \cdot Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

Wear protective equipment. Keep unprotected persons away.	
· Environmental precautions:	
Do not allow product to reach sewage system or any water course.	
Inform respective authorities in case of seepage into water course or sewage system.	
Do not allow to enter sewers/ surface or ground water.	
• Methods and material for containment and cleaning up:	
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Dispose contaminated material as waste according to section 13.	
Ensure adequate ventilation.	
· Reference to other sections	
See Section 7 for information on safe handling.	
See Section 8 for information on personal protection equipment.	
See Section 13 for disposal information.	
· Protective Action Criteria for Chemicals	
· PAC-1:	
CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)	230 ppm
CAS: 108-05-4 Vinyl Acetate, Reagent Grade	6.7 ppm
· PAC-2:	
• PAC-2:CAS: 540-84-12,2,4-Trimethylpentane (Iso-Octane)	830 ppm

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: Vinyl Acetate 100.0 ppm w/w in Isooctane

CAS: 108-05-4	Vinyl Acetate, Reagent Grade	(Contd. of page 3) 36 ppm
· PAC-3:		
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	5000* ppm
CAS: 108-05-4	Vinyl Acetate, Reagent Grade	180 ppm

7 Handling and storage

· Handling:

- *Precautions for safe handling* Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- *Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.*
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

- TLV Long-term value: 300 ppm
- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

(Contd. on page 5)

[·]US

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: Vinyl Acetate 100.0 ppm w/w in Isooctane

(Contd. of page 4)

US

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

Physical and chemical proper	ties
Information on basic physical and o	chemical properties
General Information	* *
Appearance:	
Form:	Liquid
Color:	Colorless
Odor:	Sweetish
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-107.4 °C (-161.3 °F)
Boiling point/Boiling range:	98-99 °C (208.4-210.2 °F)
Flash point:	-8 °C (17.6 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	410 °C (770 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	6 Vol %
Vapor pressure at 20 °C (68 °F):	15 hPa (11.3 mm Hg)
<i>Density at 20 °C (68 °F):</i>	0.692 g/cm ³ (5.77474 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: Vinyl Acetate 100.0 ppm w/w in Isooctane

		(Contd. of page
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wo	iter): Not determined.	
· Viscosity:		
<i>Dynamic at 20 •C (68 •F):</i>	0.51 mPas	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	99.99 %	
	691.9 g/l / 5.77 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- \cdot on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 108-05-4 Vinyl Acetate, Reagent Grade

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

(Contd. on page 7)

2B

US

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: Vinyl Acetate 100.0 ppm w/w in Isooctane

(Contd. of page 6)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number		
· DOT, IMDG, IATA	UN1262	
· UN proper shipping name		
$\cdot DOT$	Octanes	
· IMDG, IATA	OCTANES	
PLAMARILE LOUD		
· Class	3 Flammable liquids	
· Label	3	

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: Vinyl Acetate 100.0 ppm w/w in Isooctane

	(Contd. of page
IMDG, IATA	
Class Label	3 Flammable liquids
Labei	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substances: Octane
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler cod	de): 33
EMS Number:	F- E , S - D
Stowage Category	В
Transport in bulk according to Annex II of	of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (\widetilde{EQ})	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN ''Model Regulation'':	UN 1262 OCTANES, 3, II

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

· Section 355 (extremely hazardous substances):	
CAS: 108-05-4 Vinyl Acetate, Reagent Grade	
· Section 313 (Specific toxic chemical listings):	
CAS: 108-05-4 Vinyl Acetate, Reagent Grade	
· TSCA (Toxic Substances Control Act):	
2,2,4-Trimethylpentane (Iso-Octane)	ACTIVE
Vinyl Acetate, Reagent Grade	ACTIVE
· Hazardous Air Pollutants	
All ingredients are listed.	
	(Contd. on page 9)

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: Vinyl Acetate 100.0 ppm w/w in Isooctane

(Contd. of page 8)

Π

A3

US

· Proposition 65

 \cdot Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

 \cdot Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

· TLV (Threshold Limit Value)

CAS: 108-05-4 Vinyl Acetate, Reagent Grade

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: 2,2,4-Trimethylpentane (Iso-Octane) · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. (Contd. on page 10)

Printing date 10/19/2023

Reviewed on 10/19/2023

Trade name: Vinyl Acetate 100.0 ppm w/w in Isooctane

(Contd. of page 9)

Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice/attention.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1 • * Data compared to the previous version altered.

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department. · Contact: Date of Preparation / Last Revision: · Date of preparation / last revision Revision 0.0, 10-19-2023: creation date for SDS STN 10/19/2023 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3