Printing date 08/07/2023 Reviewed on 08/07/2023

1 Identification

· Product identifier

· Trade name: PXA A9+

Blend 2

· Article number: EXX185

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



 $GHS02\ Flame$

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1A H340 May cause genetic defects.

Carcinogenicity 1B H350 May cause cancer.

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



GHS05 Corrosion

Eye Damage 1 H318 Causes serious eye damage.



GHS07

Acute Toxicity - Inhalation 4 H332 Harmful if inhaled.
Skin Irritation 2 H315 Causes skin irritation.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 1)

· Hazard pictograms









GHS02

GHS05 GHS07

· Signal word Danger

· Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom.

m-Xylenol (2,4-Dimethylphenol)

1,2,4-Trimethylbenzene

Biphenyl

Naphthalene

Xylene (*Xylol*)

Solvent naphtha (petroleum), heavy arom.

cumene

· Hazard statements

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause genetic defects.

May cause cancer.

May cause respiratory irritation.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

(Contd. on page 3)

Reviewed on 08/07/2023 Printing date 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 2)

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*3 *Health* = *3 Fire = 2REACTIVITY 0 Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable. · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous compo	onents:	
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	52.46%
CAS: 92-52-4	Biphenyl	18.04%
CAS: 95-63-6	1,2,4-Trimethylbenzene	16.78%
CAS: 64742-94-5	Solvent naphtha (petroleum), heavy arom.	13.12%
CAS: 1330-20-7	Xylene (Xylol)	10.0%
CAS: 105-67-9	m-Xylenol (2,4-Dimethylphenol)	4.51%
CAS: 81749-29-3	1-Phenyl-1-(2,6-xylyl)ethane	4.51%
CAS: 91-20-3	Naphthalene	1.33%
CAS: 95-48-7	o-cresol	0.9%
CAS: 98-82-8	cumene	0.64%
· Table of Nonhaza	rdous Ingredients	
CAS: 65-85-0	Benzoic Acid, Reagent ACS Grade	0.23%
CAS: 1330-20-7	Xylene (Xylol)	0.22%
CAS: 91-57-6	2-Methylnaphthalene	0.2%
CAS: 108-95-2	Phenol	0.09%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

(Contd. on page 4)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 3)

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

 ${\it Inform\ respective\ authorities\ in\ case\ of\ seepage\ into\ water\ course\ or\ sewage\ system}.$

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 92-52-4	Biphenyl	0.87 ppm
CAS: 95-63-6	1,2,4-Trimethylbenzene	140 ppm
CAS: 1330-20-7	Xylene (Xylol)	130 ppm
CAS: 105-67-9	m-Xylenol (2,4-Dimethylphenol)	6.9 mg/m³
CAS: 91-20-3	Naphthalene	15 ppm
CAS: 98-82-8	cumene	50 ppm
CAS: 65-85-0	Benzoic Acid, Reagent ACS Grade	13 mg/m³
CAS: 91-57-6	2-Methylnaphthalene	9 mg/m³

(Contd. on page 5)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

CAS: 108-95-2	Phenol	15 ppm
PAC-2:		
CAS: 92-52-4	Biphenyl	9.6 ppm
CAS: 95-63-6	1,2,4-Trimethylbenzene	360 ppm
CAS: 1330-20-7	Xylene (Xylol)	920* ppm
CAS: 105-67-9	m-Xylenol (2,4-Dimethylphenol)	76 mg/m³
CAS: 91-20-3	Naphthalene	83 ppm
CAS: 98-82-8	cumene	300 ppm
CAS: 65-85-0	Benzoic Acid, Reagent ACS Grade	140 mg/m
CAS: 91-57-6	2-Methylnaphthalene	54 mg/m^3
CAS: 108-95-2	Phenol	23 ррт
PAC-3:		·
CAS: 92-52-4	Biphenyl	300 ppm
CAS: 95-63-6	1,2,4-Trimethylbenzene	480 ppm
CAS: 1330-20-7	Xylene (Xylol)	2500* ppn
CAS: 105-67-9	m-Xylenol (2,4-Dimethylphenol)	460 mg/m ³
CAS: 91-20-3	Naphthalene	500 ppm
CAS: 98-82-8	cumene	730 ppm
CAS: 65-85-0	Benzoic Acid, Reagent ACS Grade	830 mg/m ³
CAS: 91-57-6	2-Methylnaphthalene	320 mg/m ³
CAS: 108-95-2	Phenol	200 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- $\cdot \textit{Requirements to be met by storerooms and receptacles:} \ \textit{No special requirements}.$
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see section 7.

(Contd. on page 6)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 5)

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At th	is time, the other constituents have no known exposure limits.
	92-52-4 Biphenyl
PEL	Long-term value: 1 mg/m³, 0.2 ppm
REL	Long-term value: 1 mg/m³, 0.2 ppm
TLV	Long-term value: 0.2 ppm
CAS.	· 95-63-6 1,2,4-Trimethylbenzene
REL	Long-term value: 125 mg/m³, 25 ppm
TLV	Long-term value: 10 ppm A4
CAS.	: 1330-20-7 Xylene (Xylol)
PEL	Long-term value: 435 mg/m³, 100 ppm
REL	Short-term value: 655 mg/m³, 150 ppm Long-term value: 435 mg/m³, 100 ppm
TLV	Long-term value: 20 ppm BEI, A4
CAS.	: 105-67-9 m-Xylenol (2,4-Dimethylphenol)
TLV	Long-term value: 1* ppm *inh. fraction+vapor; DSEN, A3
CAS.	91-20-3 Naphthalene
PEL	Long-term value: 50 mg/m³, 10 ppm
REL	Short-term value: 75 mg/m³, 15 ppm Long-term value: 50 mg/m³, 10 ppm
TLV	Long-term value: 10 ppm Skin; BEI, A3
CAS.	95-48-7 o-cresol
PEL	Long-term value: 22 mg/m³, 5 ppm Skin
REL	Long-term value: 10 mg/m³, 2.3 ppm
TLV	Long-term value: 20* mg/m³ Skin;*as inhalable fraction and vapor, A4
CAS.	· 98-82-8 cumene
PEL	Long-term value: 245 mg/m³, 50 ppm Skin
REL	Long-term value: 245 mg/m³, 50 ppm Skin
TLV	Long-term value: 5 ppm A3
	(Contd. on pag

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 6)

· Ingredients with biological limit values:

CAS: 1330-20-7 Xylene (Xylol)

BEI 1.5 g/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methylhippuric acids

CAS: 91-20-3 Naphthalene

BEI -

LD50 Intraperitoneal: -

Time: end of shift

LD50: 1-Naphthol with hydrolysis + 2-Naphthol with hydrolysis (Nq,Ns)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 7)

Physical and chemical proper	ties — — — — — — — — — — — — — — — — — — —
· Information on basic physical and o	chemical properties
· General Information	
· Appearance:	
Form:	Liquid
Color:	Not determined.
· Odor:	Aromatic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	162 °C (323.6 °F)
· Flash point:	45 °C (113 °F)
· Flammability (solid, gaseous):	Flammable.
Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
EIi lii4	1
Explosion limits: Lower:	Not determined.
Lower: Upper:	Not determined.
· Vapor pressure:	Not determined.
Density at 20 °C (68 °F):	$0.88 \text{ g/cm}^3 (7.3436 \text{ lbs/gal})$
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	81.1 %
VOC content:	81.09 %
	713.6 g/l / 5.96 lb/gal
Solids content:	18.8 %
Other information	No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

(Contd. on page 9)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 8)

- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	8,649 mg/kg (rat)
	LD50	6,926 mg/kg
Inhalative	LC50/4h	>12.5 mg/l

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Strong irritant with the danger of severe eye injury.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
CAS: 1330-20-7	Xylene (Xylol)	3
CAS: 91-20-3	Naphthalene	2B
CAS: 98-82-8	cumene	2B
CAS: 1330-20-7	Xylene (Xylol)	3
CAS: 108-95-2	Phenol	3
· NTP (National 7	Taxicalagy Program)	

,		 ·	
CAS: 91-20-3	Naphthalene		R
CAS: 98-82-8	cumene		R

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- $\cdot \textbf{\textit{Aquatic toxicity:}} \ \textit{No further relevant information available}.$
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 10)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 9)

- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

1 4 700		C	
14 Trans	nort in	torma	non
I I I I WILL	DOLD OIL	, or much	

· UN-Number · DOT, IMDG, IATA	UN1993
· UN proper shipping name	
$\cdot DOT$	Flammable liquids, n.o.s. (Solvent naphtha (petroleum), light
	arom., 1,2,4-Trimethylbenzene, Xylene (Xylol))
\cdot IMDG	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum),
	light arom., 1,2,4-Trimethylbenzene, Xylene (Xylol), Biphenyl, m-
	Xylenol (2,4-Dimethylphenol), Naphthalene, cumene, 2-
	Methylnaphthalene), MARINE POLLUTANT
\cdot IATA	FLAMMABLE LIQUID, N.O.S. (Solvent naphtha (petroleum),
	light arom., 1,2,4-Trimethylbenzene, Xylene (Xylol))

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

· Label

 \cdot *IMDG*





· Class 3 Flammable liquids

(Contd. on page 11)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

Flammable liquids II Product contains environmentally hazardous substance liphenyl es ymbol (fish and tree)
II Product contains environmentally hazardous substance Siphenyl Tes
Product contains environmentally hazardous substance Siphenyl Ses
Product contains environmentally hazardous substance Siphenyl Ses
Product contains environmentally hazardous substance Siphenyl Ses
iphenyl es
es
ymbol (fish and tree)
Varning: Flammable liquids
0
<i>S-E,<u>S-E</u></i>
lot applicable.
n passenger aircraft/rail: 60 L
On cargo aircraft only: 220 L
L
Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml
IN 1993 FLAMMABLE LIQUID, N.O.S. (SOLVENT NAPHTI
PETROLEUM), LIGHT AROM., 1,2,4-TRIMETHYLBENZEN YLENE (XYLOL)), 3, III

15 Regulatory information

 $\cdot \textit{Safety, health and environmental regulations/legislation specific for the substance or \textit{mixture}}\\$

Sara

· Section 355 (extremely hazardous substances):			
CAS: 95-48-7	o-cresol		
CAS: 108-95-2	Phenol		
· Section 313 (Specific toxic chemical listings):			
CAS: 92-52-4	Biphenyl		
CAS: 95-63-6	1,2,4-Trimethylbenzene		
CAS: 1330-20-7	Xylene (Xylol)		

(Contd. on page 12)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

CAS: 105-67-9	m-Xylenol (2,4-Dimethylphenol)	(Contd. of page 1
CAS: 91-20-3	Naphthalene	
CAS: 95-48-7	o-cresol	
CAS: 98-82-8	cumene	
CAS: 1330-20-7	Xylene (Xylol)	
	Phenol	
· TSCA (Toxic Su	bstances Control Act):	
,	(petroleum), light arom.	ACTIVI
Biphenyl	pen steining, tig.ii di emi	ACTIVI
1,2,4-Trimethylbenzene		ACTIV
<u> </u>	(petroleum), heavy arom.	ACTIV
Xylene (Xylol)	M	ACTIV
m-Xylenol (2,4-L	Dimethylphenol)	ACTIVI
Naphthalene		ACTIV
o-cresol		ACTIV
cumene		ACTIV
Benzoic Acid, Reagent ACS Grade		ACTIV
2-Methylnaphthalene		ACTIV
Phenol		ACTIV
Hazardous Air P	Collutants	
	Biphenyl	
CAS: 1330-20-7		
CAS: 91-20-3	Naphthalene	
CAS: 95-48-7	o-cresol	
CAS: 98-82-8	cumene	
CAS: 108-95-2	Phenol	
Proposition 65		
· Chemicals know	n to cause cancer:	
CAS: 91-20-3 No	aphthalene	
CAS: 98-82-8 cu	ımene	
· Chemicals know	n to cause reproductive toxicity for females:	
None of the ingre		
· Chemicals know	n to cause reproductive toxicity for males:	
None of the ingre		
<u> </u>	n to cause developmental toxicity:	
None of the ingre	<u> </u>	
Carcinogenic car	tegories ental Protection Agency)	
CAS: 92-52-4	Biphenyl	SC
CAS: 92-32-4 CAS: 95-63-6	1,2,4-Trimethylbenzene	II
CAS: 93-03-0 CAS: 1330-20-7	· · · · · · · · · · · · · · · · · · ·	II I
CAS: 1330-20-7		
CAS. 31-20-3	Naphthalene	(Contd. on page 1

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

	(Co	ntd. of pa	ge 12
CAS: 95-48-7	o-cresol	C	
CAS: 98-82-8	cumene	D, (CBD
CAS: 65-85-0	Benzoic Acid, Reagent ACS Grade	D	
CAS: 1330-20-7	Xylene (Xylol)	I	
CAS: 91-57-6	2-Methylnaphthalene	I	
CAS: 108-95-2	Phenol	<i>D, I</i>	
TLV (Threshold	Limit Value)		
CAS: 1330-20-7	Xylene (Xylol)		A4
CAS: 91-20-3	Naphthalene		A4
CAS: 1330-20-7	Xylene (Xylol)		<i>A4</i>
CAS: 91-57-6	2-Methylnaphthalene		A4
CAS: 108-95-2	Phenol		A4
NIOSH-Ca (Nat	ional Institute for Occupational Safety and Health)		
None of the ingre	edients is listed.		

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS02

GHS05

GHS07 GH

· Signal word Danger

· Hazard-determining components of labeling:

Solvent naphtha (petroleum), light arom.

m-Xylenol (2,4-Dimethylphenol)

1,2,4-Trimethylbenzene

Biphenyl

Naphthalene

Xylene (*Xylol*)

Solvent naphtha (petroleum), heavy arom.

cumene

· Hazard statements

Flammable liquid and vapor.

Harmful if inhaled.

Causes skin irritation.

Causes serious eye damage.

May cause genetic defects.

May cause cancer.

May cause respiratory irritation.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

 ${\it Take\ precautionary\ measures\ against\ static\ discharge}.$

(Contd. on page 14)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 13)

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 1.0, 08/07/2023: Reviewed SDS for Accuracy.. STN

Revision 0.3, 03-05-2019: updated all packing groups in shipping to PG II from PG III based on flash-point. STN 08/07/2023

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

(Contd. on page 15)

Printing date 08/07/2023 Reviewed on 08/07/2023

Trade name: PXA A9+ Blend 2

(Contd. of page 14)

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 3: Flammable liquids – Category 3 Acute Toxicity - Inhalation 4: Acute toxicity - Category 4 Skin Irritation 2: Skin corrosion/irritation – Category 2 Eye Damage 1: Serious eye damage/eye irritation – Category 1 Germ Cell Mutagenicity 1A: Germ cell mutagenicity – Category 1A

Carcinogenicity 1B: Carcinogenicity - Category 1B
Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Aspiration Hazard 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.