Printing date 11/30/2023

Reviewed on 11/30/2023


1 Identification

- · Product identifier
- · Trade name: Sulfur Standard 50 ppm W/V in Isooctane
- · Article number: LY498
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Aqua Solutions, Inc.
 6913 Highway 225 DEER PARK, TX 77536 USA
 800-256-2586

AQUA

- Information department: Technical Coordinator
 Sherman Nelson shermann@aquasolutions.org
 Emergency telephone number:
- *Chemtrec:* 800-424-9300 *Canutec:* 613-996-6666

2 Hazard(s) identification



Printing date 11/30/2023

Reviewed on 11/30/2023

Trade name: Sulfur Standard 50 ppm W/V in Isooctane

| () | Contd. of page 1) |
|--|-------------------|
| May cause drowsiness or dizziness. | 1.8. |
| May be fatal if swallowed and enters airways. | |
| · Precautionary statements | |
| Keep away from heat/sparks/open flames/hot surfaces No smoking. | |
| Ground/bond container and receiving equipment. | |
| Use explosion-proof electrical/ventilating/lighting/equipment. | |
| Use only non-sparking tools. | |
| Take precautionary measures against static discharge. | |
| Avoid breathing dust/fume/gas/mist/vapors/spray | |
| Wash thoroughly after handling. | |
| Use only outdoors or in a well-ventilated area. | |
| Wear protective gloves/protective clothing/eye protection/face protection. | |
| If swallowed: Immediately call a poison center/doctor. | |
| Specific treatment (see on this label). | |
| Do NOT induce vomiting. | |
| If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. | |
| IF INHALED: Remove person to fresh air and keep comfortable for breathing. | |
| Call a poison center/doctor if you feel unwell. | |
| Take off contaminated clothing and wash it before reuse. | |
| If skin irritation occurs: Get medical advice/attention. | |
| In case of fire: Use CO2, powder or water spray to extinguish. | |
| Store in a well-ventilated place. Keep container tightly closed. | |
| Store in a well-ventilated place. Keep cool. | |
| Store locked up. | |
| Dispose of contents/container in accordance with local/regional/national/international regulations. | |
| · Classification system: | |
| · NFPA ratings (scale 0 - 4) | |
| Health = 1 | |
| $\frac{3}{Fire = 3}$ | |
| $\frac{1}{1} \frac{1}{1} \frac{1}$ | |
| | |
| · HMIS-ratings (scale 0 - 4) | |
| HEALTH 1 $Health = 1$ | |
| FIRE 3 Fire = 3 | |
| $\frac{1}{\text{REACTIVITY}[0]} Reactivity = 0$ | |
| REACTIVITY 0 Reactivity = 0 | |
| · Other hazards | |
| · Results of PBT and vPvB assessment | |
| • PBT: Not applicable. | |
| • vPvB: Not applicable. | |
| | |
| | |
| 3 Composition/information on ingredients | |
| · Chemical characterization: Mixtures | |
| • Description: Mixture of the substances listed below with nonhazardous additions. | |
| • • | |
| · Dangerous components: | 00.0670 |
| CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane) | 99.967% |

· Table of Nonhazardous Ingredients

CAS: 544-40-1 Butyl sulfide

(Contd. on page 3)

0.033%

US

Printing date 11/30/2023

Reviewed on 11/30/2023

Trade name: Sulfur Standard 50 ppm W/V in Isooctane

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

| · Personal precautions, protective equipment and emergency procedures | |
|--|-----------|
| Wear protective equipment. Keep unprotected persons away. | |
| · Environmental precautions: | |
| Do not allow product to reach sewage system or any water course. | |
| Inform respective authorities in case of seepage into water course or sewage system. | |
| Do not allow to enter sewers/ surface or ground water. | |
| • Methods and material for containment and cleaning up: | |
| Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). | |
| Dispose contaminated material as waste according to section 13. | |
| Ensure adequate ventilation. | |
| · Reference to other sections | |
| See Section 7 for information on safe handling. | |
| See Section 8 for information on personal protection equipment. | |
| See Section 13 for disposal information. | |
| Protective Action Criteria for Chemicals | |
| • PAC-1: | |
| CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane) | 230 ppm |
| · PAC-2: | |
| CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane) | 830 ppm |
| · PAC-3: | |
| CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane) | 5000* ppm |

(Contd. on page 4)

Printing date 11/30/2023

Reviewed on 11/30/2023

Trade name: Sulfur Standard 50 ppm W/V in Isooctane

(Contd. of page 3)

7 Handling and storage

- · Handling:
- *Precautions for safe handling Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.*
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- Protect against electrostatic charges.
- \cdot Conditions for safe storage, including any incompatibilities
- Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:
- CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)
- TLV Long-term value: 300 ppm
- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.
- Avoid contact with the eyes and skin.
- Breathing equipment:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 5)

⁻ US

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/30/2023

Reviewed on 11/30/2023

Trade name: Sulfur Standard 50 ppm W/V in Isooctane

 \cdot Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

| Information on basic physical and | a homized avenueties |
|--------------------------------------|--|
| General Information | cnemicai properiies |
| Appearance: | |
| Form: | Liquid |
| Color: | Colorless |
| Odor: | Iso-Octane and Sulfur |
| Odor threshold: | Not determined. |
| pH-value: | Not determined. |
| Change in condition | |
| Melting point/Melting range: | -107.4 °C (-161.3 °F) |
| Boiling point/Boiling range: | 98-99 °C (208.4-210.2 °F) |
| Flash point: | -8 °C (17.6 °F) |
| Flammability (solid, gaseous): | Highly flammable. |
| Auto igniting: | 410 °C (770 °F) |
| Decomposition temperature: | Not determined. |
| Ignition temperature: | Product is not selfigniting. |
| Danger of explosion: | Product is not explosive. However, formation of explosive air/vapo mixtures are possible. |
| Explosion limits: | |
| Lower: | 1.1 Vol % |
| Upper: | 6 Vol % |
| Vapor pressure at 20 °C (68 °F): | 15 hPa (11.3 mm Hg) |
| Density at 20 °C (68 °F): | 0.69194 g/cm³ (5.77424 lbs/gal) |
| Relative density | Not determined. |
| Vapor density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with | |
| Water: | Not miscible or difficult to mix. |
| Partition coefficient (n-octanol/wat | er): Not determined. |
| Viscosity: | |
| Dynamic at 20 °C (68 °F): | 0.51 mPas |
| Kinematic: | Not determined. |

US

Printing date 11/30/2023

Reviewed on 11/30/2023

Trade name: Sulfur Standard 50 ppm W/V in Isooctane

| | (Contd. of p | age 5 |
|---|--|-------|
| · Solvent content: Organic solvents: | 100.0 % | |
| VOC content: | 99.97 % | |
| C. P. L. second south | 691.7 g/l / 5.77 lb/gal | |
| Solids content: | 0.0 % | |
| • Other information | No further relevant information available. | |

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

(Contd. on page 7)

US

Printing date 11/30/2023 Reviewed on 11/30/2023 Trade name: Sulfur Standard 50 ppm W/V in Isooctane (Contd. of page 6) Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. · Other adverse effects No further relevant information available. **13 Disposal considerations** · Waste treatment methods · Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system. · Uncleaned packagings: • Recommendation: Disposal must be made according to official regulations. **14 Transport information** · UN-Number · DOT, IMDG, IATA UN1993 · UN proper shipping name $\cdot DOT$ Flammable liquids, n.o.s. (Octanes) · IMDG, IATA FLAMMABLE LIQUID, N.O.S. (Octanes) · Transport hazard class(es) · DOT · Class 3 Flammable liquids · Label 3 · IMDG, IATA · Class 3 Flammable liquids . Lahel

| · Label | 3 |
|--|--|
| · Packing group · DOT, IMDG, IATA | II |
| · Environmental hazards: | Product contains environmentally hazardous substances: Octanes |
| Special precautions for user Hazard identification number (Kemler | Warning: Flammable liquids r code): 33 |
| · EMS Number: | F- E , S - E |
| · Stowage Category | В |
| | (Contd. on page 8) |

____US -

Printing date 11/30/2023

Reviewed on 11/30/2023

Trade name: Sulfur Standard 50 ppm W/V in Isooctane

| | (Contd. of page 7 |
|--|---|
| • Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| ·DOT | |
| • Quantity limitations | On passenger aircraft/rail: 5 L |
| | On cargo aircraft only: 60 L |
| · IMDG | |
| Limited quantities (LQ) | 1L |
| \cdot Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| UN ''Model Regulation'': | UN 1993 FLAMMABLE LIQUID, N.O.S. (OCTANES), 3, II |

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 Sara

| · Section 355 (extremely hazardous substances): | |
|---|--------|
| None of the ingredients is listed. | |
| · Section 313 (Specific toxic chemical listings): | |
| None of the ingredients is listed. | |
| · TSCA (Toxic Substances Control Act): | |
| 2,2,4-Trimethylpentane (Iso-Octane) | ACTIVE |
| Butyl sulfide | ACTIVE |
| · Hazardous Air Pollutants | |
| CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane) | |
| · Proposition 65 | |
| · Chemicals known to cause cancer: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause reproductive toxicity for females: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause reproductive toxicity for males: | |
| None of the ingredients is listed. | |
| · Chemicals known to cause developmental toxicity: | |
| None of the ingredients is listed. | |
| · Carcinogenic categories | |
| · EPA (Environmental Protection Agency) | |

CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

• TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 9)

II

US

Printing date 11/30/2023

Reviewed on 11/30/2023

Trade name: Sulfur Standard 50 ppm W/V in Isooctane

(Contd. of page 8) • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: 2,2,4-Trimethylpentane (Iso-Octane) · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

• Contact: Date of Preparation / Last Revision:

- Date of preparation / last revision Creation date for SDS 11-30-2023. CMC/STN 11/30/2023
- Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

US

Printing date 11/30/2023

Reviewed on 11/30/2023

Trade name: Sulfur Standard 50 ppm W/V in Isooctane

| | (Contd. of page 9) |
|---|--------------------|
| DOT: US Department of Transportation | |
| IATA: International Air Transport Association | |
| EINECS: European Inventory of Existing Commercial Chemical Substances | |
| ELINCS: European List of Notified Chemical Substances | |
| CAS: Chemical Abstracts Service (division of the American Chemical Society) | |
| NFPA: National Fire Protection Association (USA) | |
| HMIS: Hazardous Materials Identification System (USA) | |
| VOC: Volatile Organic Compounds (USA, EU) | |
| PBT: Persistent, Bioaccumulative and Toxic | |
| vPvB: very Persistent and very Bioaccumulative | |
| NIOSH: National Institute for Occupational Safety | |
| OSHA: Occupational Safety & Health | |
| TLV: Threshold Limit Value | |
| PEL: Permissible Exposure Limit | |
| REL: Recommended Exposure Limit | |
| Flammable Liquids 2: Flammable liquids – Category 2 | |
| Skin Irritation 2: Skin corrosion/irritation – Category 2 | |
| Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3 | |
| Aspiration Hazard 1: Aspiration hazard – Category 1 | |
| | US |