Printing date 11/13/2023 Reviewed on 11/13/2023

1 Identification

· Product identifier

· Trade name: HBBLI Level 2 Standard

· Article number: ARL030

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

• Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carcinogenicity 1B H350 May cause cancer.

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 1 H372 Causes damage to the hearing organs through

prolonged or repeated exposure.

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



Skin Irritation 2 H315 Causes skin irritation.

Eye Irritation 2A H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

(Contd. of page 1)

· Signal word Danger

· Hazard-determining components of labeling:

Cyclohexane

Styrene 99+%

Hexane

4-Vinyl-1-Cyclohexene

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Causes damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 3

Reactivity = 0

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

· HMIS-ratings (scale 0 - 4)

HEALTH*2Health = *2FIRE3Fire = 3REACTIVITY 0Reactivity = 0

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable. · **vPvB**: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 110-82-7	Cyclohexane	70.0%
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	10.0%
CAS: 100-42-5	Styrene 99+%	10.0%
CAS: 110-54-3	Hexane	10.0%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

US

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

(Contd. of page 3)

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

	· - · · · · · · · · · · · · · · · · · ·	
· PAC-1:		
CAS: 110-82-7	Cyclohexane	300 ppm
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	0.3 ppm
CAS: 100-42-5	Styrene 99+%	20 ppm
CAS: 110-54-3	Hexane	260 ppm
· PAC-2:		
CAS: 110-82-7	Cyclohexane	1700* ppm
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	210 ppm
CAS: 100-42-5	Styrene 99+%	130 ppm
CAS: 110-54-3	Hexane	2900* ppm
· PAC-3:		
CAS: 110-82-7	Cyclohexane	10000** ppm
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	340 ppm
CAS: 100-42-5	Styrene 99+%	1100* ppm
CAS: 110-54-3	Hexane	8600** ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 5)

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

(Contd. of page 4)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 \cdot *Specific end use*(s) *No further relevant information available.*

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:					
CAS: 1	CAS: 110-82-7 Cyclohexane				
PEL	Long-term value: 1050 mg/m³, 300 ppm				
REL	Long-term value: 1050 mg/m³, 300 ppm				
TLV	Long-term value: 100 ppm				
	BEI				

CAS: 100-40-3 4-Vinyl-1-Cyclohexene

TLV	Long-term value: 0.1 ppm
	A3

WEEL Long-term value: 4.4 mg/m³, 1 ppm

CAS: 100-42-5 Styrene 99+%

PEL	Long-term value: 100 ppm
	Ceiling limit value: 200; 600* ppm
	Long-term value: 100 ppm Ceiling limit value: 200; 600* ppm *5-min peak in any 3 hrs
REL	Short-term value: 425 mg/m³, 100 pp

Long-term value: 425 mg/m², 100 ppm Long-term value: 215 mg/m³, 50 ppm TLV Short-term value: 20 ppm

Long-term value: 20 ppm BEI, OTO, A3

CAS: 110-54-3 Hexane

PEL	Long-term value: 1800 mg/m³, 500 ppm
REL	Long-term value: 180 mg/m³, 50 ppm
TLV	Long-term value: 50 ppm
	Skin; BEI

· Ingredients with biological limit values:

CAS: 110-82-7 Cyclohexane

BEI NIC-50 mg/g creatinine LD50 Intraperitoneal: -

Time: end of shift at end of workweek

LD50: NIC-1.2-Cyclohexanediol (nonspecific)

(Contd. on page 6)

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

(Contd. of page 5)

CAS: 100-42-5 Styrene 99+%

BEI 400 mg/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Mandelic acid plus phenylglyoxylic acid (nonspecific)

 $40 \mu g/L$

LD50 Intraperitoneal: urine

Time: end of shift LD50: Styrene

CAS: 110-54-3 Hexane

BEI 0.5 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: 2.5-Hexanedione without hydrolysis

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

(Contd. on page 7)

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

· Body protection: Protective work clothing

(Contd. of page 6)

9 Physical and chemical properties		
Information on basic physical and ch	hemical properties	
· General Information		
· Appearance: Form:	Liquid	
	Liquid	
Color: · Odor:	Clear Organic	
· Ouor: · Odor threshold:	Not determined.	
	Not determined.	
· pH-value:	Noi determined.	
· Change in condition Melting point/Melting range:	Undetermined.	
	69 °C (156.2 °F)	
Boiling point/Boiling range:		
· Flash point:	-26 °C (-14.8 °F)	
· Flammability (solid, gaseous):	Highly flammable.	
· Auto igniting:	240 °C (464 °F)	
Decomposition temperature:	Not determined.	
· Ignition temperature:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vape mixtures are possible.	
· Explosion limits:		
Lower:	1.2 Vol %	
Upper:	8.9 Vol %	
· Vapor pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)	
· Vapor pressure at 50 °C (122 °F):	540 hPa (405 mm Hg)	
· Density at 20 °C (68 °F):	0.7857 g/cm³ (6.55667 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/water	r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	90.0 %	
VOC content:	90.00 %	
	707.1 g/l / 5.90 lb/gal	
Solids content:	0.0 %	

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

(Contd. of page 7)

· Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Inhalative LC50/4h 110 mg/l

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
	4-Vinyl-1-Cyclohexene	2B
CAS: 100-42-5	Styrene 99+%	2A
· NTP (National	Toxicology Program)	
CAS: 100-42-5	Styrene 99+%	R
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ing	redients is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

(Contd. on page 9)

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

(Contd. of page 8)

Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Cyclohexane, Hexane, Styrene 99+4-Vinyl-1-Cyclohexene)
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Cyclohexane, Hexane, Styre 99+%, 4-Vinyl-1-Cyclohexene)
Transport hazard class(es)	
DOT	
RAMMABLE LOUIS	
Class	3 Flammable liquids
Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substanc Cyclohexane
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemle	
EMS Number:	F- E , S - D

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

	(Contd. of page
· Stowage Category	B
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT · Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (CYCLOHEXAN) HEXANE, STYRENE 99+%, 4-VINYL-1-CYCLOHEXENE), 3, II

5 Regulatory ii	formation		
· Safety, health a · Sara	nd environmental regulations/legislation specific for the substance or mixture		
· Section 355 (ex	remely hazardous substances):		
None of the ing	edients is listed.		
· Section 313 (Sp	ecific toxic chemical listings):		
CAS: 110-82-7	Cyclohexane		
CAS: 100-42-5	Styrene 99+%		
CAS: 110-54-3	Hexane		
· TSCA (Toxic S	ubstances Control Act):		
Cyclohexane		ACTIVE	
4-Vinyl-1-Cyclo	hexene	ACTIVE	
Styrene 99+%	Styrene 99+% ACTIV		
Hexane		ACTIVE	
· Hazardous Air	Pollutants		
CAS: 100-42-5	Styrene 99+%		
CAS: 110-54-3	Hexane		
· Proposition 65			
	vn to cause cancer:		
	CAS: 100-40-3 4-Vinyl-1-Cyclohexene		
CAS: 100-42-5	CAS: 100-42-5 Styrene 99+%		
· Chemicals know	vn to cause reproductive toxicity for females:		
CAS: 100-40-3	4-Vinyl-1-Cyclohexene		
· Chemicals know	vn to cause reproductive toxicity for males:		
CAS: 110-54-3	Hexane		

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

(Contd. of page 10)

· Carcinogenic categories

· EPA (Environmental Protection Agency)		
CAS: 110-82-7		I
CAS: 110-54-3	Hexane	II
· TLV (Threshold Limit Value)		
CAS: 100-40-3	4-Vinyl-1-Cyclohexene	A3
CAS: 100-42-5	Styrene 99+%	A4
· NIOSH-Ca (National Institute for Occupational Safety and Health)		
None of the ingredients is listed.		

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS07 GH

- · Signal word Danger
- · Hazard-determining components of labeling:

Cyclohexane

Styrene 99+%

Hexane

4-Vinyl-1-Cyclohexene

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

May cause cancer.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

Causes damage to the hearing organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

(Contd. on page 12)

Printing date 11/13/2023 Reviewed on 11/13/2023

Trade name: HBBLI Level 2 Standard

(Contd. of page 11)

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 0.0, 11-13-2023: creation date for SDS_STN/CMC

11/13/2023

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A

Carcinogenicity 1B: Carcinogenicity - Category 1B

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3

Specific Target Organ Toxicity - Repeated Exposure 1: Specific target organ toxicity (repeated exposure) - Category 1

Aspiration Hazard 1: Aspiration hazard - Category 1