Printing date 11/16/2023

Reviewed on 11/16/2023

## **1** Identification

- · Product identifier
- · Trade name: <u>Hex Analysis Level 1 Standard</u>
- · Article number: ARL043
- Details of the supplier of the safety data sheet
  Manufacturer/Supplier: Aqua Solutions, Inc.
  6913 Highway 225 DEER PARK, TX 77536 USA
  800-256-2586
- Information department: Technical Coordinator Sherman Nelson shermann@aquasolutions.org • Emergency telephone number:
- *Chemtrec:* 800-424-9300 *Canutec:* 613-996-6666

## 2 Hazard(s) identification

· Classification of the substance or mixture



Flammable Liquids 2

H225 Highly flammable liquid and vapor.

GHS08 Health hazard

Toxic to Reproduction 2H361 Suspected of damaging fertility or the unborn child.Specific Target Organ Toxicity - Repeated Exposure 2H373 May cause damage to organs through prolonged or<br/>repeated exposure.

Aspiration Hazard 1



Skin Irritation 2 Eye Irritation 2A Specific Target Organ Toxicity - Single Exposure 3 H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

(Contd. on page 2)

US –

Printing date 11/16/2023

Reviewed on 11/16/2023

Trade name: Hex Analysis Level 1 Standard

	(Contd. of page 1)
Hazard-determining co	mponents of labeling:
Hexane	
Cyclohexane	
Methylcyclopentane 98	$\sim$
3-Methylpentane	
Hexanes (From Petrole	um)
Hazard statements	
Highly flammable liquid	and vapor.
Causes skin irritation.	
Causes serious eye irrit	ition.
Suspected of damaging	fertility or the unborn child.
May cause drowsiness a	r dizziness.
May cause damage to o	rgans through prolonged or repeated exposure.
May be fatal if swallow	ed and enters airways.
Precautionary statemen	ts
Obtain special instructi	ons before use.
Do not handle until all	safety precautions have been read and understood.
Keep away from heat/s <sub>l</sub>	arks/open flames/hot surfaces No smoking.
Ground/bond container	and receiving equipment.
Use explosion-proof ele	ctrical/ventilating/lighting/equipment.
Use only non-sparking	ools.
Take precautionary mea	isures against static discharge.
Do not breathe dust/fun	ne/gas/mist/vapors/spray.
Wash thoroughly after l	andling.
Use only outdoors or in	a well-ventilated area.
Wear protective gloves/	protective clothing/eye protection/face protection.
If swallowed: Immediat	ely call a poison center/doctor.
Specific treatment (see	on this label).
Do NOT induce vomitin	g.
	e off immediately all contaminated clothing. Rinse skin with water/shower. person to fresh air and keep comfortable for breathing.
If in eyes: Rinse caution	usly with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.	
IF exposed or concerne	d: Get medical advice/attention.
Call a poison center/do	ctor if you feel unwell.
Get medical advice/atte	
Take off contaminated o	lothing and wash it before reuse.
If skin irritation occurs.	Get medical advice/attention.
	Get medical advice/attention.
	<i>P, powder or water spray to extinguish.</i>
	d place. Keep container tightly closed.
Store in a well-ventilate	d place. Keep cool.
Store locked up.	
	tainer in accordance with local/regional/national/international regulations.
Classification system:	
NFPA ratings (scale 0	4)
Health =	2
Fire = $3$	

(Contd. on page 3)

-US-

Printing date 11/16/2023

Reviewed on 11/16/2023

#### Trade name: Hex Analysis Level 1 Standard

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)



• Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

#### **3** Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
	0.0%	
CAS: 110-82-7 Cyclohexane 35	5.0%	
CAS: 96-14-0 3-Methylpentane 5.	.0%	
CAS: 96-37-7 Methylcyclopentane 98% 5.	.0%	
CAS: 107-83-5 Hexanes (From Petroleum) 5.	.0%	

#### 4 First-aid measures

- · Description of first aid measures
- General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

## **5** Fire-fighting measures

- Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- $\cdot$  For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

US

Printing date 11/16/2023

Reviewed on 11/16/2023

#### Trade name: Hex Analysis Level 1 Standard

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

#### 6 Accidental release measures

• *Personal precautions, protective equipment and emergency procedures Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.* 

#### · Environmental precautions:

Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

#### • Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

- See Section 13 for disposal information.
- · Protective Action Criteria for Chemicals

1.0000000000000000000000000000000000000	in Crueria for Chemicais	
· PAC-1:		
CAS: 110-54-3	Hexane	260 ppm
CAS: 110-82-7	Cyclohexane	300 ppm
CAS: 96-14-0	3-Methylpentane	1,000 ppm
CAS: 96-37-7	Methylcyclopentane 98%	14 ppm
CAS: 107-83-5	Hexanes (From Petroleum)	1,000 ppm
· PAC-2:		
CAS: 110-54-3	Hexane	2900* ppm
CAS: 110-82-7	Cyclohexane	1700* ppm
CAS: 96-14-0	3-Methylpentane	11000** ppm
CAS: 96-37-7	Methylcyclopentane 98%	160 ppm
CAS: 107-83-5	Hexanes (From Petroleum)	11000** ppm
· PAC-3:		
CAS: 110-54-3	Hexane	8600** ppm
CAS: 110-82-7	Cyclohexane	10000** ppm
CAS: 96-14-0	3-Methylpentane	66000*** ppm
CAS: 96-37-7	Methylcyclopentane 98%	940 ppm
CAS: 107-83-5	Hexanes (From Petroleum)	66000*** ppm

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

(Contd. on page 5)

(Contd. of page 3)

Printing date 11/16/2023

Reviewed on 11/16/2023

#### Trade name: Hex Analysis Level 1 Standard

(Contd. of page 4)

- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- $\cdot$  Specific end use(s) No further relevant information available.

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Contro	ol parameters
· Comp	onents with limit values that require monitoring at the workplace:
CAS:	110-54-3 Hexane
PEL	Long-term value: 1800 mg/m³, 500 ppm
REL	Long-term value: 180 mg/m <sup>3</sup> , 50 ppm
TLV	Long-term value: 50 ppm
1	Skin; BEI
CAS:	110-82-7 Cyclohexane
PEL I	Long-term value: 1050 mg/m³, 300 ppm
REL	Long-term value: 1050 mg/m³, 300 ppm
TLV	Long-term value: 100 ppm
i	BEI
CAS:	96-14-0 3-Methylpentane
	Long-term value: 350 mg/m³, 100 ppm
	Ceiling limit value: 1800* mg/m <sup>3</sup> , 510* ppm
	*15-min
	Short-term value: 1000 ppm
	Long-term value: 500 ppm
	96-37-7 Methylcyclopentane 98%
	Long-term value: 350 mg/m³, 100 ppm Ceiling limit value: 1800* mg/m³, 510* ppm
	*15-min
	Short-term value: 3500 mg/m <sup>3</sup> , 1000 ppm
	Long-term value: 1760 mg/m <sup>3</sup> , 500 ppm
	107-83-5 Hexanes (From Petroleum)
REL I	Long-term value: 350 mg/m <sup>3</sup> , 100 ppm
	Ceiling limit value: 1800* mg/m <sup>3</sup> , 510* ppm
'	*15-min
	Short-term value: 1000 ppm
1	Long-term value: 500 ppm
	(Contd. on page 6)

Printing date 11/16/2023

Reviewed on 11/16/2023

Trade name: Hex Analysis Level 1 Standard

Ingredients with biological limit values:         CAS: 110-54-3 Hexane         BEI       0.5 mg/L         LD50 Intraperitoneal: urine		
BEI 0.5 mg/L		
Time: end of shift		
LD50: 2.5-Hexanedione without hydrolysis		
CAS: 110-82-7 Cyclohexane		
BEI NIC-50 mg/g creatinine		
LD50 Intraperitoneal: -		
Time: end of shift at end of workweek		
LD50: NIC-1.2-Cyclohexanediol (nonspecific)		
Additional information: The lists that were valid during the creation were used as basis.		
Exposure controls		
Personal protective equipment:		
General protective and hygienic measures:		
Keep away from foodstuffs, beverages and feed.		
Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.		
Store protective clothing separately.		
Avoid contact with the eyes and skin.		
Breathing equipment:		
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or long	er exposure us	
respiratory protective device that is independent of circulating air.	1	
Protection of hands:		
in the second seco		
Mi Protective gloves		
Troiteure Sieves		
The glove material has to be impermeable and resistant to the product/ the substance/ the preparate		
Due to missing tests no recommendation to the glove material can be given for the product/ the p chemical mixture.	preparation/ th	
cnemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the	degradation	
Selection of the glove material on consideration of the penetration times, rates of affusion and the Material of gloves	ucgruuunon	
Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality an		
varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.		
The exact break through time has to be found out by the manufacturer of the protective glove	s and has to b	
observed.		
Eye protection:		
Tightly sealed goggles		
rignity sected goggies		
Body protection: Protective work clothing		

(Contd. on page 7)

US

Printing date 11/16/2023

\*

Reviewed on 11/16/2023

Trade name: Hex Analysis Level 1 Standard

(Contd. of page 6)

Information on basic physical and cl	hemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Organic Not determined.
Odor threshold:	
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	62 °C (143.6 °F)
Flash point:	-29 °C (-20.2 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	240 °C (464 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.3 Vol %
Vapor pressure at 20 °C (68 °F):	160 hPa (120 mm Hg)
Vapor pressure at 50 °C (122 °F):	540 hPa (405 mm Hg)
Density at 20 °C (68 °F):	0.70615 g/cm <sup>3</sup> (5.89282 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	85.0 %
VOC content:	90.00 %
	635.5 g/l / 5.30 lb/gal
Solids content:	5.0 %
Other information	No further relevant information available.

(Contd. on page 8)

Printing date 11/16/2023

Reviewed on 11/16/2023

Trade name: Hex Analysis Level 1 Standard

(Contd. of page 7)

#### **10 Stability and reactivity**

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 10,000 mg/kg

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

#### **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- **vPvB:** Not applicable.

(Contd. on page 9)

(Contd. of page 8)

## Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2023

Reviewed on 11/16/2023

Trade name: Hex Analysis Level 1 Standard

• Other adverse effects No further relevant information available.

## **13 Disposal considerations**

• Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number	
· DOT, IMDG, IATA	UN1993
· UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Hexane, Cyclohexane, Hexanes (Fr Petroleum), Methylcyclopentane 98%)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Hexane, Cyclohexane, Hexa (From Petroleum), Methylcyclopentane 98%)
· Transport hazard class(es)	
DOT	
RAMARE LOUD	
Class	3 Flammable liquids
Label	3
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substanc
	Cyclohexane
Special precautions for user	Warning: Flammable liquids
• Hazard identification number (Kemler code • EMS Number:	
· EMS Number: · Stowage Category	F-E,S-D B
• Transport in bulk according to Annex II of	

Printing date 11/16/2023

Reviewed on 11/16/2023

Trade name: Hex Analysis Level 1 Standard

• Transport/Additional information:	(Contd. of page
• DOT • Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (HEXANE CYCLOHEXANE, HEXANES (FROM PETROLEUM) METHYLCYCLOPENTANE 98%), 3, II

# **15 Regulatory information**

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

•	Sara
---	------

· Section 355 (er	xtremely hazardous substances):	
	redients is listed.	
	pecific toxic chemical listings):	
CAS: 110-54-3		
CAS: 110-82-7		
	Substances Control Act):	
Hexane		ACTIVE
Cyclohexane		ACTIVE
3-Methylpentar	ne	ACTIVE
Methylcycloper	ntane 98%	ACTIVE
Hexanes (From	Hexanes (From Petroleum)	
· Hazardous Air	Pollutants	· · ·
CAS: 110-54-3	Hexane	
· Proposition 65		
· Chemicals kno	wn to cause cancer:	
None of the ingredients is listed.		
· Chemicals kno	wn to cause reproductive toxicity for females:	
None of the ing	redients is listed.	
· Chemicals kno	wn to cause reproductive toxicity for males:	
CAS: 110-54-3	Hexane	
· Chemicals kno	wn to cause developmental toxicity:	
None of the ingredients is listed.		
· Carcinogenic d	categories	
· EPA (Environ	mental Protection Agency)	
CAS: 110-54-3	Hexane	II
	·	(Contd. on page 11)

US

(Contd. of page 10)

Ι

#### Safety Data Sheet acc. to OSHA HCS

Printing date 11/16/2023

Reviewed on 11/16/2023

Trade name: Hex Analysis Level 1 Standard

CAS: 110-82-7 Cyclohexane

· TLV (Threshold Limit Value)

None of the ingredients is listed.

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

· Hazard-determining components of labeling: Hexane Cvclohexane Methylcyclopentane 98% 3-Methylpentane Hexanes (From Petroleum) · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Causes serious eye irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Get medical advice/attention if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.

(Contd. on page 12)

US

Printing date 11/16/2023

Reviewed on 11/16/2023

Trade name: Hex Analysis Level 1 Standard

(Contd. of page 11)

If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. • Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact: Date of Preparation / Last Revision: · Date of preparation / last revision Revision 0.0, 11-16-2023: creation date for SDS STN/CMC 11/16/2023 · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation - Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Toxic to Reproduction 2: Reproductive toxicity - Category 2 Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) - Category 2 Aspiration Hazard 1: Aspiration hazard - Category 1 • \* Data compared to the previous version altered.

- US -