Printing date 12/05/2023 Reviewed on 12/05/2023

1 Identification

· Product identifier

· Trade name: Water 20% v/v in Acetic Acid

· Article number: LY510

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 3 H226 Flammable liquid and vapor.



GHS05 Corrosion

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.



GHS07

Acute Toxicity - Dermal 4 H312 Harmful in contact with skin.

Sensitization - Skin 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

602 GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Acetic Acid, Glacial

· Hazard statements

Flammable liquid and vapor.

(Contd. on page 2)

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

(Contd. of page 1)

Harmful in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 2

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



3 Health = 3Fire = 2

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 64-19-7 Acetic Acid, Glacial

80.814%

(Contd. on page 3)

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

(Contd. of page 2)

· Table of Nonhazardous Ingredients

CAS: 7732-18-5 | Water | 19.187%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textit{Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

(Contd. on page 4)

250 ppm

Safety Data Sheet acc. to OSHA HCS

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

CAS: 64-19-7 Acetic Acid, Glacial

 • Protective Action Criteria for Chemicals

 • PAC-1:
 CAS: 64-19-7 | Acetic Acid, Glacial
 5 ppm

 • PAC-2:
 CAS: 64-19-7 | Acetic Acid, Glacial
 35 ppm

 • PAC-3:
 PAC-3:

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with	limit values that require mor	nitoring at the workplace:
CAS: 64-19-7 Ac	etic Acid Glacial	

PEL Long-term value: 25 mg/m³, 10 ppm REL Short-term value: 37 mg/m³, 15 ppm

Long-term value: 25 mg/m³, 10 ppm

TLV Short-term value: 15 ppm Long-term value: 10 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 5)

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:

· General Information



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

Appearance:
Form: Liquid
Color: Clear
Odor: Acetic Acid Odor

· Odor threshold: Not determined.
· pH-value: Not determined.

· Information on basic physical and chemical properties

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:100 °C (212 °F)

Flash point: 40 °C (104 °F)
 Flammability (solid, gaseous): Flammable.

· Auto igniting: 485 °C (905 °F)

Decomposition temperature: Not determined.
 Ignition temperature: Product is not selfigniting.

• Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· Explosion limits:

Lower: 4 Vol %

 Upper: 17 Vol %

(Contd. on page 6)

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

	(Contd. of pag	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.04283 g/cm³ (8.70242 lbs/gal)	
Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	80.8 %	
Water:	19.2 %	
VOC content:	80.81 %	
	842.7 g/l / 7.03 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Dermal LD50 1,312 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

(Contd. on page 7)

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

(Contd. of page 6)

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

· UN-Number

· **DOT, IMDG, IATA** UN2789

· UN proper shipping name

 \cdot **DOT** Acetic acid solution

· IMDG, IATA ACETIC ACID SOLUTION

(Contd. on page 8)

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

	(Contd. of pag
Transport hazard class(es)	
DOT	
CORROSIVE FLAMMASLE LIQUID	
3	
Class	8+3
Label	8, 3
 IMDG	
A	
Class	8+3
Label	8/3
IATA	
3	
Class	8+3
Label	8 (3)
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Not applicable.
Hazard identification number (Kemler code)	
EMS Number:	F-E,S-C
Segregation groups Stowage Category	(SGG1) Acids A
Siowage Calegory Segregation Code	SG36 Stow "separated from" SGG18-alkalis.
avg. vgon	SG49 Stow "separated from" SGG6-cyanides
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 1 L
2	On cargo aircraft only: 30 L
 IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
- · · ~	Manimum not augustitu non inn an nach acina. 20 ml
	Maximum net quantity per inner packaging: 30 ml

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

(Contd. of page 8)

· UN "Model Regulation":

UN 2789 ACETIC ACID SOLUTION, 8 (3), II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

Acetic Acid, Glacial ACTIVE
Water ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

2 GHS05

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Acetic Acid, Glacial

(Contd. on page 10)

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

(Contd. of page 9)

· Hazard statements

Flammable liquid and vapor.

Harmful in contact with skin.

Causes severe skin burns and eye damage.

May cause an allergic skin reaction.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Take off contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

Wash contaminated clothing before reuse.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 0.0, 12-05-2023: creation date for SDS_STN/CMC

12/05/2023

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)

Printing date 12/05/2023 Reviewed on 12/05/2023

Trade name: Water 20% v/v in Acetic Acid

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flammable Liquids 3: Flammable liquids — Category 3
Acute Toxicity - Dermal 4: Acute toxicity — Category 4
Skin Corrosion 1B: Skin corrosion/irritation — Category 1B
Eye Damage 1: Serious eye damage/eye irritation — Category 1
Sensitization - Skin 1: Skin sensitisation — Category 1

(Contd. of page 10)

TIC