Printing date 05/30/2024 Reviewed on 05/30/2024

## 1 Identification

· Product identifier

· Trade name: Mixed Amine Standard

· Article number: VEN006

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS06 Skull and crossbones

Acute Toxicity - Dermal 1 H310 Fatal in contact with skin.



GHS08 Health hazard

Sensitization - Respiratory 1 H334 May cause allergy or asthma symptoms or breathing

difficulties if inhaled.

Carcinogenicity 2 H351 Suspected of causing cancer.

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.



GHS05 Corrosion

Skin Corrosion 1B H314 Causes severe skin burns and eye damage.

Eye Damage 1 H318 Causes serious eye damage.



Sensitization - Skin 1 H317 May cause an allergic skin reaction.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

(Contd. on page 2)

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

(Contd. of page 1)

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms











GHS02

GHS05

GHS06

GHS07

· Signal word Danger

## · Hazard-determining components of labeling:

**Piperazine** 

Diethanolamine

Diisopropylamine

2-Aminoethanol (Monoethanolamine), Reagent Grade

2-(2-aminoethoxy)ethanol

### · Hazard statements

Highly flammable liquid and vapor.

Fatal in contact with skin.

Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

*Ground/bond container and receiving equipment.* 

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

[In case of inadequate ventilation] wear respiratory protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

*If experiencing respiratory symptoms: Call a poison center/doctor.* 

In case of fire: Use CO2, powder or water spray to extinguish.

(Contd. on page 3)

Printing date 05/30/2024 Reviewed on 05/30/2024

### Trade name: Mixed Amine Standard

(Contd. of page 2)

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 4Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



\*3 *Health* = \*3 Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 110-85-0	Piperazine	15.0%
CAS: 105-59-9	N-Methyldiethanolamine, 99%	7.0%
	Diisopropylamine	7.0%
CAS: 111-42-2	Diethanolamine	7.0%
CAS: 141-43-5	2-Aminoethanol (Monoethanolamine), Reagent Grade	7.0%
CAS: 929-06-6	2-(2-aminoethoxy)ethanol	7.0%
· Table of Nonh	azardous Ingredients	
~ . ~ ==		<b>50.00</b> /

## C

CAS: 7732-18-5	Water	50.0%	ı
----------------	-------	-------	---

## 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

*In case of unconsciousness place patient stably in side position for transportation.* 

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

(Contd. of page 3)

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

## 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
CAS: 110-85-0	Piperazine	0.09 ppn
CAS: 108-18-9	Diisopropylamine	15 ppm
CAS: 111-42-2	Diethanolamine	$3 \text{ mg/m}^3$
CAS: 141-43-5	2-Aminoethanol (Monoethanolamine), Reagent Grade	6 <i>ppm</i>
CAS: 929-06-6	2-(2-aminoethoxy)ethanol	9 mg/m³
PAC-2:		
CAS: 110-85-0	Piperazine	8.9 ppm
CAS: 108-18-9	Diisopropylamine	170 ppm
CAS: 111-42-2	Diethanolamine	28 mg/m
CAS: 141-43-5	2-Aminoethanol (Monoethanolamine), Reagent Grade	170 ppm
CAS: 929-06-6	2-(2-aminoethoxy)ethanol	99 mg/m
PAC-3:		
CAS: 110-85-0	Piperazine	54 ppm
CAS: 108-18-9	Diisopropylamine	1,000 ppn
CAS: 111-42-2	Diethanolamine	130 mg/m
CAS: 141-43-5	2-Aminoethanol (Monoethanolamine), Reagent Grade	1,000 ppn
	, , , , , , , , , , , , , , , , , , , ,	(Contd. on page

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

CAS: 929-06-6 2-(2-aminoethoxy)ethanol

(Contd. of page 4)

 $590 \, mg/m^3$ 

## 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 $\cdot$  *Specific end use*(s) *No further relevant information available.* 

## 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

CAS:	110-85-0 Piperazine		
TLV	Long-term value: 0.03* ppm *inh. fraction+vapor,DSEN,RSEN;A4;as piperazine		
CAS.	· 108-18-9 Diisopropylamine		
PEL	Long-term value: 20 mg/m³, 5 ppm Skin		
REL	Long-term value: 20 mg/m³, 5 ppm Skin		
TLV	Long-term value: 5 ppm Skin		
CAS:	CAS: 111-42-2 Diethanolamine		
REL	Long-term value: 15 mg/m³, 3 ppm		
TLV	Long-term value: 1* mg/m³ Skin; *inhalable fraction and vapor, A3		
CAS.	CAS: 141-43-5 2-Aminoethanol (Monoethanolamine), Reagent Grade		
PEL	Long-term value: 6 mg/m³, 3 ppm		

(Contd. on page 6)

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

(Contd. of page 5)

REL Short-term value: 15 mg/m³, 6 ppm Long-term value: 8 mg/m³, 3 ppm

TLV Short-term value: 6 ppm Long-term value: 3 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

## 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Clear

Odor: Ammonia-like
Odor threshold: Not determined.

(Contd. on page 7)

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

	(Contd. of page
pH-value:	Not determined.
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. 84 °C (183.2 °F)
· Flash point:	-7 °C (19.4 °F)
· Flammability (solid, gaseous):	Highly flammable.
· Auto igniting:	265 °C (509 °F)
· Decomposition temperature:	Not determined.
· Ignition temperature:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vap mixtures are possible.
· Explosion limits: Lower: Upper:	3.9 Vol % 11.9 Vol %
· Vapor pressure at 20 °C (68 °F): · Vapor pressure at 50 °C (122 °F):	23 hPa (17.3 mm Hg) 15 hPa (11.3 mm Hg)
· Density at 20 °C (68 °F): · Relative density · Vapor density · Evaporation rate	1.00918 g/cm³ (8.42161 lbs/gal) Not determined. Not determined. Not determined.
· Solubility in / Miscibility with Water:	Fully miscible.
· Partition coefficient (n-octanol/water	r): Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
· Solvent content: Organic solvents: Water: VOC content:	14.0 % 50.0 % 14.00 % 141.3 g/l / 1.18 lb/gal
Solids content:	22.0 %
· Other information	No further relevant information available.

# 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 8)

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

(Contd. of page 7)

· Hazardous decomposition products: No dangerous decomposition products known.

## 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· <i>LD/LC50</i> 1	values tha	t are relevant for classification:
ATE (Acut		·
Oral	LD50	3,183 mg/kg
Dermal	LD50	26.6 mg/kg
Inhalative	LC50/4h	33.7 mg/l

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

· Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Corrosive

Irritant

Very toxic

Danger through skin absorption.

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
CAS: 111-42-2 Diethanolamine	2 <i>B</i>

### · NTP (National Toxicology Program)

None of the ingredients is listed.

## · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach bodies of water or drainage ditch undiluted or unneutralized.

(Contd. on page 9)

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

(Contd. of page 8)

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number	
DOT, IMDG, IATA	UN2735
UN proper shipping name DOT	Amines, liquid, corrosive, n.o.s. (Diisopropylamine, Piperazine,
	(2-aminoethoxy)ethanol, 2-Aminoethanol (Monoethanolamin Reagent Grade)
IMDG, IATA	AMINES, LIQUID, CORROSIVE, N.O.S. (Diisopropylami, Piperazine, 2-(2-aminoethoxy)ethanol, 2-Aminoethan (Monoethanolamine), Reagent Grade)
Transport hazard class(es)	
DOT	
OORROSIVE 8	
Class	8 Corrosive substances
Label	8
IMDG, IATA	
Class	8 Corrosive substances
Label	8
Packing group DOT, IMDG, IATA	III
Environmental hazards:	Not applicable.

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

	(Contd. of page
· EMS Number:	F-A,S-B
· Segregation groups	(SGG18) Alkalis
· Stowage Category	A
· Segregation Code	SG35 Stow "separated from" SGG1-acids
· Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
$\cdot$ DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 1000 ml
· UN ''Model Regulation'':	UN 2735 AMINES, LIQUID, CORROSIVE, N.O.
-	(DIISOPROPYLAMINE, PIPERAZINE, 2-(2-AMINOETHOX
	ETHANOL, 2-AMINOETHANOL (MONOETHANOLAMINE
	REAGENT GRADE), 8, III

# 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara

· Section 355 (extremely hazardous substances):
None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):
CAS: 111-42-2 Diethanolamine
· TSCA (Toxic Substances Control Act):

· ISCA (Toxic Substances Control Act):	
Water	ACTIVE
Piperazine	ACTIVE
N-Methyldiethanolamine, 99%	ACTIVE
Diisopropylamine	ACTIVE
Diethanolamine	ACTIVE
2-Aminoethanol (Monoethanolamine), Reagent Grade	ACTIVE
2-(2-aminoethoxy)ethanol	ACTIVE

## · Hazardous Air Pollutants

CAS: 111-42-2 Diethanolamine

- · Proposition 65
- · Chemicals known to cause cancer:

CAS: 111-42-2 Diethanolamine

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

(Contd. on page 11)

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

(Contd. of page 10)

### · Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

#### · Carcinogenic categories

### · EPA (Environmental Protection Agency)

None of the ingredients is listed.

### · TLV (Threshold Limit Value)

CAS: 111-42-2 Diethanolamine

*A3* 

## · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms









GHS07



GHS02

GHS05

GHS06

GHS0

· Signal word Danger

## · Hazard-determining components of labeling:

**Piperazine** 

Diethanolamine

Diisopropylamine

2-Aminoethanol (Monoethanolamine), Reagent Grade

2-(2-aminoethoxy)ethanol

### · Hazard statements

Highly flammable liquid and vapor.

Fatal in contact with skin.

Causes severe skin burns and eye damage.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction.

Suspected of causing cancer.

Suspected of damaging fertility or the unborn child.

May cause respiratory irritation.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

*Use only non-sparking tools.* 

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Do not get in eyes, on skin, or on clothing.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 12)

Printing date 05/30/2024 Reviewed on 05/30/2024

Trade name: Mixed Amine Standard

(Contd. of page 11)

[In case of inadequate ventilation] wear respiratory protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation or rash occurs: Get medical advice/attention.

*If experiencing respiratory symptoms: Call a poison center/doctor.* 

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 0.0, 05-29-2024: Creation date for SDS CMC/STN 05/30/2024

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

 ${\it HMIS: Hazardous\ Materials\ Identification\ System\ (USA)}$ 

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids - Category 2

Acute Toxicity - Dermal 1: Acute toxicity - Category 1

Skin Corrosion 1B: Skin corrosion/irritation - Category 1B

Eye Damage 1: Serious eye damage/eye irritation – Category 1 Sensitization - Respiratory 1: Respiratory sensitisation – Category 1

Sensitization - Skin 1: Skin sensitisation - Category 1

Carcinogenicity 2: Carcinogenicity – Category 2

Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3