Printing date 11/14/2017

Reviewed on 11/14/2017

I Identification	
· Product identifier	
· Trade name: <u>Isopropyl Alcohol /</u>	
Acetic Acid Solution	
Article number: ERL266	
Details of the supplier of the safety data sheet	
Manufacturer/Supplier:	
Aqua Solutions, Inc. 6913 Highway 225	SOLUTIONS
DEER PARK, TX 77536	
USA	
800-256-2586	
· Information department:	
Technical Coordinator Sherman Nelson sherman@aquasolutions.org	
• Emergency telephone number:	
<i>Chemtrec:</i> 800-424-9300	
Canutec: 613-996-6666	
P Hazard(s) identification	
· Classification of the substance or mixture	
GHS02 Flame	
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation.	
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness.	
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. • Label elements	cording to the Globally Harmonized System (G
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. • Label elements • GHS label elements The product is classified and labeled ad	cording to the Globally Harmonized System (G
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. • Label elements	cording to the Globally Harmonized System (G
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. • Label elements • GHS label elements The product is classified and labeled ad	ccording to the Globally Harmonized System (G
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled ad	cording to the Globally Harmonized System (G
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled ad	ccording to the Globally Harmonized System (G
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	cording to the Globally Harmonized System (G
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	cording to the Globally Harmonized System (G
Flam. Liq. 2 H225 Highly flammable liquid and vapor.	cording to the Globally Harmonized System (G
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled ad Hazard pictograms	ccording to the Globally Harmonized System (G
 Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled action. Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements Hajhly flammable liquid and vapor. 	cording to the Globally Harmonized System (G
 Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled ac Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. 	cording to the Globally Harmonized System (G
 Flam. Liq. 2 H225 Highly flammable liquid and vapor. Flam. Liq. 2 H225 Highly flammable liquid and vapor. Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled ad Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. 	ccording to the Globally Harmonized System (G
 Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS07 Eye Irrit. 2A H319 Causes serious eye irritation. STOT SE 3 H336 May cause drowsiness or dizziness. Label elements GHS label elements The product is classified and labeled ac Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of labeling: Isopropanol Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. 	

Printing date 11/14/2017

Trade name: Isopropyl Alcohol / Acetic Acid Solution Reviewed on 11/14/2017

(Contd. of page 1) Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. *Continue rinsing.* Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 3Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH ² Health = 2FIRE 3 Fire = 3**REACTIVITY O** Reactivity = 0· Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients · Chemical characterization: Mixtures · Description: Mixture of the substances listed below with nonhazardous additions. · Dangerous components:

 CAS: 67-63-0
 Isopropanol
 93.651%

 CAS: 64-19-7
 Acetic Acid
 6.349%

4 First-aid measures

- · Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

(Contd. on page 3)

US

Printing date 11/14/2017

Reviewed on 11/14/2017

Trade name: Isopropyl Alcohol / Acetic Acid Solution

(Contd. of page 2)

- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures
 Wear protective equipment. Keep unprotected persons away.
 Environmental precautions:
 - Dilute with plenty of water.
- Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

- Ensure adequate ventilation.
- · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
CAS: 67-63-0 Isopropanol	400 ppm
CAS: 64-19-7 Acetic Acid	5 ppm
· PAC-2:	
CAS: 67-63-0 Isopropanol	2000* ppm
CAS: 64-19-7 Acetic Acid	35 ppm
· PAC-3:	
CAS: 67-63-0 Isopropanol	12000** ppm
CAS: 64-19-7 Acetic Acid	250 ppm

7 Handling and storage

· Handling:

• Precautions for safe handling No special precautions are necessary if used correctly.

- · Information about protection against explosions and fires:
- Keep ignition sources away Do not smoke. Protect against electrostatic charges.

(Contd. on page 4)

US

Printing date 11/14/2017

Trade name: Isopropyl Alcohol / Acetic Acid Solution Reviewed on 11/14/2017

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
CAS	: 67-63-0 Isopropanol
PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm
	Long-term value: 980 mg/m ³ , 400 ppm
TLV	Short-term value: 984 mg/m³, 400 ppm
	Long-term value: 492 mg/m ³ , 200 ppm
	BEI
CAS	: 64-19-7 Acetic Acid
PEL	Long-term value: 25 mg/m ³ , 10 ppm
REL	Short-term value: 37 mg/m ³ , 15 ppm
	Long-term value: 25 mg/m ³ , 10 ppm
TLV	Short-term value: 37 mg/m ³ , 15 ppm
	Long-term value: 25 mg/m³, 10 ppm
· Ingr	edients with biological limit values:
CAS	: 67-63-0 Isopropanol
BEI	40 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift at end of workweek
	LD50: Acetone (background, nonspecific)
• Addi	itional information: The lists that were valid during the creation were used as basis.
	osure controls
	onal protective equipment:
	eral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing. h hands before breaks and at the end of work.
	d contact with the eyes.
	d contact with the eyes and skin.
	uthing equipment: Not required.
· Prot	ection of hands:
	glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
	to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the nical mixture.
Selec	ction of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 5)

-- US

Printing date 11/14/2017

Trade name: Isopropyl Alcohol / Acetic Acid Solution

Reviewed on 11/14/2017

```
· Material of gloves
```

(Contd. of page 4)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:

Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and of General Information	chemical properties
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Vinegar
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	82 °C (179.6 °F)
Flash point:	13 °C (55.4 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	2 Vol %
Upper:	12 Vol %
Vapor pressure at 20 °C (68 °F):	43 hPa (32.3 mm Hg)
Density at 20 °C (68 °F):	0.79614 g/cm³ (6.64379 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.

US

Printing date 11/14/2017

Reviewed on 11/14/2017

Trade name: Isopropyl Alcohol / Acetic Acid Solution

		(Contd. of page
Partition coefficient (n-octan	ol/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	796.1 g/l / 6.64 lb/gl	
Solids content:	0.0 %	
Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	52,137 mg/kg (rat)
Dermal	LD50	16,697 mg/kg (rabbit)
Inhalative	LC50/4 h	32 mg/l (rat)

CAS: 67-63-0 Isopropanol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

· Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: Irritating effect.

- Sensitization: No sensitizing effects known.
- · Additional toxicological information:
- The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 67-63-0 Isopropanol

(Contd. on page 7)

3

⁻ US

Printing date 11/14/2017

Reviewed on 11/14/2017

Trade name: Isopropyl Alcohol / Acetic Acid Solution

(Contd. of page 6)

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

- Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

UN-Number		
DOT, IMDG, IATA	UN1993	
UN proper shipping name		
DOT	Flammable liquids, n.o.s. (Isopropanol)	
IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (Isopropanol)	
Transport hazard class(es)		
DOT		
3		

Printing date 11/14/2017

Reviewed on 11/14/2017

Trade name: Isopropyl Alcohol / Acetic Acid Solution

	(Contd. of page
- Label	3
· IMDG, IATA	
· Class	3 Flammable liquids
· Label	3
Packing group	
· DOT, IMDG, IATA	II
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Stowage Category	В
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	1L
\cdot Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (ISOPROPANOL), 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):
None of the ingredients is listed.
· Section 313 (Specific toxic chemical listings):
CAS: 67-63-0 Isopropanol
· TSCA (Toxic Substances Control Act):
Isopropanol
Acetic Acid
· Proposition 65
· Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 9)

US -

(Contd. of page 8)

A4

Safety Data Sheet acc. to OSHA HCS

Printing date 11/14/2017

Reviewed on 11/14/2017

Trade name: Isopropyl Alcohol / Acetic Acid Solution

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

• TLV (Threshold Limit Value established by ACGIH)

CAS: 67-63-0 Isopropanol

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• Hazard-determining components of labeling: Isopropanol

· Hazard statements

Highly flammable liquid and vapor. Causes serious eye irritation.

May cause drowsiness or dizziness.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a poison center/doctor if you feel unwell.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 10)

Printing date 11/14/2017

Reviewed on 11/14/2017

Trade name: Isopropyl Alcohol / Acetic Acid Solution

• Chemical safety assessment: A Chemical Safety Assessment has not been carried out. (Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision 11-14-2017: review SDS for accuracy. STN Creation date for SDS 11-12-2014. STN 11/14/2017 / -· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A STOT SE 3: Specific target organ toxicity (single exposure) - Category 3