Printing date 06/05/2015

Reviewed on 06/05/2015

1 Identification

- · Product identifier
- · Trade name: Sulfur PPM QA Material
- · Article number: AM108A
- · Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586 AQUA

- Information department: Product safety department • Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666
- 2 Hazard(s) identification

· Classification of the substance or mixture

GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.

GHS06 Skull and crossbones

Acute Tox. 1 H310 Fatal in contact with skin.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1A H350 May cause cancer.

- STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.
- Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



(Contd. on page 2)

USA

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

• Signal word Danger	(Contd. of page 1)
-	
• Hazard-determining components of labeling: benzene	
· Hazard statements	
Highly flammable liquid and vapor.	
Fatal in contact with skin.	
Causes skin irritation.	
Causes serious eye irritation.	
May cause genetic defects.	
May cause cancer.	
Causes damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
· Precautionary statements	
If medical advice is needed, have product container or label at hand.	
Keep out of reach of children.	
Read label before use.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wear protective gloves / eye protection / face protection.	
Wear protective gloves.	
Wear protective gloves / protective clothing.	
Wear eye protection / face protection.	
Ground/bond container and receiving equipment.	
Do not get in eyes, on skin, or on clothing.	
Keep container tightly closed.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
If swallowed: Immediately call a poison center/doctor.	
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pres	ent and easy to do.
Continue rinsing.	
Specific treatment (see on this label).	
IF exposed or concerned: Get medical advice/attention.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
Get medical advice/attention if you feel unwell.	
Do NOT induce vomiting.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Take off immediately all contaminated clothing and wash it before reuse.	
Store locked up.	
Store in a well-ventilated place. Keep cool.	,•
Dispose of contents/container in accordance with local/regional/national/international regular	tions.
· Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 3	
Fire = 3	
$\frac{3}{0} Reactivity = 0$	
	(Contd. on page 3)

USA

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

(Contd. of page 2)

99.88%

· HMIS-ratings (scale 0 - 4)



• Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 71-43-2 benzene

4 First-aid measures

- · Description of first aid measures
- · General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- · Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

(Contd. of page 3)

 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities • Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
71-4 3	3-2 benzene
PEL	Short-term value: 15* mg/m³, 5* ppm Long-term value: 3* mg/m³, 1* ppm *table Z-2 for exclusions in 29CFR1910.1028(d)
	Short-term value: 1 ppm Long-term value: 0.1 ppm See Pocket Guide App. A
TLV	Short-term value: 8 mg/m³, 2.5 ppm Long-term value: 1.6 mg/m³, 0.5 ppm Skin; BEI
	(Contd. on page 5)
	USA

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

(Contd. of page 4)

-	edients with biological limit values: 3-2 benzene
	25 μg/g creatinine
	LD50 Intraperitoneal: urine
	Time: end of shift Parameter
	LD50: S-Phenylmercapturic acid (background
	500 μg/g creatinine
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: t,t-Muconic acid (background)
Addi	tional information: The lists that were valid during the creation were used as basis.
Frnd	sure controls
	onal protective equipment:
	ral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	hands before breaks and at the end of work.
	protective clothing separately.
	l contact with the eyes and skin.
	thing equipment:
	se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure u
respi	ratory protective device that is independent of circulating air.
	ection of hands:
	Protective gloves
Due	glove material has to be impermeable and resistant to the product/ the substance/ the preparation. to missing tests no recommendation to the glove material can be given for the product/ the preparation/ th ical mixture.
	tion of the glove material on consideration of the penetration times, rates of diffusion and the degradation
	rial of gloves
	velection of the suitable gloves does not only depend on the material, but also on further marks of quality ar
	s from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance
	love material can not be calculated in advance and has therefore to be checked prior to the application.
Pene	tration time of glove material
	exact break through time has to be found out by the manufacturer of the protective gloves and has to b
obset	
Eye p	protection:
	Tightly sealed goggles
	I ignity sectient goggies

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

(Contd. of page 5)

Information on basic physical and ca	hemical properties
General Information	
Appearance:	
Form: Color:	Fluid According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	6 °C (43 °F)
Boiling point/Boiling range:	176 °C (349 °F)
Flash point:	12 °C (54 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	555 °C (1031 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8 Vol %
Vapor pressure at 20 $\bullet C$ (68 $\bullet F$):	100 hPa (75 mm Hg)
Density at 20 °C (68 °F):	0.88 g/cm ³ (7.344 lbs/gal)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with Water at 20 °C (68 °F):	0.7 g/l
Partition coefficient (n-octanol/water	
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	99.9 %
VOC content:	99.9 % 878.9 g/l / 7.34 lb/gl
Solids content:	0.1%
Other information	No further relevant information available.

(Contd. on page 7)

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

(Contd. of page 6)

10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimates))
--------------------------------	---

Oral		LD50	4900 mg/kg (rat)
-	-		

Dermal LD50 48.1 mg/kg (mouse)

71-43-2 benzene

Oral	LD50	4894 mg/kg (rat)
Dermal		48 mg/kg (mouse)
Inhalative	LC50/4 h	9980 mg/l (mouse)

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Irritating effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

71-43-2 benzene

· NTP (National Toxicology Program)

71-43-2 benzene

· OSHA-Ca (Occupational Safety & Health Administration)

All ingredients are listed.

12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.

(Contd. on page 8)

1

K

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

(Contd. of page 7)

- \cdot Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- *Recommendation:* Disposal must be made according to official regulations.

UN-Number DOT, IMDG, IATA	UN1992
UN proper shipping name DOT IMDG, IATA	Flammable liquids, toxic, n.o.s. (Benzene) FLAMMABLE LIQUID, TOXIC, N.O.S. (BENZENE)
Transport hazard class(es)	
DOT	
FUMMARE LOUID 3 6	
- Class	3 Flammable liquids
Label	3+6.1
IMDG, IATA	
Class	3 Flammable liquids
Label	3+6.1
Packing group DOT, IMDG, IATA	I
Environmental hazards: Marine pollutant:	No
Special precautions for user Danger code (Kemler):	Warning: Flammable liquids 336

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

	(Contd. of page 8
· EMS Number:	F-E,S-D
• Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
·DOT	
· Quantity limitations	On passenger aircraft/rail: Forbidden
	On cargo aircraft only: 30 L
· IMDG	
· Limited quantities (LQ)	0
\cdot Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· UN "Model Regulation":	UN1992, Flammable liquids, toxic, n.o.s. (Benzene), 3 (6.1), I

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
All ingredients are listed.	
· TSCA (Toxic Substances Control Act):	
All ingredients are listed.	
· Proposition 65	
· Chemicals known to cause cancer:	
All ingredients are listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
All ingredients are listed.	
· Chemicals known to cause developmental toxicity:	
All ingredients are listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
71-43-2 benzene	A, K/L
· TLV (Threshold Limit Value established by ACGIH)	
71-43-2 benzene	A1
NIOSH-Ca (National Institute for Occupational Safety and Health)	
All ingredients are listed.	
• GHS label elements The product is classified and labeled according to the Globally Harmonized Sys	stem (GHS).

(Contd. on page 10) USA

USA

Safety Data Sheet acc. to OSHA HCS

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

Hazard pictograms	(Contd. of page 9)
GHS02 GHS06 GHS08	
Signal word Danger	
Hazard-determining components of labeling: benzene	
Hazard statements	
Highly flammable liquid and vapor.	
Fatal in contact with skin.	
Causes skin irritation.	
Causes serious eye irritation.	
May cause genetic defects.	
May cause cancer.	
Causes damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
If medical advice is needed, have product container or label at hand.	
Keep out of reach of children.	
Read label before use.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wear protective gloves / eye protection / face protection.	
Wear protective gloves.	
Wear protective gloves / protective clothing.	
Wear eye protection / face protection.	
Ground/bond container and receiving equipment.	
Do not get in eyes, on skin, or on clothing.	
Keep container tightly closed.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Wash thoroughly after handling.	
Do not eat, drink or smoke when using this product.	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
If swallowed: Immediately call a poison center/doctor. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin v	with water/shower
If on skin (or hair). Remove/Take of immediately at contaminated clothing. Kinse skin (If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if p	
Continue rinsing.	eseni una easy 10 a0.
Specific treatment (see on this label).	
IF exposed or concerned: Get medical advice/attention.	
If skin irritation occurs: Get medical advice/attention.	
If eye irritation persists: Get medical advice/attention.	
Get medical advice/attention if you feel unwell.	
Do NOT induce vomiting.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Take off immediately all contaminated clothing and wash it before reuse.	
Store locked up.	
Store in a well-ventilated place. Keep cool.	
~~~~~ <i>r</i> ~~~ <i>r</i> ~~~ <i>r</i> ~~~	

Dispose of contents/container in accordance with local/regional/national/international regulations.

Printing date 06/05/2015

Reviewed on 06/05/2015

Trade name: Sulfur PPM QA Material

(Contd. of page 10)

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. *Exceptions can be made by the authorities in certain cases.* 

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Date of preparation / last revision 06/05/2015 / -

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 1: Acute toxicity, Hazard Category 1

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Muta. 1B: Germ cell mutagenicity, Hazard Category 1B

Carc. 1A: Carcinogenicity, Hazard Category 1A

STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

ISA -

[·] Contact: Mr. Nelson