Printing date 06/17/2024

Reviewed on 06/17/2024

Identification	
Product identifier	
Trade name: Oil & Grease	
QA Standard	
Article number: 6530	
Details of the supplier of the safety data s	sheet
Manufacturer/Supplier: Aqua Solutions, Inc.	AQUA
6913 Highway 225	SOLUTIONS
DEER PARK, TX 77536	
USA 800-256-2586	
Information department: Technical Coordinator	
Sherman Nelson shermann@aquasolution	ns.org
Technical Coordinator	
Sherman Nelson shermann@aquasolution Emergency telephone number:	<i>is.org</i>
<i>Chemtrec: 800-424-9300</i>	
Canutec: 613-996-6666	
Hazard(s) identification	
Classification of the substance or mixtur	<i>p</i>
Classification of the substance or mixtur	e
Classification of the substance or mixture	e
GHS02 Flame	
	e H225 Highly flammable liquid and vapor.
GHS02 Flame Flammable Liquids 2	
GHS02 Flame	
GHS02 Flame Flammable Liquids 2	
GHS02 Flame Flammable Liquids 2 GHS07 Eye Irritation 2A	H225 Highly flammable liquid and vapor.
GHS02 Flame Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness.
GHS02 Flame Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation.
GHS02 Flame Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness.
GHS02 Flame Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness.
GHS02 Flame Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness.
GHS02 Flame Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi Hazard pictograms	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi Hazard pictograms GHS02 GHS07	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness.
GHS02 Flame Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi Hazard pictograms	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness.
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of label	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness. fied and labeled according to the Globally Harmonized System (GHS
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of label Acetone	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness. fied and labeled according to the Globally Harmonized System (GHS
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of label	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness. fied and labeled according to the Globally Harmonized System (GHS
Flammable Liquids 2 Flammable Liquids 2 GHS07 Eye Irritation 2A Specific Target Organ Toxicity - Single E: Label elements GHS label elements The product is classi Hazard pictograms GHS02 GHS07 Signal word Danger Hazard-determining components of label Acetone Hazard statements	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. xposure 3 H336 May cause drowsiness or dizziness. fied and labeled according to the Globally Harmonized System (GHS

Printing date 06/17/2024

Trade name: Oil & Grease QA Standard Reviewed on 06/17/2024

(Contd. of page 1) · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 2Fire = 0Reactivity = 0· HMIS-ratings (scale 0 - 4) HEALTH 2 Health = 2FIRE 0 Fire = 0Reactivity = 0**REACTIVITY** 0 · Other hazards · Results of PBT and vPvB assessment · **PBT:** Not applicable. · vPvB: Not applicable. **3** Composition/information on ingredients

• Chemical characterization: Mixtures

• **Description:** Mixture of the substances listed below with nonhazardous additions.

· Dangerous comp	ponents:	
CAS: 67-64-1 A	cetone	24.385%
· Table of Nonhazardous Ingredients		
CAS: 7732-18-5	Water	75.603%
CAS: 57-11-4	Stearic Acid	0.006%
CAS: 544-76-3	Hexadecane	0.006%
		(Contd. on page 3)

Printing date 06/17/2024

Trade name: Oil & Grease QA Standard

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

(Contd. of page 2) 0.0002%

Reviewed on 06/17/2024

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- *Indication of any immediate medical attention and special treatment needed No further relevant information available.*
- **5** Fire-fighting measures
- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- *Environmental precautions: Dilute with plenty of water.*
- Do not allow to enter sewers/ surface or ground water.
- \cdot Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.
- Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information. • Protective Action Criteria for Chemicals

• PAC-1:		
CAS: 67-64-1	Acetone	200 ppm
CAS: 57-11-4	Stearic Acid	14 mg/m ³
CAS: 544-76-3	Hexadecane	35 mg/m ³
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	$0.20 \ mg/m^3$
· PAC-2:		
CAS: 67-64-1	Acetone	3200* ppm
		(Contd. on page 4)

US

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Oil & Grease QA Standard

		(Contd. of page 3)
CAS: 57-11-4	Stearic Acid	150 mg/m ³
CAS: 544-76-3	Hexadecane	380 mg/m ³
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	8.7 mg/m ³
· PAC-3:		
CAS: 67-64-1	Acetone	5700* ppm
CAS: 57-11-4	Stearic Acid	910 mg/m ³
CAS: 544-76-3	Hexadecane	2,800 mg/m ³
CAS: 7664-93-9	Sulfuric Acid 96 - 98%	160 mg/m ³

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

CAS: 67-64-1 Acetone

PEL Long-term value: 2400 mg/m³, 1000 ppm

REL Long-term value: 590 mg/m³, 250 ppm

TLV Short-term value: 500 ppm

Long-term value: 250 ppm

A4, BEI

· Ingredients with biological limit values:

CAS: 67-64-1 Acetone

BEI 25 mg/L

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Acetone (nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

⁻ US

Printing date 06/17/2024

Trade name: Oil & Grease QA Standard

(Contd. of page 4)

Reviewed on 06/17/2024

Exposure controls
Personal protective equipment:
General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes. Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. • Protection of hands:

H (Call

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

 Information on basic physical and General Information Appearance: 	chemical properties	
Form:	Liquid	
Color:	Clear	
· Odor:	Slight acetone	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	55 °C (131 °F)	
· Flash point:	-17 °C (1.4 °F)	

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Oil & Grease QA Standard

	(Contd. of page
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	465 °C (869 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	2.6 Vol %
Upper:	13 Vol %
· Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
Density at 20 °C (68 °F):	0.9391 g/cm³ (7.83679 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	24.4 %
Water:	75.6 %
VOC content:	0.00 %
	0.0 g/l / 0.00 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

Printing date 06/17/2024

Trade name: Oil & Grease QA Standard Reviewed on 06/17/2024

(Contd. of page 6)

11 Toxicological information · Information on toxicological effects · Acute toxicity: · Primary irritant effect: • on the skin: No irritant effect. • on the eye: Irritating effect. • Sensitization: No sensitizing effects known. · Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Irritant · Carcinogenic categories · IARC (International Agency for Research on Cancer) CAS: 7664-93-9 Sulfuric Acid 96 - 98% 1 · NTP (National Toxicology Program) CAS: 7664-93-9 Sulfuric Acid 96 - 98% K · OSHA-Ca (Occupational Safety & Health Administration) None of the ingredients is listed.

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.

· Behavior in environmental systems:

- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

(Contd. on page 8)

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Oil & Grease QA Standard

(Contd. of page 7)

· UN-Number		
· DOT, ADN, IMDG, IATA	Not regulated	
· UN proper shipping name · DOT, ADN, IMDG, IATA	Not regulated	
· Transport hazard class(es)		
· DOT, ADN, IMDG, IATA		
· Class	Not regulated	
· Packing group		
· DOT, IMDG, IATA	Not regulated	
· Environmental hazards:	Not applicable.	
· Special precautions for user	Not applicable.	
• Transport in bulk according to Annex	II of	
MARPOL73/78 and the IBC Code	Not applicable.	

15 Regulatory information

 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
 Sara

· Section 355 (extremely hazardous substances):

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

 Section 313 (Specific toxic chemical listings): CAS: 7664-93-9 Sulfuric Acid 96 - 98%

• TSCA (Toxic Substances Control Act):

Water	ACTIVE
Acetone	ACTIVE
Stearic Acid	ACTIVE
Hexadecane	ACTIVE
Sulfuric Acid 96 - 98%	ACTIVE
· Hazardous Air Pollutants	

None of the ingredients is listed.

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 9)

US -

Printing date 06/17/2024

Reviewed on 06/17/2024

Trade name: Oil & Grease OA Standard

(Contd. of page 8)

Ι

A4

A2

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 67-64-1 Acetone

• TLV (Threshold Limit Value)

CAS: 67-64-1 Acetone

CAS: 7664-93-9 Sulfuric Acid 96 - 98%

\cdot NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Acetone · Hazard statements Highly flammable liquid and vapor. Causes serious eye irritation. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eve protection/face protection. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If eye irritation persists: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 10)

Printing date 06/17/2024

Trade name: Oil & Grease QA Standard Reviewed on 06/17/2024

(Contd. of page 9)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of Preparation / Last Revision: · Date of preparation / last revision Revision 0.1, 06/17/2024: Reviewed SDS for accuracy. MH/STN 06/17/2024 / 1.0 • Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Eye Irritation 2A: Serious eye damage/eye irritation - Category 2A Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) - Category 3 \cdot * Data compared to the previous version altered.

- US -