Printing date 11/28/2017 Reviewed on 11/28/2017

1 Identification


· Product identifier

· Trade name: Lithium Metal Wire (In Mineral Oil)

· Article number: L5100

• CAS Number: 7439-93-2 • EC number: 231-102-5

• Index number: 003-001-00-4



• Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225

DEER PARK, TX 77536 USA

800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Water-react. 1 H260 In contact with water releases flammable gases, which may ignite spontaneously.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

- · Label elements
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS05

- · Signal word Danger
- · Hazard statements

In contact with water releases flammable gases, which may ignite spontaneously. Causes severe skin burns and eye damage.

· Precautionary statements

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

(Contd. on page 2)

Printing date 11/28/2017 Reviewed on 11/28/2017

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 1)

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, sand, extinguishing powder.

Store in a dry place. Store in a closed container.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3 Fire = 0Reactivity = 2

The substance demonstrates unusual reactivity with water.

· HMIS-ratings (scale 0 - 4)



Health = 3Fire = 0

Reactivity = 2

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Substances
- · CAS No. Description 7439-93-2 lithium
- · Identification number(s)
- · EC number: 231-102-5
- · Index number: 003-001-00-4

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.

(Contd. on page 3)

Printing date 11/28/2017 Reviewed on 11/28/2017

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

Extinguishing powder. Do not use water.

CO2. Do not use water.

Sand. Do not use water.

Special powder for metal fires. Do not use water.

CO2, sand, extinguishing powder. Do not use water.

Use fire fighting measures that suit the environment.

- · For safety reasons unsuitable extinguishing agents: Water
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

- · Protective Action Criteria for Chemicals
- · PAC-1: 3.3 mg/m³
- · PAC-2: 36 mg/m³
- · PAC-3: 220 mg/m3

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Thorough dedusting.

Ensure good ventilation/exhaustion at the workplace.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

(Contd. on page 4)

Printing date 11/28/2017 Reviewed on 11/28/2017

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 3)

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace: Not required.
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

Printing date 11/28/2017 Reviewed on 11/28/2017

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 4)

Physical and chemical proper	ties
Information on basic physical and c	
General Information	nemicui properiies
Appearance:	
Form:	Solid
Color:	White
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not applicable.
Change in condition	
Melting point/Melting range:	180.54 °C (357 °F)
Boiling point/Boiling range:	1,347 °C (33.8 °F)
Flash point:	Not applicable.
Flammability (solid, gaseous):	Contact with water liberates extremely flammable gases.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto igniting:	Not determined.
Danger of explosion:	Not determined.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapor pressure at 20 °C (68 °F):	0 hPa (0 mm Hg)
Density at 20 °C (68 °F):	$0.534 \text{ g/cm}^3 (4.45623 \text{ lbs/gal})$
Relative density	Not determined.
Vapor density	Not applicable.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Insoluble.
Partition coefficient (n-octanol/wate	e r): Not determined.
Viscosity:	
Dynamic:	Not applicable.
Kinematic:	Not applicable.
Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions Contact with water releases flammable gases.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6)

Printing date 11/28/2017 Reviewed on 11/28/2017

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 5)

· Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye: Strong caustic effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

- · Carcinogenic categories
- · IARC (International Agency for Research on Cancer) Substance is not listed.
- · NTP (National Toxicology Program) Substance is not listed.
- · OSHA-Ca (Occupational Safety & Health Administration) Substance is not listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- $\cdot \textit{\textbf{Mobility in soil}} \ \textit{No further relevant information available}.$
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

UN1415

(Contd. on page 7)

Printing date 11/28/2017 Reviewed on 11/28/2017

Trade name: Lithium Metal Wire (In Mineral Oil)

	(Contd. of page
UN proper shipping name	
DOT	Lithium
IMDG, IATA	LITHIUM
Transport hazard class(es)	
DOT	
DANCEROUS TO	
Class	4.3 Substances which, in contact with water, emit flammable gases
Label	4.3
IMDG, IATA	
Class	4.3 Substances which, in contact with water, emit flammable gases
Label	4.3
Packing group DOT, IMDG, IATA	I
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Warning: Substances which, in contact with water, emit flammab
	gases
Danger code (Kemler):	X423
EMS Number:	<u>4.3</u> -01
Stowage Category	E
Handling Code	H1 Keep as dry as reasonably practicable
Segregation Code	SG26 In addition: from goods of classes 2.1 and 3 when stowed a
	deck of a containership a minimum distance of two container space athwartship shall be maintained, when stowed on ro-ro ships
	distance of 6 m athwartship shall be maintained.
	SG35 Stow "separated from" acids.
Transport in bulk according to Annex II o	f
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: Forbidden On cargo aircraft only: 15 kg
<i>IMDG</i>	
Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1415 LITHIUM, 4.3, I

Printing date 11/28/2017 Reviewed on 11/28/2017

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 7)

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances): Substance is not listed.
- · Section 313 (Specific toxic chemical listings): Substance is not listed.
- · TSCA (Toxic Substances Control Act):

lithium

- · Proposition 65
- · Chemicals known to cause cancer: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for females: Substance is not listed.
- · Chemicals known to cause reproductive toxicity for males: Substance is not listed.
- · Chemicals known to cause developmental toxicity: Substance is not listed.
- · Carcinogenic categories
- · EPA (Environmental Protection Agency) Substance is not listed.
- TLV (Threshold Limit Value established by ACGIH) Substance is not listed.
- · NIOSH-Ca (National Institute for Occupational Safety and Health) Substance is not listed.
- · GHS label elements The substance is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS05

- · Signal word Danger
- · Hazard statements

In contact with water releases flammable gases, which may ignite spontaneously.

Causes severe skin burns and eye damage.

· Precautionary statements

Do not allow contact with water.

Handle under inert gas. Protect from moisture.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages.

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, sand, extinguishing powder.

Store in a dry place. Store in a closed container.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

Printing date 11/28/2017 Reviewed on 11/28/2017

Trade name: Lithium Metal Wire (In Mineral Oil)

(Contd. of page 8)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

11-28-2017: review SDS for accuracy. STN Creation date for SDS 11-06-2014. STN 11/28/2017 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International

Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Water-react. 1: Substances and mixtures which in contact with water emit flammable gases - Category 1

Skin Corr. 1B: Skin corrosion/irritation - Category 1B