Printing date 07/01/2024

Reviewed on 07/01/2024

1 Identification

*

*

- · Product identifier
- Trade name: <u>Mixed Alcohol Solvent</u>
- · Article number: BAP001
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier: Aqua Solutions, Inc.
 6913 Highway 225 DEER PARK, TX 77536

USA 800-256-2586

- Information department: Technical Coordinator
 Sherman Nelson shermann@aquasolutions.org
 Emergency telephone number:
- *Chemtrec:* 800-424-9300 *Canutec:* 613-996-6666

2 *Hazard*(s) *identification*

· Classification of the substance or mixture		
GHS02 Flame		
Flammable Liquids 2	H225	Highly flammable liquid and vapor.
GHS06 Skull and crossbones		
Acute Toxicity - Oral 3	H301	Toxic if swallowed.
Acute Toxicity - Dermal 3	H311	Toxic in contact with skin.
Acute Toxicity - Inhalation 3	H331	Toxic if inhaled.
GHS08 Health hazard Specific Target Organ Toxicity - Single Exposure 1	<i>H370</i>	Causes damage to the central nervous system and the visual organs.
GHS05 Corrosion		
Eye Damage 1	H318	Causes serious eye damage.
GHS07		
Skin Irritation 2	H315	Causes skin irritation.
Specific Target Organ Toxicity - Single Exposure 3	Н335-Н336	
		drowsiness or dizziness. (Contd. on page 2)



Printing date 07/01/2024

· Label elements

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

Reactivity = 0

(Contd. of page 1)

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS05 GHS06 GHS08 GHS07 · Signal word Danger · Hazard-determining components of labeling: n-Butyl Alcohol Methanol · Hazard statements Highly flammable liquid and vapor. Toxic if swallowed, in contact with skin or if inhaled. Causes skin irritation. Causes serious eye damage. Causes damage to the central nervous system and the visual organs. May cause respiratory irritation. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. *Use explosion-proof electrical/ventilating/lighting/equipment.* Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Rinse mouth. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF exposed: Call a POISON CENTER or doctor/physician. Call a poison center/doctor if you feel unwell. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Classification system: · NFPA ratings (scale 0 - 4) Health = 3Fire = 3

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

(Contd. of page 2)

63.301%

36.327%

0.372%

· HMIS-ratings (scale 0 - 4)



• Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 71-36-3 n-Butyl Alcohol

CAS: 67-56-1 Methanol

· Table of Nonhazardous Ingredients

CAS: 7732-18-5 Water

4 First-aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

· After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Do not induce vomiting; immediately call for medical help.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.

· Protective equipment: Mouth respiratory protective device.

(Contd. on page 4)

[·] Advice for firefighters

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

(Contd. of page 3)

Personal precau	tions, protective equipment and emergency procedures	
•	ry protective device.	
	equipment. Keep unprotected persons away.	
Environmental p		
Dilute with plent	ty of water.	
	enter sewers/ surface or ground water.	
	aterial for containment and cleaning up:	
-	id-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
Use neutralizing		
*	inated material as waste according to section 13.	
Ensure adequate		
Reference to oth		
	r information on safe handling.	
	r information on personal protection equipment.	
	or disposal information.	
	n Criteria for Chemicals	
PAC-1:		
CAS: 71-36-3 n	-Butyl Alcohol	60 ppm
CAS: 67-56-1 M	1ethanol	530 ppr
<i>PAC-2:</i>		800 ppm
	-Butyl Alcohol	000 ppm
CAS: 71-36-3 n		~ ~
CAS: 71-36-3 n CAS: 67-56-1 M		
PAC-2: CAS: 71-36-3 n. CAS: 67-56-1 M. PAC-3: CAS: 71-36-3 n.	Iethanol	2,100 ppm 2,100 ppm 8000** ppm

7 Handling and storage

· Handling:

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Open and handle receptacle with care.
- Prevent formation of aerosols.
- · Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

Printing date 07/01/2024

*

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

(Contd. of page 4)

	tional information about design of technical systems: No further data; see section 7.
	rol parameters
	ponents with limit values that require monitoring at the workplace:
	: 71-36-3 n-Butyl Alcohol
PEL	Long-term value: 300 mg/m ³ , 100 ppm
REL	Ceiling limit value: 150 mg/m³, 50 ppm Skin
TLV	Long-term value: 20 ppm
	: 67-56-1 Methanol
PEL	Long-term value: 260 mg/m ³ , 200 ppm
	Short-term value: 325 mg/m ³ , 250 ppm
	Long-term value: 260 mg/m ³ , 200 ppm Skin
TLV	Short-term value: 250 ppm
	Long-term value: 200 ppm
	Skin; BEIc
· Ingre	edients with biological limit values:
CAS:	: 67-56-1 Methanol
BEI	15 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: Methanol (background, nonspecific)
· Addi	tional information: The lists that were valid during the creation were used as basis.
· Expo	osure controls
	onal protective equipment:
	ral protective and hygienic measures:
	away from foodstuffs, beverages and feed.
	ediately remove all soiled and contaminated clothing.
	n hands before breaks and at the end of work.
	protective clothing separately.
	d contact with the skin.
	d contact with the eyes and skin.
	thing equipment:
	se of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure us
	ratory protective device that is independent of circulating air.
· Prote	ection of hands:
ſ	η
111	Protective gloves

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot *Material of gloves*

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



*

Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

Information on basic physical and c General Information	
Appearance:	y ,
Form:	Liquid
Color: • Odor:	Clear de l'alcool
Guor:	
	1
• Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64 °C (147.2 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	340 °C (644 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.5 Vol %
Upper:	44 Vol %
· Vapor pressure at 20 °C (68 °F):	128 hPa (96 mm Hg)
Density at 20 °C (68 °F):	0.80616 g/cm ³ (6.72741 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
• Evaporation rate	Not determined.
Solubility in / Miscibility with Water:	Fully miscible.
Partition coefficient (n-octanol/wate	pr). Not determined

(Contd. of page 5)

US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

		(Contd. of page
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	99.6 %	
Water:	0.4~%	
VOC content:	99.63 %	
	803.2 g/l / 6.70 lb/gal	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)			
	LD50	204 mg/kg	
		826 mg/kg	
Inhalative	LC50/4h	8.26 mg/l	

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

- on the eye: Strong irritant with the danger of severe eye injury.
- Sensitization: No sensitizing effects known.

• Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: *Toxic*

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 8)

US-

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT IMDG, IATA	Flammable liquids, n.o.s. (Methanol, Butanols) FLAMMABLE LIQUID, N.O.S. (Methanol, Butanols)
Transport hazard class(es)	
DOT	
RAMABLE LOOD	
- Class	3 Flammable liquids
	(Contd. on pag

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

	(Contd. of page
· Label	3
IMDG, IATA	
Class	3 Flammable liquids
Label	3
Packing group DOT, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user Hazard identification number (Kemler code)	
EMS Number: Stowage Category	F-E,S-D B
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (METHANO) BUTANOLS), 3, II

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- Section 355 (extremely hazardous substances): None of the ingredients is listed.
- · Section 313 (Specific toxic chemical listings):
- CAS: 71-36-3 n-Butyl Alcohol
- CAS: 67-56-1 Methanol
- · TSCA (Toxic Substances Control Act):
- n-Butyl Alcohol
- Methanol
- Water

(Contd. on page 10)

ACTIVE ACTIVE

ACTIVE

US

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

(Contd. of page 9)

D

• Hazardous Air Pollutants CAS: 67-56-1 Methanol

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 67-56-1 Methanol

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 71-36-3 n-Butyl Alcohol

• TLV (Threshold Limit Value)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: n-Butyl Alcohol Methanol · Hazard statements Highly flammable liquid and vapor. Toxic if swallowed, in contact with skin or if inhaled. Causes skin irritation. Causes serious eye damage. Causes damage to the central nervous system and the visual organs. May cause respiratory irritation. May cause drowsiness or dizziness. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection.

(Contd. on page 11)

Printing date 07/01/2024

Reviewed on 07/01/2024

Trade name: Mixed Alcohol Solvent

	(Contd. of page 10)
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Rinse mouth.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with we	iter/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses Continue rinsing.	, if present and easy to do.
IF exposed: Call a POISON CENTER or doctor/physician.	
Call a poison center/doctor if you feel unwell.	
Take off immediately all contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use CO2, powder or water spray to extinguish.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/internationa	l regulations.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.	0
6 Other information	
This information is based on our present knowledge. However, this shall not con- specific product features and shall not establish a legally valid contractual relationship	
· Department issuing SDS: Environment protection department.	
· Contact:	
Date of Preparation / Last Revision:	
\cdot Date of preparation / last revision	
Revision 1.2 07/01/2024: Reviewed SDS for accuracy. MH/STN	
Creation date for SDS 12-29-2014. STN	
07/01/2024 / -	
· Abbreviations and acronyms:	

 Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit Flammable Liquids 2: Flammable liquids – Category 2 Acute Toxicity - Oral 3: Acute toxicity - Category 3 Skin Irritation 2: Skin corrosion/irritation - Category 2 Eye Damage 1: Serious eye damage/eye irritation - Category 1 Specific Target Organ Toxicity - Single Exposure 1: Specific target organ toxicity (single exposure) - Category 1 \cdot * Data compared to the previous version altered.

us -