Printing date 01/04/2018

1 Identification

Reviewed on 01/04/2018

· Product identifier			
• Trade name: <u>Pentar</u>			
	ne 56% w/w Solution		
• Article number: SP			
• Details of the suppli • Manufacturer/Supp	ier of the safety data sheet blier:		
Aqua Solutions, Inc.			
6913 Highway 225 DEER PARK, TX 77	7536		3010110113
USA			
800-256-2586			
• Information departm Technical Coordinat			
Sherman Nelson she	erman@aquasolutions.org		
• Emergency telephon Chemtrec: 800-424-			
Canutec: 613-996-6			
2 Hazard(s) identij	fication		
	e substance or mixture		
	substance of maxime		
GHS02 Fl	lame		
	*** 11 /1 11 11 11	,	
Flam. Liq. 2 H225	Highly flammable liquid and	l vapor.	
	lealth hazard		
	eann nazara		
Repr. 2 H361	Suspected of damaging ferti	lity or the unborn child.	
STOT RE 2 H373	May cause damage to organ	s through prolonged or repe	ated exposure.
Asp. Tox. 1 H304	May be fatal if swallowed an	nd enters airways.	
\wedge			
GHS07			
Chine Lunit 2 11215	Causes skin irritation.		
	May cause drowsiness or di	77110055	
· Label elements			
	The product is classified an	d labeled according to the G	lobally Harmonized System (GHS).
• Hazard pictograms			
GHS02 GHS07	GHS08		
• Signal word Danger			
• Hazard-determining Toluene	g components of labeling:		
			(Contd. on page 2)

US

Printing date 01/04/2018

Reviewed on 01/04/2018

Trade name: Pentane 44% w/w Toluene 56% w/w Solution

	(Contd. of page 1)
Pentane	
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of damaging fertility or the unborn child.	
May cause drowsiness or dizziness.	
May cause damage to organs through prolonged or repeated exposure.	
May be fatal if swallowed and enters airways.	
· Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Do not breathe dust/fume/gas/mist/vapors/spray.	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.	
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Get medical advice/attention if you feel unwell.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If skin irritation occurs: Get medical advice/attention.	
Take off contaminated clothing and wash it before reuse.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	<i>S</i> .
· Classification system:	
· NFPA ratings (scale 0 - 4)	
Health = 1	
$4 \qquad Fire = 4$	
$\frac{1}{10} \frac{1}{Reactivity} = 0$	
$\bigvee \bigvee \operatorname{Keucuvuy} = 0$	
· HMIS-ratings (scale 0 - 4)	
HEALTH 1 Health = 1	
FIRE 4 $Fire = 4$	
REACTIVITY Reactivity = 0	

• Other hazards

- Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable.

(Contd. on page 3)

US

Printing date 01/04/2018

Reviewed on 01/04/2018

Trade name: Pentane 44% w/w

Toluene 56% w/w Solution

(Contd. of page 2)

56.0%

44.0%

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

٠Ì	Dangerous	components:
----	-----------	-------------

- CAS: 108-88-3 Toluene
- CAS: 109-66-0 Pentane

4 First-aid measures

- · Description of first aid measures
- General information:
- Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- \cdot After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

• <i>Personal precautions, protective equipment and emergency procedures</i> Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
• Environmental precautions: Do not allow to enter sewers/ surface or ground water.
• Methods and material for containment and cleaning up:
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
· Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

(Contd. on page 4)

US

Printing date 01/04/2018

Reviewed on 01/04/2018

Trade name: Pentane 44% w/w Toluene 56% w/w Solution

· Protective Action Criteria for Chemicals	(Contd. of page 3
· PAC-1:	
CAS: 108-88-3 Toluene	67 ppm
CAS: 109-66-0 Pentane	3000* ppm
· PAC-2:	
CAS: 108-88-3 Toluene	560 ppm
CAS: 109-66-0 Pentane	33000*** ppm
· PAC-3:	<u>_</u>
CAS: 108-88-3 Toluene	3700* ppm
CAS: 109-66-0 Pentane	200000*** ppm

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- Conditions for safe storage, including any incompatibilities • Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- $\cdot \textit{Specific end use}(s) \textit{ No further relevant information available}.$

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Components with lin	nit values that re	auire monitoring	at the workplace:
· · · · · · · · · · · · · · · · · · ·		1 0	···· · · · · · · · · · · · · · · · · ·

CA.	S: 108-88-3 Toluene	
PEI	L Long-term value: 200 ppm Ceiling limit value: 300: 500* ppm	
	Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift	
REI	L Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm	
TLV	⁷ Long-term value: 75 mg/m ³ , 20 ppm BEI	
	•	(Cantil an arrest

(Contd. on page 5)

US

(Contd. of page 4)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2018

Reviewed on 01/04/2018

Trade name: Pentane 44% w/w Toluene 56% w/w Solution

CAS: 109-66-0 Pentane
PEL Long-term value: 2950 mg/m ³ , 1000 ppm
REL Long-term value: 350 mg/m ³ , 120 ppm
Ceiling limit value: 1800* mg/m³, 610* ppm
*15-min
TLV Long-term value: 2950 mg/m ³ , 1000 ppm
· Ingredients with biological limit values:
CAS: 108-88-3 Toluene
BEI 0.02 mg/L
LD50 Intraperitoneal: blood
Time: prior to last shift of workweek
LD50: Toluene
0.03 mg/L
LD50 Intraperitoneal: urine
Time: end of shift
LD50: Toluene
0.3 mg/g creatinine
LD50 Intraperitoneal: urine
Time: end of shift
LD50: o-Cresol with hydrolysis (background)
• Additional information: The lists that were valid during the creation were used as basis.
· Exposure controls
· Personal protective equipment:
• General protective and hygienic measures:
Keep away from foodstuffs, beverages and feed.

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

• Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

US

Printing date 01/04/2018

Trade name: Pentane 44% w/w Toluene 56% w/w Solution

Reviewed on 01/04/2018

(Contd. of page 5)

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and o	hemical properties
General Information	
Appearance:	
Form:	Liquid
Color:	Clear
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	36 °C (96.8 °F)
Flash point:	-35 °C (-31 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	285 °C (545 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	7.8 Vol %
Vapor pressure at 20 °C (68 °F):	573 hPa (429.8 mm Hg)
Density at 20 °C (68 °F):	0.76097 g/cm³ (6.35029 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wate	r): Not determined.
Viscosity:	
Dynamic:	Not determined.

Printing date 01/04/2018

Reviewed on 01/04/2018

Trade name: Pentane 44% w/w Toluene 56% w/w Solution

		(Contd. of page 6
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	100.0 %	
VOC content:	100.00 %	
	761.0 g/l / 6.35 lb/gl	
Solids content:	0.0 %	
• Other information	No further relevant information available.	

10 Stability and reactivity

· Reactivity No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.

 \cdot Conditions to avoid No further relevant information available.

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

 Oral
 LD50
 >3,012 mg/kg (rat)

 Inhalative
 LC50/4 h
 >45.5 mg/l (rat)

· Primary irritant effect:

- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 108-88-3 Toluene

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

· Toxicity

• Aquatic toxicity: No further relevant information available.

3

⁻ US

(Contd. of page 7)

Safety Data Sheet acc. to OSHA HCS

Printing date 01/04/2018

Reviewed on 01/04/2018

Trade name: Pentane 44% w/w Toluene 56% w/w Solution

· Persistence and degradability No further relevant information available.

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- *PBT:* Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

· UN-Number	1011002
· DOT, IMDG, IATA	UN1993
· UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Pentanes, Toluene)
·IMDG	FLAMMABLE LIQUID, N.O.S. (PENTANES, TOLUENE), MARIN POLLUTANT
·IATA	FLAMMABLE LIQUID, N.O.S. (PENTANES, TOLUENE)
• Transport hazard class(es)	
Class Label	3 Flammable liquids 3

Printing date 01/04/2018

Reviewed on 01/04/2018

Trade name: Pentane 44% w/w Toluene 56% w/w Solution

	(Contd. of page
Label	3
IATA	
3	
Class	3 Flammable liquids
Label	3 Fiammable liquids
Packing group DOT, IMDG, IATA	11
Environmental hazards:	Product contains environmentally hazardous substances: Pentane
Marine pollutant:	Yes Such al (fish and tree)
	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	F-E, <u>S-E</u> B
Stowage Category	5
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (\widetilde{EQ})	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (PENTANE
	TOLUENE), 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 108-88-3 Toluene

· TSCA (Toxic Substances Control Act):

Toluene

Pentane

(Contd. on page 10)

⁻ US

Printing date 01/04/2018

Reviewed on 01/04/2018

Trade name: Pentane 44% w/w

Toluene 56% w/w Solution

(Contd. of page 9)

II

A4

· Proposition 65

 \cdot Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

 \cdot Chemicals known to cause developmental toxicity:

CAS: 108-88-3 Toluene

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 108-88-3 Toluene

· TLV (Threshold Limit Value established by ACGIH)

CAS: 108-88-3 Toluene

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

· Hazard-determining components of labeling: Toluene Pentane · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of damaging fertility or the unborn child. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor.

(Contd. on page 11)

US

Printing date 01/04/2018

Reviewed on 01/04/2018

Trade name: Pentane 44% w/w Toluene 56% w/w Solution

(Contd. of page 10)

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
IF exposed or concerned: Get medical advice/attention.
Call a poison center/doctor if you feel unwell.
Get medical advice/attention if you feel unwell.
Specific treatment (see on this label).
Do NOT induce vomiting.
If skin irritation occurs: Get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use for extinction: CO2, powder or water spray.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

· Contact:

Date of preparation / last revision
01-04-2018: review SDS for accuracy. STN
Creation date for SDS 01-27-2015. STN
01/04/2018 / Abbreviations and acronyms:
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
DOT: US Department of Transportation

IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit **BEI:** Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Repr. 2: Reproductive toxicity - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard - Category 1