

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

1 Identification

- **Product identifier**
- **Trade name:** Hexanes (From Petroleum)
Technical Grade
- **Article number:** H1955
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**
Hexane

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 1)

Naphtha (petroleum), hydrotreated light

Cyclohexane

Methylcyclopentane 98%

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of fire: Use for extinction: CO₂, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store away from flammable substances.

Store away from oxidizing agents.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: Hexanes (From Petroleum)
Technical Grade

· **vPvB:** Not applicable.

(Contd. of page 2)

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 110-54-3	Hexane	50.0%
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	34.0%
CAS: 96-37-7	Methylcyclopentane 98%	15.0%
CAS: 110-82-7	Cyclohexane	1.0%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Immediately remove any clothing soiled by the product.
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 3)

- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· **PAC-1:**

CAS: 110-54-3	Hexane	260 ppm
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	1,000 mg/m ³
CAS: 96-37-7	Methylcyclopentane 98%	14 ppm
CAS: 110-82-7	Cyclohexane	300 ppm

· **PAC-2:**

CAS: 110-54-3	Hexane	2900* ppm
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	11,000 mg/m ³
CAS: 96-37-7	Methylcyclopentane 98%	160 ppm
CAS: 110-82-7	Cyclohexane	1700* ppm

· **PAC-3:**

CAS: 110-54-3	Hexane	8600** ppm
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	66,000 mg/m ³
CAS: 96-37-7	Methylcyclopentane 98%	940 ppm
CAS: 110-82-7	Cyclohexane	10000** ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 4)

CAS: 110-54-3 Hexane

PEL Long-term value: 1800 mg/m³, 500 ppm

REL Long-term value: 180 mg/m³, 50 ppm

TLV Long-term value: 176 mg/m³, 50 ppm
 Skin; BEI

CAS: 96-37-7 Methylcyclopentane 98%

REL Long-term value: 350 mg/m³, 100 ppm
 Ceiling limit value: 1800* mg/m³, 510* ppm
 *15-min

TLV Short-term value: 3500 mg/m³, 1000 ppm
 Long-term value: 1760 mg/m³, 500 ppm

CAS: 110-82-7 Cyclohexane

PEL Long-term value: 1050 mg/m³, 300 ppm

REL Long-term value: 1050 mg/m³, 300 ppm

TLV Long-term value: 344 mg/m³, 100 ppm

· Ingredients with biological limit values:**CAS: 110-54-3 Hexane**

BEI 0.4 mg/L
 LD50 Intraperitoneal: urine
 Time: end of shift at end of workweek
 LD50: 2,5-Hexanedione without hydrolysis

· **Additional information:** The lists that were valid during the creation were used as basis.

· Exposure controls**· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
 Immediately remove all soiled and contaminated clothing.
 Wash hands before breaks and at the end of work.
 Store protective clothing separately.
 Avoid contact with the skin.
 Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: *Hexanes (From Petroleum)*
Technical Grade

(Contd. of page 5)

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Liquid

Color: Colorless

· **Odor:** Organic

· **Odor threshold:** Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 67 °C (152.6 °F)

· **Flash point:** -18 °C (-0.4 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Ignition temperature:** 240 °C (464 °F)

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 1.2 Vol %

Upper: 7.4 Vol %

· **Vapor pressure at 20 °C (68 °F):** 160 hPa (120 mm Hg)

· **Density:** Not determined.

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.

· **Viscosity:**

Dynamic: Not determined.

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 6)

Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	85.0 %
VOC content:	85.00 %
	850.0 g/l / 7.09 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

ATE (Acute Toxicity Estimate)

Oral LD50 3,333 mg/kg

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

None of the ingredients is listed.

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: Hexanes (From Petroleum)
Technical Grade




(Contd. of page 7)

- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---------------------------|
| · UN-Number | UN1208 |
| · DOT, IMDG, IATA | |
| · UN proper shipping name | Hexanes |
| · DOT | HEXANES, MARINE POLLUTANT |
| · IMDG | HEXANES |
| · IATA | |
| · Transport hazard class(es) | |
| · DOT | |
|  | |
| · Class | 3 Flammable liquids |
| · Label | 3 |
| · IMDG | |
|   | |
| · Class | 3 Flammable liquids |

(Contd. on page 9)

Safety Data Sheet


acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 8)

· Label	3
· IATA	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, IMDG, IATA	II
· Environmental hazards:	Product contains environmentally hazardous substances: Cyclohexane
· Marine pollutant:	Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code):	33
· EMS Number:	F-E,S-D
· Stowage Category	E
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1208 HEXANES, 3, II

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 110-54-3 Hexane

CAS: 110-82-7 Cyclohexane

· **TSCA (Toxic Substances Control Act):**

Hexane

ACTIVE

Naphtha (petroleum), hydrotreated light

ACTIVE

Methylcyclopentane 98%

ACTIVE

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 9)

Cyclohexane

ACTIVE

· **Hazardous Air Pollutants**

CAS: 110-54-3 Hexane

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

CAS: 110-54-3 Hexane

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

CAS: 110-54-3 Hexane

II

CAS: 110-82-7 Cyclohexane

I

· **TLV (Threshold Limit Value)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Hexane

Naphtha (petroleum), hydrotreated light

Cyclohexane

Methylcyclopentane 98%

· **Hazard statements**

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 05/19/2021

Reviewed on 05/19/2021

Trade name: *Hexanes (From Petroleum)*
Technical Grade

(Contd. of page 10)

Take precautionary measures against static discharge.
 Wash thoroughly after handling.
 Wear protective gloves / eye protection / face protection.
 If swallowed: Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Do NOT induce vomiting.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Get medical advice/attention if you feel unwell.
 Take off immediately all contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Remove contact lenses, if present and easy to do. Continue rinsing.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep cool.
 Store away from flammable substances.
 Store away from oxidizing agents.
 Dispose of contents/container in accordance with local/regional/national/international regulations.
 • **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.
- **Contact:**
- **Date of preparation / last revision**
 Revision 0.1, 05-10-2017: included 0.2 um Filtered in description. STN
 Revision 1.0, 05-07-2021: Updated hazard information. STN
 05/19/2021 / -
- **Abbreviations and acronyms:**
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 BEI: Biological Exposure Limit
 Flam. Liq. 2: Flammable liquids – Category 2
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
 Asp. Tox. 1: Aspiration hazard – Category 1