Printing date 06/27/2024 Reviewed on 06/27/2024

1 Identification

· Product identifier

· Trade name: <u>Hexanes (From Petroleum)</u>

Technical Grade

· Article number: H1955

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Toxic to Reproduction 2 H361 Suspected of damaging fertility or the unborn child.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to organs through prolonged or repeated exposure.

Aspiration Hazard 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irritation 2
Specific Target Organ Toxicity - Single Exposure 3

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 1)

· Hazard-determining components of labeling:

Hexane

Naphtha (petroleum), hydrotreated light

Cyclohexane

Methylcyclopentane 98%

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store away from flammable substances.

Store away from oxidizing agents.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 1 Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.

(Contd. on page 3)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 2)

· vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · **Description**: Mixture of the substances listed below with nonhazardous additions.

	· Dangerous components:		
Γ	CAS: 110-54-3	Hexane	50.0%
Γ	CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	34.0%
Γ	CAS: 96-37-7	Methylcyclopentane 98%	15.0%
Γ	CAS: 110-82-7	Cyclohexane	1.0%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

(Contd. on page 4)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 3)

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 110-54-3	Hexane	260 ppm
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	$1,000 \ mg/m^3$
CAS: 96-37-7	Methylcyclopentane 98%	14 ppm
CAS: 110-82-7	Cyclohexane	300 ppm
· PAC-2:		
CAS: 110-54-3	Hexane	2900* ppm
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	$11,000 \text{ mg/m}^3$
CAS: 96-37-7	Methylcyclopentane 98%	160 ppm
CAS: 110-82-7	Cyclohexane	1700* ppm
· PAC-3:		
CAS: 110-54-3	Hexane	8600** ppm
CAS: 64742-49-0	Naphtha (petroleum), hydrotreated light	66,000 mg/m³
CAS: 96-37-7	Methylcyclopentane 98%	940 ppm
CAS: 110-82-7	Cyclohexane	10000** ppm

7 Handling and storage

- · Handling
- · Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 110-54-3 Hexane

PEL Long-term value: 1800 mg/m³, 500 ppm

(Contd. on page 5)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum)
Technical Grade

	(Contd. of page 4)
REL	Long-term value: 180 mg/m³, 50 ppm
TLV	Long-term value: 50 ppm
	Skin; BEI
CAS	: 64742-49-0 Naphtha (petroleum), hydrotreated light
TLV	Long-term value: 100 ppm
	Skin, A3
CAS	: 96-37-7 Methylcyclopentane 98%
REL	Long-term value: 350 mg/m³, 100 ppm
	Ceiling limit value: 1800* mg/m³, 510* ppm
	*15-min
TLV	Short-term value: 3500 mg/m³, 1000 ppm
G 4 6	Long-term value: 1760 mg/m³, 500 ppm
	: 110-82-7 Cyclohexane
	Long-term value: 1050 mg/m³, 300 ppm
REL	Long-term value: 1050 mg/m³, 300 ppm
TLV	Long-term value: 100 ppm
	BEI
· Ingr	edients with biological limit values:
CAS	: 110-54-3 Hexane
BEI	0.5 mg/L
	LD50 Intraperitoneal: urine
	Time: end of shift
	LD50: 2.5-Hexanedione without hydrolysis
	: 110-82-7 Cyclohexane
BEI	NIC-50 mg/g creatinine
	LD50 Intraperitoneal: -
	Time: end of shift at end of workweek LD50: NIC-1.2-Cyclohexanediol (nonspecific)
	LD30. 1VIC-1.2-Cyclonexaneuloi (nonspecylc)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 6)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 5)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

 Information 	on basic physical	l and chemical properties
---------------------------------	-------------------	---------------------------

· General Information

· Appearance:

Form: Liquid
Color: Colorless
Odor: Organic
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:67 °C (152.6 °F)

• Flash point: $-18 \, ^{\circ}C \, (-0.4 \, ^{\circ}F)$

 $\cdot \textit{Flammability (solid, gaseous):} \qquad \qquad \textit{Highly flammable}.$

• Auto igniting: $240 \, ^{\circ}C \, (464 \, ^{\circ}F)$

Decomposition temperature: Not determined.
 Ignition temperature: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

· Explosion limits:

 Lower:
 1.2 Vol %

 Upper:
 7.4 Vol %

· Vapor pressure at 20 °C (68 °F): 160 hPa (120 mm Hg)

Density: Not determined.Relative density Not determined.

Vapor density
 Evaporation rate
 Not determined.
 Not determined.

(Contd. on page 7)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum)
Technical Grade

		(Contd. of page
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/w	ater): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	85.0 %	
VOC content:	85.00 %	
	850.0 g/l / 7.09 lb/gal	
Solids content:	0.0 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 3,333 mg/kg

- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

(Contd. on page 8)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

UN1208

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

- · UN-Number
- · DOT, IMDG, IATA

· UN proper shipping name

 \cdot **DOT** Hexanes

· IMDG HEXANES, MARINE POLLUTANT

· IATA HEXANES

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

(Contd. on page 9)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum) Technical Grade

	(Contd. of pag
· Label	3
· IMDG	
1 1 1 1 1 1 1 1 1 1	
· Class	3 Flammable liquids
·Label	3
· IATA	
· Class	2 Elammahla liquida
· Cuss · Label	3 Flammable liquids 3
Packing group	
· DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substance Cyclohexane
Marine pollutant:	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler code):	33
EMS Number:	F- E , S - D
Stowage Category	E
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
· DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
Z	On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN "Model Regulation":	UN 1208 HEXANES, 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 10)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 9) · Section 313 (Specific toxic chemical listings): CAS: 110-54-3 Hexane CAS: 110-82-7 Cyclohexane · TSCA (Toxic Substances Control Act): **ACTIVE** Hexane Naphtha (petroleum), hydrotreated light **ACTIVE** *ACTIVE* Methylcyclopentane 98% Cyclohexane ACTIVE· Hazardous Air Pollutants CAS: 110-54-3 Hexane · Proposition 65 · Chemicals known to cause cancer: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for females: None of the ingredients is listed. · Chemicals known to cause reproductive toxicity for males: CAS: 110-54-3 Hexane · Chemicals known to cause developmental toxicity: None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)			
CAS: 110-54-3	Hexane	II	
CAS: 110-82-7	Cyclohexane	I	
· TLV (Threshold Limit Value)			
None of the ingredients is listed.			
· NIOSH-Ca (National Institute for Occupational Safety and Health)			
None of the ing	None of the ingredients is listed.		

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling:

Hexane

Naphtha (petroleum), hydrotreated light

Cyclohexane

Methylcyclopentane 98%

· Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Suspected of damaging fertility or the unborn child.

(Contd. on page 11)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum)
Technical Grade

(Contd. of page 10)

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wash thoroughly after handling.

Wear protective gloves / eye protection / face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off immediately all contaminated clothing and wash it before reuse.

 ${\it If skin irritation occurs: Get medical advice/attention.}$

If eye irritation persists: Get medical advice/attention.

Remove contact lenses, if present and easy to do. Continue rinsing.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store away from flammable substances.

Store away from oxidizing agents.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:

Date of Preparation / Last Revision:

· Date of preparation / last revision

Revision 1.2 06/27/2024: Reviewed SDS for accuracy. MH/STN

Revision 0.0, 05-29-2024: Creation date for SDS. STN

06/27/2024 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

(Contd. on page 12)

Printing date 06/27/2024 Reviewed on 06/27/2024

Trade name: Hexanes (From Petroleum) Technical Grade

(Contd. of page 11)

vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2 Skin Irritation 2: Skin corrosion/irritation – Category 2 Toxic to Reproduction 2: Reproductive toxicity – Category 2

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3
Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

IIS