Printing date 03/03/2022 Reviewed on 03/03/2022

1 Identification

· Product identifier

· Trade name: Ethyl Alcohol, Denatured

· Article number: E2424

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Specific Target Organ Toxicity - Single Exposure 2 H371 May cause damage to the central nervous system and the visual organs.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Methanol

Methyl Ethyl Ketone

n-Heptane

Ethyl Acetate

· Hazard statements

Highly flammable liquid and vapor.

May cause damage to the central nervous system and the visual organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

(Contd. on page 2)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol, Denatured

(Contd. of page 1)

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Call a poison center/doctor.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 3Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*1 *Health* = *1

Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	92.0%
CAS: 67-56-1	Methanol	4.0%
CAS: 78-93-3	Methyl Ethyl Ketone	2.0%
CAS: 141-78-6		1.0%
CAS: 142-82-5	n-Heptane	1.0%

4 First-aid measures

- · Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.

(Contd. on page 3)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol, Denatured

(Contd. of page 2)

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

- · Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- $\cdot \textit{Methods and material for containment and cleaning up:} \\$

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

PAC-1:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 78-93-3	Methyl Ethyl Ketone	200 ppm
CAS: 141-78-6	Ethyl Acetate	1,200 ppn
CAS: 142-82-5	n-Heptane	500 ppm
PAC-2:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppn
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 78-93-3	Methyl Ethyl Ketone	2700* ppn
CAS: 141-78-6	Ethyl Acetate	1,700 ppm
CAS: 142-82-5	n-Heptane	830 ppm
PAC-3:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
		(Contd. on page

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol, Denatured

		(Contd. of page 3)
CAS: 67-56-1	Methanol	7200* ppm
CAS: 78-93-3	Methyl Ethyl Ketone	4000* ppm
CAS: 141-78-6	Ethyl Acetate	10000** ppm
CAS: 142-82-5	n-Heptane	5000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

CAS:	64-17-5 Ethyl Alcohol, Absolute 200 Proof
PEL	Long-term value: 1900 mg/m³, 1000 ppm
REL	Long-term value: 1900 mg/m³, 1000 ppm
	Short-term value: 1000 ppm A3
CAS:	67-56-1 Methanol
PEL	Long-term value: 260 mg/m³, 200 ppm
	Short-term value: 325 mg/m³, 250 ppm Long-term value: 260 mg/m³, 200 ppm Skin
	Short-term value: 250 ppm Long-term value: 200 ppm Skin; BEI
CAS:	78-93-3 Methyl Ethyl Ketone
PEL	Long-term value: 590 mg/m³, 200 ppm
	(Contd. on page .

ge 3)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol, Denatured

(Contd. of page 4) REL Short-term value: 885 mg/m³, 300 ppm Long-term value: 590 mg/m³, 200 ppm TLV Short-term value: 300 ppm Long-term value: 200 ppm BEICAS: 141-78-6 Ethyl Acetate PEL Long-term value: 1400 mg/m³, 400 ppm REL Long-term value: 1400 mg/m³, 400 ppm TLV Long-term value: 400 ppm CAS: 142-82-5 n-Heptane PEL Long-term value: 2000 mg/m³, 500 ppm REL Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm *15-min TLV Short-term value: 500 ppm Long-term value: 400 ppm · Ingredients with biological limit values: CAS: 67-56-1 Methanol BEI 15 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Methanol (background, nonspecific) CAS: 78-93-3 Methyl Ethyl Ketone BEI 2 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Methyl ethyl ketone (nonspecific)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation (Contd. on page 6)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol, Denatured

· Material of gloves

(Contd. of page 5)

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

α \mathbf{D}	•	1		•	- 7			
9 Ph	vercal	and	\sim 1	101111	σ	nra	nort	100
			-	изник	1444		<i>119</i> 8 9	1190

· Information on basic physical and c	rhemical properties
· General Information	
· Appearance:	
Form:	Fluid
Color:	According to product specification
· Odor:	Characteristic
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	78 °C (172.4 °F)
· Flash point:	13 °C (55.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	425 °C (797 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	3.5 Vol %
Upper:	19 Vol %
· Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
· Density at 20 °C (68 °F):	0.79 g/cm³ (6.59255 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	e r): Not determined.

(Contd. on page 7)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol, Denatured

	(Contd. of page
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	100.0 %
VOC content:	100.00 %
	790.0 g/l / 6.59 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· <i>LD/LC50</i> 1	· LD/LC50 values that are relevant for classification:		
ATE (Acut	ATE (Acute Toxicity Estimate)		
Oral	LD50	2,500 mg/kg	
Dermal	LD50	7,500 mg/kg	
Inhalative		· ·	

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

· Carcinogenic categories

· Carcinogenic categories	
· IARC (International Agency for Research on Cancer)	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	1
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

US

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol, Denatured

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- $\cdot \textit{Bioaccumulative potential No further relevant information available}.$
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

	 r	. •
ransport	Orma	700
rummuri		,,,,,,

•	UN-Number
---	-----------

· DOT, IMDG, IATA

· UN proper shipping name

 $\cdot DOT$ Flammable liquids, n.o.s. (Ethanol, Methanol)

· IMDG, IATA FLAMMABLE LIQUID, N.O.S. (Ethanol, Methanol)

UN1993

- · Transport hazard class(es)
- $\cdot DOT$



· Class 3 Flammable liquids

· Label

· IMDG, IATA



3 Flammable liquids · Class

· Label 3

(Contd. on page 9)

Reviewed on 03/03/2022 Printing date 03/03/2022

Trade name: Ethyl Alcohol, Denatured

	(Contd. of page
Packing group	
· DOT, IMDG, IATA	II
Environmental hazards:	
· Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code)	: 33
EMS Number:	F- E , S - E
· Stowage Category	B
Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
~ ,	On cargo aircraft only: 60 L
· IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
• • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANO
-	METHANOL), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

· Sara	
· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
CAS: 67-56-1 Methanol	
· TSCA (Toxic Substances Control Act):	
Ethyl Alcohol, Absolute 200 Proof	ACTIVE
Methanol	ACTIVE
Methyl Ethyl Ketone	ACTIVE
Ethyl Acetate	ACTIVE
n-Heptane	ACTIVE
· Hazardous Air Pollutants	<u> </u>
CAS: 67-56-1 Methanol	

· Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 10)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol, Denatured

	(Contd. of page 9)
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	
CAS: 67-56-1 Methanol	

· Carcinogenic categories

8			
· EPA (Environ	mental Protection Agency)		
CAS: 78-93-3	Methyl Ethyl Ketone	I	
CAS: 142-82-5	n-Heptane	D	
· TLV (Threshol	ld Limit Value)		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	A3	
· NIOSH-Ca (National Institute for Occupational Safety and Health)			
None of the ing	redients is listed.		

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Methanol

Methyl Ethyl Ketone

n-Heptane

Ethyl Acetate

· Hazard statements

Highly flammable liquid and vapor.

May cause damage to the central nervous system and the visual organs.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Call a poison center/doctor.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

(Contd. on page 11)

Printing date 03/03/2022 Reviewed on 03/03/2022

Trade name: Ethyl Alcohol, Denatured

(Contd. of page 10)

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Creation date for SDS 07-21-2015. STN

03/03/2022 / 1.0

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Specific Target Organ Toxicity - Single Exposure 2: Specific target organ toxicity (single exposure) - Category 2

 \cdot * Data compared to the previous version altered.

US ·