Printing date 01/05/2018 Reviewed on 01/05/2018

1 Identification

· Product identifier

· Trade name: Aggregates Sand Stock ASTM D2419

· Article number: SPX372

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300

Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



GHS08 Health hazard

Muta. 2 H341 Suspected of causing genetic defects.

Carc. 1A H350 May cause cancer.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07

GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Formaldehyde

· Hazard statements

Causes skin irritation.

Causes serious eye irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

(Contd. on page 2)

Printing date 01/05/2018 Reviewed on 01/05/2018

Trade name: Aggregates Sand Stock ASTM D2419

(Contd. of page 1)

May cause cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 2 Fire = 1Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = 2 Fire = 1Reactivity = 1

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 56-81-5	Glycerin (Glycerol)	45.853%	
CAS: 10035-04-8	Calcium Chloride Dihydrate	13.46%	
CAS: 50-00-0	Formaldehyde	1.049%	

· Table of Nonhazardous Ingredients				
CAS: 7732-18-5 Water	39.638%			

U.S

Printing date 01/05/2018 Reviewed on 01/05/2018

Trade name: Aggregates Sand Stock ASTM D2419

(Contd. of page 2)

4 First-aid measures

- · Description of first aid measures
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- · Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

1.01001170112011011	er u.e. u ye. ercenneuns			
· PAC-1:				
CAS: 56-81-5	Glycerin (Glycerol)	45 mg/m ³		
CAS: 10035-04-8	Calcium Chloride Dihydrate	16 mg/m³		
CAS: 50-00-0 Formaldehyde				
· PAC-2:				
CAS: 56-81-5	Glycerin (Glycerol)	$180 mg/m^3$		
CAS: 10035-04-8	Calcium Chloride Dihydrate	170 mg/m^3		
CAS: 50-00-0	Formaldehyde	14 ppm		
· PAC-3:				
CAS: 56-81-5	Glycerin (Glycerol)	$1,100 \text{ mg/m}^3$		
		(Contd. on page 4)		

Printing date 01/05/2018 Reviewed on 01/05/2018

Trade name: Aggregates Sand Stock ASTM D2419

		(Contd. of page 3)
CAS: 10035-04-8	Calcium Chloride Dihydrate	$1,100 \text{ mg/m}^3$
CAS: 50-00-0	Formaldehyde	56 ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

CAS	CAS: 56-81-5 Glycerin (Glycerol)				
PEL	Long-term value: 15* 5** mg/m³ mist; *total dust **respirable fraction				
TLV TLV withdrawn-insufficient data human occup. exp.					
CAS	: 50-00-0 Formaldehyde				
PEL	Short-term value: 2 ppm Long-term value: 0.75 ppm see 29 CFR 1910.1048(c)				
REL	Long-term value: 0.016 ppm Ceiling limit value: 0.1* ppm *15-min; See Pocket Guide App. A				
TLV	Short-term value: 0.37 mg/m³, 0.3 ppm Long-term value: 0.12 mg/m³, 0.1 ppm DSEN; RSEN				

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

(Contd. on page 5)

Printing date 01/05/2018 Reviewed on 01/05/2018

Trade name: Aggregates Sand Stock ASTM D2419

(Contd. of page 4)

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

 $The \ glove \ material \ has \ to \ be \ impermeable \ and \ resistant \ to \ the \ product / \ the \ substance / \ the \ preparation.$

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· Information	on basic	nhycical	and chamica	I proporties
· iniormation	on pasic	pnvsicai	ana cnemica	i properiies

· General Information

· Appearance:

Form: Liquid

Color: Clear water white to distinct yellow

Odor: OrganicOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:Undetermined.Boiling point/Boiling range:100 °C (212 °F)

Flash point: 160 °C (320 °F)
 Flammability (solid, gaseous): Not applicable.

• Ignition temperature: 400 °C (752 °F)

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

• Danger of explosion: Product does not present an explosion hazard.

(Contd. on page 6)

Printing date 01/05/2018 Reviewed on 01/05/2018

Trade name: Aggregates Sand Stock ASTM D2419

		(Contd. of page
· Explosion limits:		
Lower:	0.9 Vol %	
Upper:	Not determined.	
· Vapor pressure at 20 °C (68 °F):	23 hPa (17.3 mm Hg)	
· Density at 20 °C (68 °F):	1.18203 g/cm³ (9.86404 lbs/gal)	
· Relative density	Not determined.	
· Vapor density	Not determined.	
· Evaporation rate	Not determined.	
· Solubility in / Miscibility with		
Water:	Fully miscible.	
· Partition coefficient (n-octanol/wate	e r): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	46.9 %	
Water:	39.6 %	
VOC content:	1.05 %	
	12.4 g/l / 0.10 lb/gl	
Solids content:	13.5 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.

100 mg/kg (ATE)

- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

LD50

- · Information on toxicological effects
- . Acute toxicity

Oral

· Acute toxi	· Acute toxicity:					
· LD/LC50	· LD/LC50 values that are relevant for classification:					
ATE (Acua	ATE (Acute Toxicity Estimate)					
Oral LD50 >5,346 mg/kg (rat) Dermal LD50 28,599 mg/kg						
Dermal	LD50	28,599 mg/kg				
Inhalative LC50/4 h 286 mg/l						
CAS: 50-0	CAS: 50-00-0 Formaldehyde					

(Contd. on page 7)

Printing date 01/05/2018 Reviewed on 01/05/2018

Trade name: Aggregates Sand Stock ASTM D2419

		(Contd. of page 6)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4 h	3 mg/l (ATE)

- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

1				
K				
· OSHA-Ca (Occupational Safety & Health Administration) CAS: 50-00-0 Formaldehyde				

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

US.

Printing date 01/05/2018 Reviewed on 01/05/2018

Trade name: Aggregates Sand Stock ASTM D2419

(Contd. of page 7)

UN-Number	
DOT, ADN, IMDG, IATA	Not regulated
UN proper shipping name DOT, ADN, IMDG, IATA	Not regulated
Transport hazard class(es)	
DOT, ADN, IMDG, IATA Class	Not regulated
Packing group DOT, IMDG, IATA	Not regulated
Environmental hazards:	
Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	r Not applicable.
UN "Model Regulation":	Not regulated

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section	355	(extremely	hazardous	substances):
Section	JJJ	(exil ellieiv	nuzuruvus	substances i.

CAS: 50-00-0 Formaldehyde

· Section 313 (Specific toxic chemical listings):

CAS: 50-00-0 Formaldehyde

· TSCA (Toxic Substances Control Act):

Glycerin (Glycerol)

Formaldehyde

Water

· TSCA new (21st Century Act) (Substances not listed)

CAS: 10035-04-8 Calcium Chloride Dihydrate

· Proposition 65

· Chemicals known to cause cancer:

CAS: 50-00-0 Formaldehyde

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)

Printing date 01/05/2018 Reviewed on 01/05/2018

Trade name: Aggregates Sand Stock ASTM D2419

(Contd. of page 8)

· Carcinogenic categories

· EPA (Environmental Protection Agency)	
CAS: 50-00-0 Formaldehyde	B1
· TLV (Threshold Limit Value established by ACGIH)	
CAS: 50-00-0 Formaldehyde	A2
· NIOSH-Ca (National Institute for Occupational Safety and Health)	
CAS: 50-00-0 Formaldehyde	

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS07 GHS08

- · Signal word Danger
- · Hazard-determining components of labeling:

Formaldehyde

· Hazard statements

Causes skin irritation.

Causes serious eve irritation.

May cause an allergic skin reaction.

Suspected of causing genetic defects.

May cause cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash thoroughly after handling.

Contaminated work clothing must not be allowed out of the workplace.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Specific treatment (see on this label).

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

(Contd. on page 10)

Printing date 01/05/2018 Reviewed on 01/05/2018

Trade name: Aggregates Sand Stock ASTM D2419

(Contd. of page 9)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

01-05-2018: review SDS for accuracy. STN Creation date for SDS 07-02-2015. STN 01/05/2018 / -

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1 Muta. 2: Germ cell mutagenicity – Category 2 Carc. 1A: Carcinogenicity – Category 1A

US