Printing date 05/11/2023 Reviewed on 05/11/2023

1 Identification

· Product identifier

· Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

· Article number: E2435

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Technical Coordinator

Sherman Nelson shermann@aquasolutions.org

Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



 $GHS02\ Flame$

Flammable Liquids 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B H340 May cause genetic defects.

Carcinogenicity 2 H351 Suspected of causing cancer.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

- · Signal word Danger
- · Hazard-determining components of labeling:

Gasoline, natural

· Hazard statements

Highly flammable liquid and vapor.

May cause genetic defects.

Suspected of causing cancer.

(Contd. on page 2)

Printing date 05/11/2023 Reviewed on 05/11/2023

Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

(Contd. of page 1)

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 0Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



*0 *Health* = *0

Fire = 3

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components	
------------------------	--

g	g		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	98.0%	
CAS: 8006-61-9	Gasoline, natural	2.0%	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Immediately rinse with water.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

Printing date 05/11/2023 Reviewed on 05/11/2023

Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

(Contd. of page 2)

- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot \textit{Indication of any immediate medical attention and special treatment needed}$

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
· PAC-2:	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	3300* ppm
· PAC-3:	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	15000* ppm

7 Handling and storage

- · Handling:
- · Precautions for safe handling Open and handle receptacle with care.
- · Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 4)

Printing date 05/11/2023 Reviewed on 05/11/2023

Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

(Contd. of page 3)

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see section 7.
- · Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

PEL Long-term value: 1900 mg/m³, 1000 ppm

REL Long-term value: 1900 mg/m³, 1000 ppm

TLV Short-term value: 1000 ppm

A3

CAS: 8006-61-9 Gasoline, natural

REL See Pocket Guide App. A

TLV Short-term value: 1480 mg/m³, 500 ppm Long-term value: 890 mg/m³, 300 ppm

bulk handling

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 05/11/2023 Reviewed on 05/11/2023

Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and cl	hemical properties
General Information	
Appearance:	77
Form: Color:	Liquid
Cotor: Odor:	Clear ethanol-gasoline odor
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	-114 °C (-173.2 °F)
Boiling point/Boiling range:	78 °C (172.4 °F)
Flash point:	13 °C (55.4 °F)
Flammability (solid, gaseous):	Highly flammable.
Auto igniting:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapmixtures are possible.
Explosion limits:	
Lower:	3.5 Vol %
Upper:	19 Vol %
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
Vapor pressure at 50° C (122° F):	280 hPa (210 mm Hg)
Density at 20 °C (68 °F):	0.78934 g/cm³ (6.58704 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 20 °C (68 °F):	1,000 g/l
Partition coefficient (n-octanol/water	r): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 6)

Printing date 05/11/2023 Reviewed on 05/11/2023

Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

	(Contd. of page 5
· Solvent content: Organic solvents: VOC content:	98.0 % 98.00 % 980.0 g/l / 8.18 lb/gal
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: The product can cause inheritable damage.

· Carcinogenic categories

	· Cartinogenic talegories		
	· IARC (Internatio	onal Agency for Research on Cancer)	
	CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1
	CAS: 8006-61-9	Gasoline, natural	2 <i>B</i>
	· NTP (National Toxicology Program)		
	None of the ingredients is listed.		
Ī	· OSHA-Ca (Occupational Safety & Health Administration)		
	None of the ingredients is listed.		
_			

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.

(Contd. on page 7)

Printing date 05/11/2023 Reviewed on 05/11/2023

Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

(Contd. of page 6)

- · Additional ecological information:
- · General notes:

Water hazard class 3 (Self-assessment): extremely hazardous for water

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

Danger to drinking water if even extremely small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1 / 7		C	, •
14 Trans	nort in	torma	สภาก
I I I I WILL	port in	JUITITUTE	TOIL

TIA	7 A	****	hor

· DOT, IMDG, IATA

UN1987

· UN proper shipping name

 $\cdot DOT$

Alcohols, n.o.s. (Ethanol)

· IMDG, IATA

ALCOHOLS, N.O.S. (Ethanol)

- · Transport hazard class(es)
- $\cdot DOT$



· Class

3 Flammable liquids

· Label

3

· IMDG, IATA



· Class

3 Flammable liquids

· Label

3

· Packing group

· DOT, IMDG, IATA

II

· Environmental hazards:

· Marine pollutant:

No

(Contd. on page 8)

Printing date 05/11/2023 Reviewed on 05/11/2023

Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

	(Contd. of page
· Special precautions for user	Warning: Flammable liquids
· Hazard identification number (Kemler code)	<i>: 33</i>
· EMS Number:	F- E , S - E
· Stowage Category	В
· Transport in bulk according to Annex II of	
MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
\cdot DOT	
· Quantity limitations	On passenger aircraft/rail: 5 L
-	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E2
• • • • •	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1987 ALCOHOLS, N.O.S. (ETHANOL), 3, II

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

Ethyl Alcohol, Absolute 200 Proof

Gasoline, natural

ACTIVE

ACTIVE

· Hazardous Air Pollutants

None of the ingredients is listed.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

- · Carcinogenic categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

(Contd. on page 9)

Printing date 05/11/2023 Reviewed on 05/11/2023

Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

(Contd. of page 8)

· TLV (Threshold Limit Value)

All components have the value A3.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 8006-61-9 Gasoline, natural

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





- · Signal word Danger
- · Hazard-determining components of labeling:

Gasoline, natural

· Hazard statements

Highly flammable liquid and vapor.

May cause genetic defects.

Suspected of causing cancer.

· Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Get medical advice/attention.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · National regulations:
- · Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 1.0 05/11/2023, reviewed SDS for accuracy. STN 05/11/2023

(Contd. on page 10)

Printing date 05/11/2023 Reviewed on 05/11/2023

Trade name: Ethanol Fuel Grade CDA 20-1 (200 Proof)

(Contd. of page 9)

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) PBT: Persistent, Bioaccumulative and Toxic

PB1: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health TLV: Threshold Limit Value

PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 2: Carcinogenicity – Category 2

* * Data compared to the previous version altered.

LIS