Printing date 01/08/2015

Reviewed on 01/08/2015

| Identification   |   |
|--|---|
|  |   |
| Product identifier   |   |
| Trade name: <u>Nitrogen Std 100 ug/ul</u><br>in Isooctane  |   |
| Article number: LY070  |   |
| Details of the supplier of the safety data sheet<br>Manufacturer/Supplier:<br>Aqua Solutions, Inc.<br>6913 Highway 225<br>DEER PARK, TX 77536  | AQUA<br>SOLUTIONS                       |
| USA  |   |
| 800-256-2586   |   |
| Information department:<br>Product safety department<br>Technical Coordinator<br>Sherman Nelson sherman@aquasolutions.org<br>Emergency telephone number:<br>Chemtrec: 800-424-9300<br>Canutec: 613-996-6666  |   |
| Hazard(s) identification   |   |
| GHS02 Flame  |   |
| <i>GHS02 Flame</i><br><i>Flam. Liq. 2 H225 Highly flammable liquid and vapor.</i><br><i>GHS08 Health hazard</i>  |   |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor.   |   |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor.   |   |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor.<br>GHS08 Health hazard<br>Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.  |   |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor.<br>GHS08 Health hazard<br>Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.<br>GHS07   |   |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor.<br>GHS08 Health hazard<br>Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.<br>GHS07<br>Skin Irrit. 2 H315 Causes skin irritation.   | to the Globally Harmonized System (GHS) |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor.   | to the Globally Harmonized System (GHS) |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor.   | to the Globally Harmonized System (GHS) |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor.   | to the Globally Harmonized System (GHS, |
| Flam. Liq. 2 H225 Highly flammable liquid and vapor.<br>GHS08 Health hazard<br>Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.<br>GHS07<br>Skin Irrit. 2 H315 Causes skin irritation.<br>STOT SE 3 H336 May cause drowsiness or dizziness.<br>Label elements<br>GHS label elements The product is classified and labeled according<br>Hazard pictograms<br>Markov Contents Con | to the Globally Harmonized System (GHS) |

*Printing date 01/08/2015* 

Reviewed on 01/08/2015

Trade name: Nitrogen Std 100 ug/ul in Isooctane

| (Contd. of page 1)   |
|--|
| · Hazard statements  |
| Highly flammable liquid and vapor.   |
| Causes skin irritation.  |
| May cause drowsiness or dizziness.   |
| May be fatal if swallowed and enters airways.  |
| · Precautionary statements   |
| If medical advice is needed, have product container or label at hand.                                      |
| Keep out of reach of children.   |
| Read label before use.   |
| Keep away from heat/sparks/open flames/hot surfaces No smoking.  |
| Use explosion-proof electrical/ventilating/lighting/equipment.   |
| Avoid breathing dust/fume/gas/mist/vapors/spray  |
| If swallowed: Immediately call a poison center/doctor.   |
| IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| Specific treatment (see on this label).  |
| Store locked up.   |
| Dispose of contents/container in accordance with local/regional/national/international regulations.        |
| Classification system:   |
| · NFPA ratings (scale 0 - 4)   |
| Health = 1   |
| $\frac{3}{Fire = 3}$   |
| $\frac{1}{10} Reactivity = 0$  |
|  |
| · HMIS-ratings (scale 0 - 4)   |
| HEALTH 2 Health = $2$  |
|  |
|  |
| <b>REACTIVITY</b> $0$ Reactivity = 0   |
| · Other hazards  |
| · Results of PBT and vPvB assessment   |
| · <b>PBT:</b> Not applicable.  |
| · <b>vPvB</b> : Not applicable.  |
| 11   |
|  |

# 3 Composition/information on ingredients

· Chemical characterization: Mixtures

- · Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

- Table of Nonhazardous Ingredients
- CAS: 110-86-1 Pyridine

# 4 First-aid measures

- · Description of first aid measures
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

(Contd. on page 3)

99.918%

0.082%

USA

Printing date 01/08/2015

## Reviewed on 01/08/2015

Trade name: Nitrogen Std 100 ug/ul in Isooctane

#### (Contd. of page 2)

Most important symptoms and effects, both acute and delayed No further relevant information available.
 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

## **6** Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions:
   Do not allow product to reach sewage system or any water course.
   Inform respective authorities in case of seepage into water course or sewage system.
   Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
   Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## 7 Handling and storage

## · Precautions for safe handling

- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- *Specific end use(s) No further relevant information available.*

(Contd. on page 4)

Printing date 01/08/2015

Reviewed on 01/08/2015

Trade name: Nitrogen Std 100 ug/ul in Isooctane

(Contd. of page 3)

## 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

## · Control parameters

· Components with limit values that require monitoring at the workplace:

## 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

PEL Long-term value: 2350 mg/m<sup>3</sup>, 500 ppm n-Octane only

TLV Long-term value: 1401 mg/m<sup>3</sup>, 300 ppm

• Additional information: The lists that were valid during the creation were used as basis.

## · Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the skin.

Avoid contact with the eyes and skin.

## • Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  **Material of gloves** 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

(Contd. on page 5)

Printing date 01/08/2015

Reviewed on 01/08/2015

Trade name: Nitrogen Std 100 ug/ul in Isooctane

(Contd. of page 4)

| <b>T</b> ( ) <b>1</b> · 1 · 1 · 1 · 1  | 1 • 1 /•   |
|--|--|
| <ul> <li>Information on basic physical and c</li> <li>General Information</li> </ul> | hemical properties   |
| · General Information<br>· Appearance:   |  |
| Form:  | Liquid   |
| Color:   | Clear  |
| · Odor:  | Pyridine   |
| · Odour threshold:   | Not determined.  |
| · pH-value:  | Not determined.  |
| · Change in condition  |  |
| Melting point/Melting range:   | -107 °C (-161 °F)  |
| <b>Boiling point/Boiling range:</b>  | 98 °C (208 °F)   |
| · Flash point:   | -12 °C (10 °F)   |
| · Flammability (solid, gaseous):   | Not applicable.  |
| · Ignition temperature:  | 410 °C (770 °F)  |
| • Decomposition temperature:   | Not determined.  |
| • Auto igniting:   | Product is not selfigniting.   |
| · Danger of explosion:   | Product is not explosive. However, formation of explosive air/vapo<br>mixtures are possible. |
| · Explosion limits:  |  |
| Lower:   | 1.1 Vol %  |
| Upper:   | 6 Vol %  |
| · Vapor pressure at 20 °C (68 °F):   | 15 hPa (11 mm Hg)  |
| · Density at 20 °C (68 °F):  | 0.69017 g/cm³ (5.759 lbs/gal)  |
| · Relative density   | Not determined.  |
| · Vapour density   | Not determined.  |
| · Evaporation rate   | Not determined.  |
| $\cdot$ Solubility in / Miscibility with   |  |
| Water:   | Not miscible or difficult to mix.  |
| · Partition coefficient (n-octanol/wate  | <b>r</b> ): Not determined.  |
| · Viscosity:   |  |
| Dynamic:   | Not determined.  |
| Kinematic:   | Not determined.  |
| · Solvent content:   |  |
| Organic solvents:  | 99.9 %   |
| VOC content:   | 99.9 %   |
|  | 689.6 g/l / 5.76 lb/gl   |
| • Other information  | No further relevant information available.   |

(Contd. on page 6)

Printing date 01/08/2015

Reviewed on 01/08/2015

Trade name: Nitrogen Std 100 ug/ul in Isooctane

(Contd. of page 5)

## **10 Stability and reactivity**

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

## **11 Toxicological information**

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:

540-84-1 2,2,4-Trimethylpentane (Iso-Octane)

LD50 ->2000 mg/kg (rat) Dermal

Inhalative LC50/4 h -4h->33.52 mg/l (rat)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

## · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

110-86-1 Pyridine

## · NTP (National Toxicology Program)

None of the ingredients is listed.

## · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- · Ecotoxical effects:
- · Remark: Very toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

> (Contd. on page 7) USA

3

Printing date 01/08/2015

Reviewed on 01/08/2015

Trade name: Nitrogen Std 100 ug/ul in Isooctane

(Contd. of page 6)

Also poisonous for fish and plankton in water bodies. Very toxic for aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# **13 Disposal considerations**

· Waste treatment methods

- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

| UN-Number                  |   |
|----------------------------|---|
| DOT, IMDG, IATA            | UN1993                                    |
| UN proper shipping name    |   |
| DOT                        | Flammable liquids, n.o.s. (Octanes)       |
| IMDG                       | FLAMMABLE LIQUID, N.O.S. (OCTANES), MARIN |
| 14774                      | POLLUTANT                                 |
| IATA                       | FLAMMABLE LIQUID, N.O.S. (OCTANES)        |
| Transport hazard class(es) |   |
| DOT                        |   |
|                            |   |
|                            |   |
|                            |   |
| •                          |   |
| Class                      | 3 Flammable liquids                       |
| Label                      | 3   |
| IMDG                       |   |
|                            |   |
|                            |   |
| 3                          |   |
|                            |   |
| Class<br>Label             | 3 Flammable liquids                       |
|                            | ,   |
| IATA                       |   |
|                            |   |
|                            |   |
| 3                          |   |
| Class                      | 3 Flammable liquids                       |
| Cuass                      |   |

*Printing date 01/08/2015* 

Reviewed on 01/08/2015

Trade name: Nitrogen Std 100 ug/ul in Isooctane

|  | (Contd. of page  |
|--|--|
| Label                                  | 3  |
| Packing group                          |  |
| DOT, IMDG, IATA                        | II   |
| Environmental hazards:                 | Product contains environmentally hazardous substances: 2,2,4 |
|  | Trimethylpentane (Iso-Octane)                                |
| Marine pollutant:                      | Yes  |
|  | Symbol (fish and tree)                                       |
| Special precautions for user           | Warning: Flammable liquids                                   |
| Danger code (Kemler):                  | 33   |
| EMS Number:                            | <i>F-E,<u>S-E</u></i>  |
| Transport in bulk according to Annex   | II of  |
| MARPOL73/78 and the IBC Code           | Not applicable.  |
| Transport/Additional information:      |  |
| DOT                                    |  |
| Quantity limitations                   | On passenger aircraft/rail: 5 L                              |
|  | On cargo aircraft only: 60 L                                 |
| IMDG                                   |  |
| Limited quantities (LQ)                | 1L   |
| Excepted quantities $(\widetilde{EQ})$ | Code: E2   |
|  | Maximum net quantity per inner packaging: 30 ml              |
|  | Maximum net quantity per outer packaging: 500 ml             |
| UN ''Model Regulation'':               | UN1993, Flammable liquids, n.o.s. (Octanes), 3, II           |

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

 $\cdot$  Section 355 (extremely hazardous substances):

None of the ingredients is listed.

 $\cdot$  Section 313 (Specific toxic chemical listings):

110-86-1 Pyridine

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

## · Proposition 65

· Chemicals known to cause cancer:

110-86-1 Pyridine

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

 $\cdot$  Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

(Contd. on page 9)

USA

Printing date 01/08/2015

Reviewed on 01/08/2015

Trade name: Nitrogen Std 100 ug/ul in Isooctane

| Carcinogenic categories<br>EPA (Environmental Protection Agency)   |   |
|--|---|
| 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)   |   |
|  |   |
| TLV (Threshold Limit Value established by ACGIH)   |   |
| 110-86-1 Pyridine  | A   |
| NIOSH-Ca (National Institute for Occupational Safety and Health)   |   |
| None of the ingredients is listed.   |   |
| <b>GHS label elements</b> The product is classified and labeled according a<br><b>Hazard pictograms</b>  | to the Globally Harmonized System (GHS)   |
| GHS02 GHS07 GHS08  |   |
| Signal word Danger   |   |
| Hazard-determining components of labeling:   |   |
| 2,2,4-Trimethylpentane (Iso-Octane)  |   |
| Hazard statements  |   |
| Highly flammable liquid and vapor.   |   |
| Causes skin irritation.  |   |
| May cause drowsiness or dizziness.   |   |
| May be fatal if swallowed and enters airways.  |   |
| Precautionary statements   |   |
| If medical advice is needed, have product container or label at hand.  |   |
| Keep out of reach of children.   |   |
| Read label before use.   |   |
| Keep away from heat/sparks/open flames/hot surfaces No smoking.  |   |
| Use explosion-proof electrical/ventilating/lighting/equipment.   |   |
| Avoid breathing dust/fume/gas/mist/vapors/spray  |   |
| If swallowed: Immediately call a poison center/doctor.   |   |
| IF ON SKIN (or hair): Remove/Take off immediately all contaminated   | d clothing. Rinse skin with water/shower. |
| Specific treatment (see on this label).  |   |
| Store locked up.   |   |
| Dispose of contents/container in accordance with local/regional/nation<br><b>Chemical safety assessment:</b> A Chemical Safety Assessment has not be |   |
|  |   |
| Other information  |   |
| This information is based on our present knowledge. However, the specific product features and shall not establish a legally valid contra            |   |

- · Contact: Mr. Nelson
- $\cdot$  Date of preparation / last revision
- Creation date for SDS 01-08-2015. STN 01/08/2015 / -
- $\cdot$  Abbreviations and acronyms:
- ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 10)

USA

Printing date 01/08/2015

Reviewed on 01/08/2015

Trade name: Nitrogen Std 100 ug/ul in Isooctane

(Contd. of page 9)

USA

DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent Flam. Liq. 2: Flammable liquids, Hazard Category 2 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2 STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3 Asp. Tox. 1: Aspiration hazard, Hazard Category 1