

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

## 1 Identification

- **Product identifier**
- **Trade name:** Demulsifier, Petrolite DMO46X
- **Article number:** D2185
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Aqua Solutions, Inc.  
6913 Highway 225  
DEER PARK, TX 77536  
USA  
800-256-2586
- **Information department:**  
Technical Coordinator  
Sherman Nelson shermann@aquasolutions.org  
Technical Coordinator  
Sherman Nelson shermann@aquasolutions.org
- **Emergency telephone number:**  
Chemtrec: 800-424-9300  
Canutec: 613-996-6666



## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Germ Cell Mutagenicity 1B

H340 May cause genetic defects.

Carcinogenicity 1A

H350 May cause cancer.

Specific Target Organ Toxicity - Repeated Exposure 2 H373 May cause damage to the hearing organs through prolonged or repeated exposure.

Aspiration Hazard 1

H304 May be fatal if swallowed and enters airways.



GHS07

Acute Toxicity - Dermal 4

H312 Harmful in contact with skin.

Acute Toxicity - Inhalation 4

H332 Harmful if inhaled.

Skin Irritation 2

H315 Causes skin irritation.

Eye Irritation 2A

H319 Causes serious eye irritation.

Specific Target Organ Toxicity - Single Exposure 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 1)

· **Hazard pictograms**· **Signal word** *Danger*· **Hazard-determining components of labeling:**

1,2,4-Trimethylbenzene  
 Solvent naphtha (petroleum), light arom.  
 2-Ethyl-1-hexanol  
 Ethylbenzene, Anhydrous, 99.8%  
 Xylene (Xylol)  
 mesitylene  
 Cumene  
 1,2,3-Trimethylbenzene

· **Hazard statements**

Highly flammable liquid and vapor.  
 Harmful in contact with skin or if inhaled.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause genetic defects.  
 May cause cancer.  
 May cause respiratory irritation.  
 May cause damage to the hearing organs through prolonged or repeated exposure.  
 May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If swallowed: Immediately call a poison center/doctor.  
 Specific treatment (see on this label).  
 Do NOT induce vomiting.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Get medical advice/attention if you feel unwell.  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 2)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 2

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = 2

Fire = 2

Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 95-63-6	1,2,4-Trimethylbenzene	30.0%
CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	30.0%
CAS: 104-76-7	2-Ethyl-1-hexanol	10.0%
CAS: 108-67-8	mesitylene	10.0%
CAS: 526-73-8	1,2,3-Trimethylbenzene	5.0%
CAS: 1330-20-7	Xylene (Xylol)	5.0%
CAS: 98-82-8	Cumene	1.0%
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	1.0%

## 4 First-aid measures

· **Description of first aid measures**· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

#### · PAC-1:

CAS: 95-63-6	1,2,4-Trimethylbenzene	140 ppm
CAS: 104-76-7	2-Ethyl-1-hexanol	0.1 ppm
CAS: 108-67-8	mesitylene	140 ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	140 ppm
CAS: 1330-20-7	Xylene (Xylol)	130 ppm
CAS: 98-82-8	Cumene	50 ppm
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	33 ppm

#### · PAC-2:

CAS: 95-63-6	1,2,4-Trimethylbenzene	360 ppm
CAS: 104-76-7	2-Ethyl-1-hexanol	100 ppm
CAS: 108-67-8	mesitylene	360 ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	360 ppm
CAS: 1330-20-7	Xylene (Xylol)	920* ppm
CAS: 98-82-8	Cumene	300 ppm
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	1100* ppm

(Contd. on page 5)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 4)

· **PAC-3:**

CAS: 95-63-6	1,2,4-Trimethylbenzene	480 ppm
CAS: 104-76-7	2-Ethyl-1-hexanol	200 ppm
CAS: 108-67-8	mesitylene	480 ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	480 ppm
CAS: 1330-20-7	Xylene (Xylol)	2500* ppm
CAS: 98-82-8	Cumene	730 ppm
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	1800* ppm

## 7 Handling and storage

· **Handling:**· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**· **Storage:**· **Requirements to be met by storerooms and receptacles:** Store in a cool location.· **Information about storage in one common storage facility:** Not required.· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see section 7.· **Control parameters**· **Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

**CAS: 95-63-6 1,2,4-Trimethylbenzene**REL Long-term value: 125 mg/m<sup>3</sup>, 25 ppm

TLV Long-term value: 10 ppm

A4

**CAS: 104-76-7 2-Ethyl-1-hexanol**

TLV Long-term value: 5 ppm

A3

**CAS: 108-67-8 mesitylene**REL Long-term value: 125 mg/m<sup>3</sup>, 25 ppm

TLV Long-term value: 10 ppm

(Contd. on page 6)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

**Trade name: Demulsifier, Petrolite DMO46X**

(Contd. of page 5)

**CAS: 526-73-8 1,2,3-Trimethylbenzene**
REL Long-term value: 125 mg/m<sup>3</sup>, 25 ppm

TLV Long-term value: 10 ppm

**CAS: 1330-20-7 Xylene (Xylol)**
PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL Short-term value: 655 mg/m<sup>3</sup>, 150 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 20 ppm

BEI, A4

**CAS: 98-82-8 Cumene**
PEL Long-term value: 245 mg/m<sup>3</sup>, 50 ppm

Skin

REL Long-term value: 245 mg/m<sup>3</sup>, 50 ppm

Skin

TLV Long-term value: 5 ppm

A3

**CAS: 100-41-4 Ethylbenzene, Anhydrous, 99.8%**
PEL Long-term value: 435 mg/m<sup>3</sup>, 100 ppmREL Short-term value: 545 mg/m<sup>3</sup>, 125 ppmLong-term value: 435 mg/m<sup>3</sup>, 100 ppm

TLV Long-term value: 20 ppm

OTO, BEI, A3

**· Ingredients with biological limit values:**
**CAS: 1330-20-7 Xylene (Xylol)**

BEI 1.5 g/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift

LD50: Methylhippuric acids

**CAS: 100-41-4 Ethylbenzene, Anhydrous, 99.8%**

BEI 0.15 g/g creatinine

LD50 Intraperitoneal: urine

Time: end of shift at end of workweek

LD50: Sum of mandelic acid and phenylglyoxylic acid (nonspecific)

**· Additional information:** The lists that were valid during the creation were used as basis.

**· Exposure controls**
**· Personal protective equipment:**
**· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

**· Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

(Contd. on page 7)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 6)

## · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

## · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

## · Eye protection:



Tightly sealed goggles

## · Body protection: Protective work clothing

## 9 Physical and chemical properties

### · Information on basic physical and chemical properties

#### · General Information

#### · Appearance:

Form:	Liquid
Color:	Dark brown
Odor:	Aromatic
Odor threshold:	Not determined.

· pH-value: Not determined.

#### · Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.

· Flash point: 116 °C (240.8 °F)

· Flammability (solid, gaseous): Highly flammable.

· Decomposition temperature: Not determined.

· Ignition temperature: Product is not selfigniting.

· Danger of explosion: Not determined.

#### · Explosion limits:

Lower:	Not determined.
Upper:	Not determined.

· Vapor pressure: Not determined.

· Density at 20 °C (68 °F): 1 g/cm<sup>3</sup> (8.345 lbs/gal)

(Contd. on page 8)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 7)

- |   |  |
|---|--|
| · <b>Relative density</b>                         | Not determined.                            |
| · <b>Vapor density</b>                            | Not determined.                            |
| · <b>Evaporation rate</b>                         | Not determined.                            |
| · <b>Solubility in / Miscibility with Water:</b>  | Not miscible or difficult to mix.          |
| · <b>Partition coefficient (n-octanol/water):</b> | Not determined.                            |
| · <b>Viscosity:</b>                               |  |
| <b>Dynamic:</b>                                   | Not determined.                            |
| <b>Kinematic:</b>                                 | Not determined.                            |
| · <b>Solvent content:</b>                         |  |
| <b>Organic solvents:</b>                          | 92.0 %                                     |
| <b>VOC content:</b>                               | 92.00 %                                    |
|   | 920.0 g/l / 7.68 lb/gal                    |
| <b>Solids content:</b>                            | 0.0 %                                      |
| · <b>Other information</b>                        | No further relevant information available. |

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

**ATE (Acute Toxicity Estimate)**

Dermal	LD50	10,393 mg/kg
Inhalative	LC50/4h	>16.1 mg/l

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful  
Irritant  
The product can cause inheritable damage.
- **Carcinogenic categories**

· **IARC (International Agency for Research on Cancer)**

CAS: 1330-20-7 Xylene (Xylol)

3

(Contd. on page 9)



# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 8)

CAS: 98-82-8	Cumene	2B
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	2B
· <b>NTP (National Toxicology Program)</b>		
CAS: 98-82-8	Cumene	R
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>		
None of the ingredients is listed.		

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 3 (Self-assessment): extremely hazardous for water  
Do not allow product to reach ground water, water course or sewage system, even in small quantities.  
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

· <b>UN-Number</b>	UN3082
· <b>DOT, IMDG, IATA</b>	
· <b>UN proper shipping name</b>	Environmentally hazardous substance, liquid, n.o.s. (1,2,4-Trimethylbenzene, mesitylene)
· <b>DOT</b>	
· <b>IMDG</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2,4-Trimethylbenzene, mesitylene, 2-Ethyl-1-hexanol, Cumene), MARINE POLLUTANT
· <b>IATA</b>	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2,4-Trimethylbenzene, mesitylene)

(Contd. on page 10)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024


Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 9)

· Transport hazard class(es)

· DOT, IMDG, IATA



· Class

9 Miscellaneous dangerous substances and articles

· Label

9

· Packing group

· DOT, IMDG, IATA

III

· Environmental hazards:

Product contains environmentally hazardous substances: 1,2,4-Trimethylbenzene

· Marine pollutant:

No

Yes (DOT)

Symbol (fish and tree)

· Special marking (IATA):

Symbol (fish and tree)

· Special precautions for user

Warning: Miscellaneous dangerous substances and articles

· Hazard identification number (Kemler code):

90

· EMS Number:

F-A,S-F

· Stowage Category

A

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations

On passenger aircraft/rail: 450 L

On cargo aircraft only: 450 L

· Remarks:

Special marking with the symbol (fish and tree).

· IMDG

· Limited quantities (LQ)

5L

· Excepted quantities (EQ)

Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation":

UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2,4-TRIMETHYLBENZENE, MESITYLENE), 9, III

## 15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 95-63-6

1,2,4-Trimethylbenzene

CAS: 1330-20-7

Xylene (Xylol)

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 10)

CAS: 98-82-8	Cumene	
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	
· <b>TSCA (Toxic Substances Control Act):</b>		
1,2,4-Trimethylbenzene		ACTIVE
Solvent naphtha (petroleum), light arom.		ACTIVE
2-Ethyl-1-hexanol		ACTIVE
mesitylene		ACTIVE
1,2,3-Trimethylbenzene		ACTIVE
Xylene (Xylol)		ACTIVE
Cumene		ACTIVE
Ethylbenzene, Anhydrous, 99.8%		ACTIVE
· <b>Hazardous Air Pollutants</b>		
CAS: 1330-20-7	Xylene (Xylol)	
CAS: 98-82-8	Cumene	
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	
· <b>Proposition 65</b>		
· <b>Chemicals known to cause cancer:</b>		
CAS: 98-82-8	Cumene	
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	
· <b>Chemicals known to cause reproductive toxicity for females:</b>		
None of the ingredients is listed.		
· <b>Chemicals known to cause reproductive toxicity for males:</b>		
None of the ingredients is listed.		
· <b>Chemicals known to cause developmental toxicity:</b>		
None of the ingredients is listed.		
· <b>Carcinogenic categories</b>		
· <b>EPA (Environmental Protection Agency)</b>		
CAS: 95-63-6	1,2,4-Trimethylbenzene	II
CAS: 108-67-8	mesitylene	II
CAS: 526-73-8	1,2,3-Trimethylbenzene	II
CAS: 1330-20-7	Xylene (Xylol)	I
CAS: 98-82-8	Cumene	D, CBD
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	D
· <b>TLV (Threshold Limit Value)</b>		
CAS: 1330-20-7	Xylene (Xylol)	A4
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	A3
· <b>NIOSH-Ca (National Institute for Occupational Safety and Health)</b>		
None of the ingredients is listed.		
· <b>GHS label elements</b> The product is classified and labeled according to the Globally Harmonized System (GHS).		

(Contd. on page 12)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Demulsifier, Petrolite DMO46X

(Contd. of page 11)

· **Hazard pictograms**· **Signal word** *Danger*· **Hazard-determining components of labeling:**

1,2,4-Trimethylbenzene  
 Solvent naphtha (petroleum), light arom.  
 2-Ethyl-1-hexanol  
 Ethylbenzene, Anhydrous, 99.8%  
 Xylene (Xylol)  
 mesitylene  
 Cumene  
 1,2,3-Trimethylbenzene

· **Hazard statements**

Highly flammable liquid and vapor.  
 Harmful in contact with skin or if inhaled.  
 Causes skin irritation.  
 Causes serious eye irritation.  
 May cause genetic defects.  
 May cause cancer.  
 May cause respiratory irritation.  
 May cause damage to the hearing organs through prolonged or repeated exposure.  
 May be fatal if swallowed and enters airways.

· **Precautionary statements**

Obtain special instructions before use.  
 Do not handle until all safety precautions have been read and understood.  
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
 Ground/bond container and receiving equipment.  
 Use explosion-proof electrical/ventilating/lighting/equipment.  
 Use only non-sparking tools.  
 Take precautionary measures against static discharge.  
 Do not breathe dust/fume/gas/mist/vapors/spray.  
 Wash thoroughly after handling.  
 Use only outdoors or in a well-ventilated area.  
 Wear protective gloves/protective clothing/eye protection/face protection.  
 If swallowed: Immediately call a poison center/doctor.  
 Specific treatment (see on this label).  
 Do NOT induce vomiting.  
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 IF exposed or concerned: Get medical advice/attention.  
 Call a poison center/doctor if you feel unwell.  
 Get medical advice/attention if you feel unwell.  
 Take off contaminated clothing and wash it before reuse.  
 If skin irritation occurs: Get medical advice/attention.  
 If eye irritation persists: Get medical advice/attention.  
 In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.  
 Store in a well-ventilated place. Keep container tightly closed.

(Contd. on page 13)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

**Trade name: Demulsifier, Petrolite DMO46X**

(Contd. of page 12)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.

Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:**

Date of Preparation / Last Revision:

· **Date of preparation / last revision**

Revision 1.2, 06/04/2024: Reviewed SDS for accuracy. MH/STN  
06/04/2024

· **Abbreviations and acronyms:**

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flammable Liquids 2: Flammable liquids – Category 2

Acute Toxicity - Dermal 4: Acute toxicity – Category 4

Skin Irritation 2: Skin corrosion/irritation – Category 2

Eye Irritation 2A: Serious eye damage/eye irritation – Category 2A

Germ Cell Mutagenicity 1B: Germ cell mutagenicity – Category 1B

Carcinogenicity 1A: Carcinogenicity – Category 1A

Specific Target Organ Toxicity - Single Exposure 3: Specific target organ toxicity (single exposure) – Category 3

Specific Target Organ Toxicity - Repeated Exposure 2: Specific target organ toxicity (repeated exposure) – Category 2

Aspiration Hazard 1: Aspiration hazard – Category 1

· **\* Data compared to the previous version altered.**