

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

1 Identification

- **Product identifier**
- **Trade name:** Demulsifier, Petrolite DMO46
- **Article number:** D2185
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Aqua Solutions, Inc.
6913 Highway 225
DEER PARK, TX 77536
USA
800-256-2586
- **Information department:**
Technical Coordinator
Sherman Nelson sherman@aquasolutions.org
- **Emergency telephone number:**
Chemtrec: 800-424-9300
Canutec: 613-996-6666



2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H335 May cause respiratory irritation.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 1)

· **Hazard pictograms**· **Signal word** *Danger*· **Hazard-determining components of labeling:***Solvent naphtha (petroleum), light arom.**Isooctanol**1,2,4-Trimethylbenzene**Xylene (Xylol)**mesitylene**cumene**1,2,3-Trimethylbenzene**Ethylbenzene, Anhydrous, 99.8%*· **Hazard statements***Highly flammable liquid and vapor.**Harmful in contact with skin or if inhaled.**Causes skin irritation.**Causes serious eye irritation.**May cause genetic defects.**May cause cancer.**May cause respiratory irritation.**May cause damage to organs through prolonged or repeated exposure.**May be fatal if swallowed and enters airways.*· **Precautionary statements***Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**Keep away from heat/sparks/open flames/hot surfaces. - No smoking.**Ground/bond container and receiving equipment.**Use explosion-proof electrical/ventilating/lighting/equipment.**Use only non-sparking tools.**Take precautionary measures against static discharge.**Do not breathe dust/fume/gas/mist/vapors/spray.**Wash thoroughly after handling.**Use only outdoors or in a well-ventilated area.**Wear protective gloves/protective clothing/eye protection/face protection.**If swallowed: Immediately call a poison center/doctor.**Specific treatment (see on this label).**Do NOT induce vomiting.**If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**IF INHALED: Remove person to fresh air and keep comfortable for breathing.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**IF exposed or concerned: Get medical advice/attention.**Call a poison center/doctor if you feel unwell.**Get medical advice/attention if you feel unwell.**Take off contaminated clothing and wash it before reuse.**If skin irritation occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**In case of fire: Use for extinction: CO2, powder or water spray.**Store in a well-ventilated place. Keep container tightly closed.*

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 2)

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 2

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = 2

Fire = 2

Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	30.0%
CAS: 95-63-6	1,2,4-Trimethylbenzene	30.0%
CAS: 108-67-8	mesitylene	10.0%
CAS: 104-76-7	Isooctanol	10.0%
CAS: 1330-20-7	Xylene (Xylol)	5.0%
CAS: 526-73-8	1,2,3-Trimethylbenzene	5.0%
CAS: 98-82-8	cumene	1.0%
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	1.0%

4 First-aid measures

· **Description of first aid measures**· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 3)

- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Prevent seepage into sewage system, workpits and cellars.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

· PAC-1:

CAS: 95-63-6	1,2,4-Trimethylbenzene	140 ppm
CAS: 108-67-8	mesitylene	140 ppm
CAS: 104-76-7	Isooctanol	0.1 ppm
CAS: 1330-20-7	Xylene (Xylol)	130 ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	140 ppm
CAS: 98-82-8	cumene	50 ppm
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	33 ppm

· PAC-2:

CAS: 95-63-6	1,2,4-Trimethylbenzene	360 ppm
CAS: 108-67-8	mesitylene	360 ppm
CAS: 104-76-7	Isooctanol	100 ppm
CAS: 1330-20-7	Xylene (Xylol)	920* ppm
CAS: 526-73-8	1,2,3-Trimethylbenzene	360 ppm
CAS: 98-82-8	cumene	300 ppm
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	1100* ppm

· PAC-3:

CAS: 95-63-6	1,2,4-Trimethylbenzene	480 ppm
CAS: 108-67-8	mesitylene	480 ppm
CAS: 104-76-7	Isooctanol	200 ppm
CAS: 1330-20-7	Xylene (Xylol)	2500* ppm

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 4)

CAS: 526-73-8	1,2,3-Trimethylbenzene	480 ppm
CAS: 98-82-8	cumene	730 ppm
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	1800* ppm

7 Handling and storage

- **Handling:**
- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

CAS: 95-63-6 1,2,4-Trimethylbenzene	
REL	Long-term value: 125 mg/m ³ , 25 ppm
TLV	Long-term value: 123 mg/m ³ , 25 ppm
CAS: 108-67-8 mesitylene	
REL	Long-term value: 125 mg/m ³ , 25 ppm
TLV	Long-term value: 123 mg/m ³ , 25 ppm
CAS: 1330-20-7 Xylene (Xylol)	
PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 655 mg/m ³ , 150 ppm
	Long-term value: 435 mg/m ³ , 100 ppm
TLV	Short-term value: 651 mg/m ³ , 150 ppm
	Long-term value: 434 mg/m ³ , 100 ppm
	BEI
CAS: 526-73-8 1,2,3-Trimethylbenzene	
REL	Long-term value: 125 mg/m ³ , 25 ppm
TLV	Long-term value: 123 mg/m ³ , 25 ppm

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: **Demulsifier, Petrolite DMO46**

(Contd. of page 5)

CAS: 98-82-8 cumene

PEL	Long-term value: 245 mg/m ³ , 50 ppm Skin
REL	Long-term value: 245 mg/m ³ , 50 ppm Skin
TLV	Long-term value: (246) NIC-0.5 mg/m ³ , (50) NIC-0.1 ppm NIC-A2

CAS: 100-41-4 Ethylbenzene, Anhydrous, 99.8%

PEL	Long-term value: 435 mg/m ³ , 100 ppm
REL	Short-term value: 545 mg/m ³ , 125 ppm Long-term value: 435 mg/m ³ , 100 ppm
TLV	Long-term value: 87 mg/m ³ , 20 ppm BEI

· Ingredients with biological limit values:**CAS: 1330-20-7 Xylene (Xylol)**

BEI	1.5 g/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: Methylhippuric acids
-----	---

CAS: 100-41-4 Ethylbenzene, Anhydrous, 99.8%

BEI	0.7 g/g creatinine LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Sum of mandelic acid and phenylglyoxylic acid (nonspecific, semi-quantitative)
-	LD50 Intraperitoneal: end-exhaled air Time: not critical LD50: Ethyl benzene (semi-quantitative)

· Additional information: The lists that were valid during the creation were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 6)

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid

Color: Dark brown

- **Odor:** Aromatic

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: Undetermined.

- **Flash point:** 116 °C (240.8 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Not determined.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapor pressure:** Not determined.

- **Density at 20 °C (68 °F):** 1 g/cm³ (8.345 lbs/gal)

- **Relative density** Not determined.

- **Vapor density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic: Not determined.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 7)

Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	92.0 %
VOC content:	92.00 %
	920.0 g/l / 7.68 lb/gl
Solids content:	0.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	14,798 mg/kg (rat)
Dermal	LD50	>6,098 mg/kg
Inhalative	LC50/4h	>16 mg/l

CAS: 64742-95-6 Solvent naphtha (petroleum), light arom.

Inhalative	LC50/4h	11 mg/l (ATE)
------------	---------	---------------

CAS: 95-63-6 1,2,4-Trimethylbenzene

Inhalative	LC50/4h	11 mg/l (ATE)
------------	---------	---------------

· Primary irritant effect:

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful

Irritant

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

CAS: 1330-20-7	Xylene (Xylol)	3
CAS: 98-82-8	cumene	2B
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%	2B

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 8)

· **NTP (National Toxicology Program)**

CAS: 98-82-8 | cumene

R

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Not known to be hazardous to water.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **UN-Number**· **DOT, IMDG, IATA**

UN3082

· **UN proper shipping name**· **DOT**

Environmentally hazardous substances, liquid, n.o.s. (1,2,4-Trimethylbenzene, 1,3,5-Trimethylbenzene)

· **IMDG**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2,4-Trimethylbenzene, 1,3,5-TRIMETHYLBENZENE, Isooctanol, ISOPROPYLBENZENE), MARINE POLLUTANT

· **IATA**

ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (1,2,4-Trimethylbenzene, 1,3,5-TRIMETHYLBENZENE)

· **Transport hazard class(es)**· **DOT, IMDG, IATA**· **Class**

9 Miscellaneous dangerous substances and articles

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 9)

· Label	9
· Packing group · DOT, IMDG, IATA	III
· Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: 1,2,4-Trimethylbenzene No Yes (DOT) Symbol (fish and tree)
· Special marking (IATA):	Symbol (fish and tree)
· Special precautions for user · Danger code (Kemler): · EMS Number: · Stowage Category	Warning: Miscellaneous dangerous substances and articles 90 F-A,S-F A
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information: · DOT · Quantity limitations · Remarks:	On passenger aircraft/rail: No limit On cargo aircraft only: No limit Special marking with the symbol (fish and tree).
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (1,2,4-TRIMETHYLBENZENE, 1,3,5-TRIMETHYLBENZENE), 9, III

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 95-63-6	1,2,4-Trimethylbenzene
CAS: 1330-20-7	Xylene (Xylol)
CAS: 98-82-8	cumene
CAS: 100-41-4	Ethylbenzene, Anhydrous, 99.8%

· TSCA (Toxic Substances Control Act):

Solvent naphtha (petroleum), light arom.
1,2,4-Trimethylbenzene
mesitylene
Isooctanol

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 10)

Xylene (Xylol)

1,2,3-Trimethylbenzene

cumene

Ethylbenzene, Anhydrous, 99.8%

· **Proposition 65**· **Chemicals known to cause cancer:**

CAS: 98-82-8 cumene

CAS: 100-41-4 Ethylbenzene, Anhydrous, 99.8%

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**· **EPA (Environmental Protection Agency)**

CAS: 95-63-6 1,2,4-Trimethylbenzene

II

CAS: 108-67-8 mesitylene

II

CAS: 1330-20-7 Xylene (Xylol)

I

CAS: 526-73-8 1,2,3-Trimethylbenzene

II

CAS: 98-82-8 cumene

D, CBD

CAS: 100-41-4 Ethylbenzene, Anhydrous, 99.8%

D

· **TLV (Threshold Limit Value established by ACGIH)**

CAS: 1330-20-7 Xylene (Xylol)

A4

CAS: 100-41-4 Ethylbenzene, Anhydrous, 99.8%

A3

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**

GHS02



GHS07



GHS08

· **Signal word** Danger· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

Isooctanol

1,2,4-Trimethylbenzene

Xylene (Xylol)

mesitylene

cumene

1,2,3-Trimethylbenzene

Ethylbenzene, Anhydrous, 99.8%

(Contd. on page 12)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 11)

· Hazard statements

Highly flammable liquid and vapor.
 Harmful in contact with skin or if inhaled.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause genetic defects.
 May cause cancer.
 May cause respiratory irritation.
 May cause damage to organs through prolonged or repeated exposure.
 May be fatal if swallowed and enters airways.

· Precautionary statements

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Ground/bond container and receiving equipment.
 Use explosion-proof electrical/ventilating/lighting/equipment.
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 Wash thoroughly after handling.
 Use only outdoors or in a well-ventilated area.
 Wear protective gloves/protective clothing/eye protection/face protection.
 If swallowed: Immediately call a poison center/doctor.
 Specific treatment (see on this label).
 Do NOT induce vomiting.
 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 IF exposed or concerned: Get medical advice/attention.
 Call a poison center/doctor if you feel unwell.
 Get medical advice/attention if you feel unwell.
 Take off contaminated clothing and wash it before reuse.
 If skin irritation occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 In case of fire: Use for extinction: CO₂, powder or water spray.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a well-ventilated place. Keep cool.
 Store locked up.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:
· Additional classification according to Decree on Hazardous Materials:

Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.
 Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 13)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/05/2018

Reviewed on 03/05/2018

Trade name: Demulsifier, Petrolite DMO46

(Contd. of page 12)

· **Department issuing SDS:** Environment protection department.

· **Contact:**

· **Date of preparation / last revision**

Revision 0.1, 03-05-2018: updated ingredient information. STN

Creation date for SDS 01-14-2015. STN

03/05/2018 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Muta. 1B: Germ cell mutagenicity – Category 1B

Carc. 1B: Carcinogenicity – Category 1B

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1