Printing date 04/23/2018

Reviewed on 04/23/2018

Trade name: <u>Salt 10.0 lb</u> ASTM D32		
Article number: THE453		
Details of the supplier of Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	the safety data sheet	AQUA SOLUTIONS
Information department: Technical Coordinator Sherman Nelson sherman Emergency telephone nu Chemtrec: 800-424-9300 Canutec: 613-996-6666	@aquasolutions.org mber:	
Hazard(s) identificat	ion	
Classification of the subs		
GHS02 Flame		
Flam. Liq. 2 H225	Highly flammable liquid and vapor.	
GHS08 Health	hazard	
•	Causes damage to organs.	
STOT SE 1 H370		
GHS05 Corros	ion	
	ion Causes serious eye damage.	
GHS05 Corros		
GHS05 Corros Eye Dam. 1 H318	Causes serious eye damage. Harmful if swallowed.	
GHS05 Corros Eye Dam. 1 H318 GHS07 Acute Tox. 4 H302 Skin Irrit. 2 H315	Causes serious eye damage.	

Printing date 04/23/2018

Reviewed on 04/23/2018

Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

(Contd. of page 1)

US



Printing date 04/23/2018

Reviewed on 04/23/2018

Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH\*3Health = 
$$*3$$
FIRE3Fire = 3REACTIVITY0Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

= 3

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## **3** Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:				
CAS: 71-36-3 n	•	63.295%		
CAS: 67-56-1 M	ethanol (Methyl Alcohol)	36.324%		
v	· Table of Nonhazardous Ingredients			
CAS: 7647-14-5	Sodium Chloride	0.000244%		
CAS: 7791-18-6	Magnesium Chloride Hexahydrate	0.000148%		
CAS: 7732-18-5	Water	0.381%		

# **4** First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Immediately call a doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

# **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • Special hazards arising from the substance or mixture No further relevant information available.

- · Advice for firefighters
- · Protective equipment: No special measures required.

(Contd. on page 4)

Printing date 04/23/2018

Reviewed on 04/23/2018

#### Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

(Contd. of page 3)

· Personal precauti	ions, protective equipment and emergency procedures	
-	quipment. Keep unprotected persons away.	
• Environmental pr		
Dilute with plenty		
	nter sewers/ surface or ground water.	
	erial for containment and cleaning up:	
<i>Absorb with liquid</i> <i>Use neutralizing d</i>	d-binding material (sand, diatomite, acid binders, universal binders, sawdus	<i>t</i> ).
	ated material as waste according to item 13.	
Ensure adequate		
· Reference to othe		
	information on safe handling.	
	information on personal protection equipment.	
	disposal information.	
	Criteria for Chemicals	
• PAC-1:		
CAS: 71-36-3	n-Butyl Alcohol	60 ppm
CAS: 67-56-1	Methanol (Methyl Alcohol)	
CAS: 67-56-1		530 pp
CAS: 67-56-1 CAS: 7791-18-6	Methanol (Methyl Alcohol)	530 pp. 34 mg/
CAS: 67-56-1 CAS: 7791-18-6	Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate	530 pp. 34 mg/
CAS: 67-56-1 CAS: 7791-18-6 CAS: 10035-04-8	Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate	530 pp. 34 mg/ 16 mg/
CAS: 67-56-1 CAS: 7791-18-6 CAS: 10035-04-8 · <b>PAC-2:</b>	Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate Calcium Chloride Dihydrate	530 pp. 34 mg/ 16 mg/ 800 ppm 2,100 pp
CAS: 67-56-1 CAS: 7791-18-6 CAS: 10035-04-8 • <b>PAC-2:</b> CAS: 71-36-3 CAS: 67-56-1 CAS: 7791-18-6	Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate Calcium Chloride Dihydrate n-Butyl Alcohol Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate	530 pp. 34 mg/ 16 mg/ 800 ppm 2,100 pp 370 mg/
CAS: 67-56-1 CAS: 7791-18-6 CAS: 10035-04-8 • <b>PAC-2:</b> CAS: 71-36-3 CAS: 67-56-1 CAS: 7791-18-6	Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate Calcium Chloride Dihydrate n-Butyl Alcohol Methanol (Methyl Alcohol)	530 pp 34 mg/i 16 mg/i 800 ppm 2,100 pp 370 mg/i
CAS: 67-56-1 CAS: 7791-18-6 CAS: 10035-04-8 • <b>PAC-2:</b> CAS: 71-36-3 CAS: 67-56-1 CAS: 7791-18-6	Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate Calcium Chloride Dihydrate n-Butyl Alcohol Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate	530 pp. 34 mg/ 16 mg/ 800 ppm 2,100 pp 370 mg/
CAS: 67-56-1 CAS: 7791-18-6 CAS: 10035-04-8 • <b>PAC-2:</b> CAS: 71-36-3 CAS: 67-56-1 CAS: 7791-18-6 CAS: 10035-04-8	Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate Calcium Chloride Dihydrate n-Butyl Alcohol Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate	530 pp. 34 mg/s 16 mg/s 800 ppm 2,100 pp 370 mg/s 170 mg/s
CAS: 67-56-1 CAS: 7791-18-6 CAS: 10035-04-8 • <b>PAC-2:</b> CAS: 71-36-3 CAS: 67-56-1 CAS: 7791-18-6 CAS: 10035-04-8 • <b>PAC-3:</b>	Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate Calcium Chloride Dihydrate n-Butyl Alcohol Methanol (Methyl Alcohol) Magnesium Chloride Hexahydrate Calcium Chloride Dihydrate	800 ppm 34 mg/i 16 mg/i 800 ppm 2,100 pp 370 mg/i 170 mg/i 8000** pp 7200* ppm

# 7 Handling and storage

· Handling:

- Precautions for safe handling No special precautions are necessary if used correctly.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- *Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.*

(Contd. on page 5)

<sup>-</sup> US

Printing date 04/23/2018

Reviewed on 04/23/2018

(Contd. of page 4)

Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

• Specific end use(s) No further relevant information available.

# 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 71-36-3 n-Butyl Alcohol

PEL Long-term value: 300 mg/m<sup>3</sup>, 100 ppm

REL Ceiling limit value: 150 mg/m<sup>3</sup>, 50 ppm Skin

*TLV* Long-term value: 61 mg/m<sup>3</sup>, 20 ppm

# CAS: 67-56-1 Methanol (Methyl Alcohol)

- PEL Long-term value: 260 mg/m<sup>3</sup>, 200 ppm
  REL Short-term value: 325 mg/m<sup>3</sup>, 250 ppm Long-term value: 260 mg/m<sup>3</sup>, 200 ppm Skin
  TLV Short-term value: 328 mg/m<sup>3</sup>, 250 ppm
- Long-term value: 262 mg/m<sup>3</sup>, 200 ppm Skin; BEI

· Ingredients with biological limit values:

CAS: 67-56-1 Methanol (Methyl Alcohol)

BEI 15 mg/L

LD50 Intraperitoneal: urine Time: end of shift LD50: Methanol (background, nonspecific)

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.

Avoid contact with the skin.

- Avoid contact with the eyes and skin.
- Breathing equipment: Not required.
- Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

(Contd. on page 6)

US

Printing date 04/23/2018

Reviewed on 04/23/2018

#### Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

(Contd. of page 5)

US

## · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. • Penetration time of glove material

# The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

#### 9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Liquid Color: Clear · Odor: Alcohol-like · Odor threshold: Not determined. Not determined. · pH-value: · Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 64 °C (147.2 °F) 11 °C (51.8 °F) · Flash point: · Flammability (solid, gaseous): Not applicable. 340 °C (644 °F) · Ignition temperature: · Decomposition temperature: Not determined. · Auto igniting: Product is not selfigniting. · Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. · Explosion limits: Lower: 1.5 Vol % Upper: 44 Vol % · Vapor pressure at 20 °C (68 °F): 128 hPa (96 mm Hg) • Density at 20 •C (68 •F): 0.80614 g/cm<sup>3</sup> (6.72724 lbs/gal) · Relative density Not determined. · Vapor density Not determined. Not determined. · Evaporation rate · Solubility in / Miscibility with Water: Fully miscible. (Contd. on page 7)

Printing date 04/23/2018

Reviewed on 04/23/2018

#### Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

Partition coefficient (n-octan	ol/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Solvent content:		
Organic solvents:	99.6 %	
Water:	0.4 %	
VOC content:	99.62 %	
	803.1 g/l / 6.70 lb/gl	
Solids content:	0.0 %	
Other information	No further relevant information available.	

# **10 Stability and reactivity**

· Reactivity No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

# **11** Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

#### ATE (Acute Toxicity Estimate)

Oral	LD50	903-1,073 mg/kg (rat)
Dermal	LD50	5,372 mg/kg (rabbit)
Inhalative	LC50/4h	353 mg/l (rat)

#### CAS: 71-36-3 n-Butyl Alcohol

Oral	LD50	500 mg/kg (ATE)
CAS: 67-5	6-1 Metha	anol (Methyl Alcohol)
	LD50	100 mg/kg (ATE)
Dermal	LD50	300 mg/kg (ATE)
Inhalative	LC50/4h	3 mg/l (ATE)

## · Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

• on the eye: Strong irritant with the danger of severe eye injury.

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

(Contd. on page 8)

Printing date 04/23/2018

Reviewed on 04/23/2018

(Contd. of page 7)

#### Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

## · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

· Toxicity

- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized. Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.
- Other adverse effects No further relevant information available.

# **13 Disposal considerations**

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- **Recommendation:** Disposal must be made according to official regulations.
- Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number	
· DOT, IMDG, IATA	UN1993
· UN proper shipping name	
· DOT	Flammable liquids, n.o.s. (Methanol, Butanols)
· IMDG, IATA	FLAMMABLE LIQUID, N.O.S. (METHANOL, BUTANOLS)

Printing date 04/23/2018

Reviewed on 04/23/2018

Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

	(Contd. of page
Transport hazard class(es)	
DOT	
3	
Class Label	3 Flammable liquids 3
IMDG, IATA	
3	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Stowage Category	В
Transport in bulk according to Annex	
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (METHANO)
	BUTANOLS), 3, II

# **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

• Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 10)

US -

Printing date 04/23/2018

Reviewed on 04/23/2018

Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

	(Contd. of page 9)
· Section 313 (Specific toxic chemical listings):	
CAS: 71-36-3 n-Butyl Alcohol	
CAS: 67-56-1 Methanol (Methyl Alcohol)	
• TSCA (Toxic Substances Control Act):	
n-Butyl Alcohol	
Methanol (Methyl Alcohol)	
Sodium Chloride	
Water	
· Proposition 65	
· Chemicals known to cause cancer:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
CAS: 67-56-1 Methanol (Methyl Alcohol)	

· Carcinogenic categories

· EPA (Environmental Protection Agency)

CAS: 71-36-3 n-Butyl Alcohol

• TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

Hazard-determining components of labeling: n-Butyl Alcohol Methanol (Methyl Alcohol)
Hazard statements Highly flammable liquid and vapor. Harmful if swallowed. Causes skin irritation. Causes serious eye damage. Causes damage to organs. May cause respiratory irritation. May cause drowsiness or dizziness.
Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed.

(Contd. on page 11)

D

Printing date 04/23/2018

Reviewed on 04/23/2018

#### Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

(Contd. of page 10) Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eve protection/face protection. If swallowed: Call a poison center/doctor if you feel unwell. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Specific treatment (see on this label). Rinse mouth. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of preparation / last revision Revision 0.0, 04-23-2018: Creation date for SDS. STN 04/23/2018 / -
- Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety **OSHA:** Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit BEI: Biological Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Acute Tox. 4: Acute toxicity - Category 4

(Contd. on page 12)

US

Printing date 04/23/2018

Reviewed on 04/23/2018

Trade name: Salt 10.0 lb/1000bbl of Crude ASTM D3230

(Contd. of page 11)

US

Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 STOT SE 1: Specific target organ toxicity (single exposure) – Category 1