Printing date 06/04/2024

*

Reviewed on 06/04/2024

AQUA
AQUA SOLUTIONS
AQUA SOLUTIONS
AQUA SOLUTIONS
H224 Extremely flammable liquid and vapor.
H272 May intensify fire; oxidizer.
2 H371 May cause damage to the central nervous system ar the visual organs.
H314 Causes severe skin burns and eye damage.
H318 Causes serious eye damage.
H332 Harmful if inhaled.

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution 10% Nitric Acid in Alcohol



The substance possesses oxidizing properties.

(Contd. on page 3)

US

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution 10% Nitric Acid in Alcohol

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

HEALTH*3Health =
$$*3$$
FIRE4Fire = 4REACTIVITY0Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

= 4

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

• Dangerous com	ponents:	
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	74.282%
CAS: 7697-37-2	Nitric Acid	17.464%
CAS: 67-56-1	Methanol	4.127%
CAS: 67-63-0	Isopropanol	4.127%

4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist. In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution

10% Nitric Acid in Alcohol

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures Mount respiratory protective device.
Wear protective equipment. Keep unprotected persons away.
Environmental precautions: Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralizing agent.
Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· PAC-1:		
1110 11		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 7697-37-2	Nitric Acid	0.16 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 67-63-0	Isopropanol	400 ppm
· PAC-2:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppm
CAS: 7697-37-2	Nitric Acid	24 ppm
CAS: 67-56-1	Methanol	2,100 ppm
CAS: 67-63-0	Isopropanol 2	
· PAC-3:		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 7697-37-2	Nitric Acid	92 ppm
CAS: 67-56-1	Methanol	7200* ppm
CAS: 67-63-0	Isopropanol	12000** ppm

7 Handling and storage

· Handling:

- · Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

(Contd. on page 5)

US

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution 10% Nitric Acid in Alcohol

(Contd. of page 4)

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:
- Keep receptacle tightly sealed.

Do not gas tight seal receptacle.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

8 Exp	osure controls/personal protection
· Addi	tional information about design of technical systems: No further data; see section 7.
· Cont	rol parameters
· Com	ponents with limit values that require monitoring at the workplace:
CAS:	: 64-17-5 Ethyl Alcohol, Absolute 200 Proof
PEL	Long-term value: 1900 mg/m³, 1000 ppm
REL	Long-term value: 1900 mg/m³, 1000 ppm
TLV	Short-term value: 1000 ppm
	A3
CAS:	: 7697-37-2 Nitric Acid
PEL	Long-term value: 5 mg/m³, 2 ppm
REL	Short-term value: 10 mg/m³, 4 ppm
	Long-term value: 5 mg/m³, 2 ppm
TLV	Short-term value: (4) NIC-0.025* ppm
	Long-term value: (2) ppm *inh. fraction + vapor, NIC-A4
CAS	**************************************
	Long-term value: 260 mg/m ³ , 200 ppm
REL	Short-term value: 325 mg/m ³ , 250 ppm
	Long-term value: 260 mg/m³, 200 ppm Skin
TLV	Short-term value: 250 ppm
1127	Long-term value: 200 ppm
	Skin; BEI
CAS.	: 67-63-0 Isopropanol
PEL	Long-term value: 980 mg/m ³ , 400 ppm
REL	Short-term value: 1225 mg/m³, 500 ppm
	Long-term value: 980 mg/m³, 400 ppm
TLV	Short-term value: 400 ppm
	Long-term value: 200 ppm
	BEI, A4
	(Contd. on page 6)

- US

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution

10% Nitric Acid in Alcohol

(Contd. of page 5)

Ingredients with biological limit values: CAS: 67-56-1 Methanol	
BEI 15 mg/L	
LD50 Intraperitoneal: urine	
Time: end of shift	
LD50: Methanol (background, nonspecific)	
CAS: 67-63-0 Isopropanol	
BEI 40 mg/L	
LD50 Intraperitoneal: urine	
<i>Time: end of shift at end of workweek</i>	
LD50: Acetone (background, nonspecific)	
Additional information: The lists that were valid during the creation were used as basis.	
Exposure controls	
Personal protective equipment:	
General protective and hygienic measures:	
Keep away from foodstuffs, beverages and feed.	
Immediately remove all soiled and contaminated clothing.	
Wash hands before breaks and at the end of work.	
Avoid contact with the eyes.	
Avoid contact with the eyes and skin.	
Breathing equipment:	
In case of brief exposure or low pollution use respiratory filter device. In case of intensive of	or longer exposure i
respiratory protective device that is independent of circulating air.	· ·
Protection of hands:	
Protective gloves	
The glove material has to be impermeable and resistant to the product/ the substance/ the pr	eparation.
Due to missing tests no recommendation to the glove material can be given for the product chemical mixture.	
Selection of the glove material on consideration of the penetration times, rates of diffusion a	nd the degradation
Material of gloves	na me degradament
The selection of the suitable gloves does not only depend on the material, but also on furthe	r marks of auality a
varies from manufacturer to manufacturer. As the product is a preparation of several substa	
the glove material can not be calculated in advance and has therefore to be checked prior to	
Penetration time of glove material	ine appreciation
The exact break through time has to be found out by the manufacturer of the protective	eloves and has to
observed.	0
Eye protection:	

Tightly sealed goggles

· Body protection: Protective work clothing

(Contd. on page 7)

Printing date 06/04/2024

*

Reviewed on 06/04/2024

Trade name: Nital Etch Solution

10% Nitric Acid in Alcohol

(Contd. of page 6)

Information on basic physical and ch	nemical properties
General Information	temicui properties
Appearance:	
Form:	Liquid
Color:	White
Odor:	Alcohol-like
Odor threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	<35 °C (<95 °F)
Flash point:	11 °C (51.8 °F)
Flammability (solid, gaseous):	Not applicable.
Auto igniting:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Ignition temperature:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	3.5 Vol %
Upper:	19 Vol %
Vapor pressure at 20 °C (68 °F):	59 hPa (44.3 mm Hg)
Vapor pressure at 20 °C (122 °F):	280 hPa (210 mm Hg)
Density at 20 °C (68 °F):	0.86061 g/cm ³ (7.18179 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Fully miscible.
Partition coefficient (n-octanol/water	-
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	82.5 %
VOC content:	82.54 %
	710.3 g/l / 5.93 lb/gal
Solids content:	0.0 %

(Contd. on page 8)

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution

10% Nitric Acid in Alcohol

(Contd. of page 7)

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral	LD50	2,423 mg/kg
Dermal	LD50	7,270 mg/kg
Inhalative	LC50/4h	13.9 mg/l

· Primary irritant effect:

- on the skin: Strong caustic effect on skin and mucous membranes.
- on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	1
CAS: 67-63-0 Isopropanol	3
· NTP (National Toxicology Program)	
None of the ingredients is listed.	
· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

12 Ecological information

· Toxicity

· Aquatic toxicity: No further relevant information available.

· Persistence and degradability No further relevant information available.

(Contd. on page 9)

US

Printing date 06/04/2024

Trade name: Nital Etch Solution 10% Nitric Acid in Alcohol Reviewed on 06/04/2024

(Contd. of page 8)

- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- \cdot **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- **vPvB**: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

· UN-Number · DOT, IMDG, IATA	UN2924
· UN proper shipping name · DOT	Flammable liquids, corrosive, n.o.s. (Ethanol, Nitric Ac. Methanol, Isopropanol
· IMDG, IATA	, FLAMMABLE LIQUID, CORROSIVE, N.O.S. (Ethanol, Nit. Acid, Methanol, Isopropanol)
· Transport hazard class(es)	
·DOT	
RAMMARIE LOOP	
· Class	3 Flammable liquids
· Label	3, 8
· IMDG	

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution 10% Nitric Acid in Alcohol

	(Contd. of page
Label	3/8
IATA	
Class	3 Flammable liquids
Label	3 (8)
Packing group	
DOT, IMDG, IATA	Ι
Environmental hazards:	Not applicable.
Special precautions for user	Warning: Flammable liquids
Hazard identification number (Kemler	code): 338
EMS Number:	F- E , S - C
Segregation groups	(SGG1) Acids
Stowage Category	E
Stowage Code	SW2 Clear of living quarters.
Transport in bulk according to Annex I	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 0.5 L
	On cargo aircraft only: 2.5 L
IMDG	
Limited quantities (LQ)	0
Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
UN "Model Regulation":	UN 2924 FLAMMABLE LIQUID, CORROSIVE, N.O.S
÷	(ETHANOL, NITRIC ACID, METHANOL, ISOPROPANOL
), 3 (8), I

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available. • Sara

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution

10% Nitric Acid in Alcohol

	(Contd. of page
Nitric Acid	ACTI
Methanol	ACTI
Isopropanol	ACTI
Hazardous Air Pollutants	
CAS: 67-56-1 Methanol	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	
CAS: 67-56-1 Methanol	
Carcinogenic categories	
EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
TLV (Threshold Limit Value)	
CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof	
CAS: 67-63-0 Isopropanol	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	
GHS label elements The product is classified and labeled according to the Hazard pictograms	
GHS02 GHS03 GHS05 GHS07 GHS08	
GHS02 GHS03 GHS05 GHS07 GHS08 • Signal word Danger • Hazard-determining components of labeling: Nitric Acid Methanol • Hazard statements Extremely flammable liquid and vapor. May intensify fire; oxidizer.	
Signal word Danger Hazard-determining components of labeling: Nitric Acid Methanol Hazard statements Extremely flammable liquid and vapor.	

May cause damage to the central nervous system and the visual organ
Precautionary statements
Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Keep/Store away from clothing/combustible materials.
Take any precaution to avoid mixing with combustibles.
Keep container tightly closed.

(Contd. on page 12)

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution 10% Nitric Acid in Alcohol

(Contd. of page 11)

Ground/bond container and receiving equipment.
Use explosion-proof electrical/ventilating/lighting/equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Do not breathe dusts or mists.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If swallowed: Rinse mouth. Do NOT induce vomiting.
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Immediately call a poison center/doctor.
IF exposed or concerned: Call a poison center/doctor.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
In case of fire: Use CO2, powder or water spray to extinguish.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.
· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Environment protection department.

• Contact: Date of Preparation / Last Revision:

- Date of preparation / last revision Revision 1.2, 06/04/2024: Reviewed SDS for accuracy. MH/STN Revision 0.0, 05-29-2024: Creation date for SDS. STN 06/04/2024
- · Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit **BEI:** Biological Exposure Limit Flammable Liquids 1: Flammable liquids - Category 1

(Contd. on page 13)

US

Printing date 06/04/2024

Reviewed on 06/04/2024

Trade name: Nital Etch Solution 10% Nitric Acid in Alcohol

(Contd. of page 12)

Oxidizing Liquids 2: Oxidizing liquids – Category 2 Acute Toxicity - Inhalation 4: Acute toxicity – Category 4 Skin Corrosion 1A: Skin corrosion/irritation – Category 1A Eye Damage 1: Serious eye damage/eye irritation – Category 1 Specific Target Organ Toxicity - Single Exposure 2: Specific target organ toxicity (single exposure) – Category 2 • * Data compared to the previous version altered.