

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

## 1 Identification

- **Product identifier**
- **Trade name:** Sulfate Std. 4.0 mg/kg  
Soln., Prep to ASTM D 7318-07
- **Article number:** SPE908
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Aqua Solutions, Inc.  
6913 Highway 225  
DEER PARK, TX 77536  
USA  
800-256-2586
- **Information department:**  
Technical Coordinator  
Sherman Nelson [shermann@aquasolutions.org](mailto:shermann@aquasolutions.org)
- **Emergency telephone number:**  
Chemtrec: 800-424-9300  
Canutec: 613-996-6666



## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

Flammable Liquids 2

H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Specific Target Organ Toxicity - Single Exposure 2 H371 May cause damage to the central nervous system and the visual organs.



GHS07

Acute Toxicity - Oral 4

H302 Harmful if swallowed.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*
- **Hazard-determining components of labeling:**  
Methanol
- **Hazard statements**  
Highly flammable liquid and vapor.

(Contd. on page 2)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

**Trade name: Sulfate Std. 4.0 mg/kg**  
**Soln., Prep to ASTM D 7318-07**

(Contd. of page 1)

*Harmful if swallowed.*

*May cause damage to the central nervous system and the visual organs.*

· **Precautionary statements**

*Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*

*Keep container tightly closed.*

*Ground/bond container and receiving equipment.*

*Use explosion-proof electrical/ventilating/lighting/equipment.*

*Use only non-sparking tools.*

*Take precautionary measures against static discharge.*

*Do not breathe dust/fume/gas/mist/vapors/spray.*

*Wash thoroughly after handling.*

*Do not eat, drink or smoke when using this product.*

*Wear protective gloves/protective clothing/eye protection/face protection.*

*If swallowed: Call a poison center/doctor if you feel unwell.*

*Rinse mouth.*

*If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*

*IF exposed or concerned: Call a poison center/doctor.*

*In case of fire: Use CO<sub>2</sub>, powder or water spray to extinguish.*

*Store in a well-ventilated place. Keep cool.*

*Store locked up.*

*Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 2

Fire = 3

Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

## 3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	90.01%
CAS: 67-56-1	Methanol	5.015%
CAS: 67-63-0	Isopropanol	4.973%

· **Table of Nonhazardous Ingredients**

CAS: 7757-82-6	Sodium Sulfate Anhydrous	0.001%
----------------	--------------------------	--------

US

(Contd. on page 3)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

**Trade name:** Sulfate Std. 4.0 mg/kg  
Soln., Prep to ASTM D 7318-07

(Contd. of page 2)

## 4 First-aid measures

- **Description of first aid measures**
- **General information:**  
Immediately remove any clothing soiled by the product.  
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Immediately rinse with water.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

## 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**  
CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**  
During heating or in case of fire poisonous gases are produced.
- **Advice for firefighters**
- **Protective equipment:** Mouth respiratory protective device.

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Mount respiratory protective device.  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- **Protective Action Criteria for Chemicals**

### · PAC-1:

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1,800 ppm
CAS: 67-56-1	Methanol	530 ppm
CAS: 67-63-0	Isopropanol	400 ppm
CAS: 7757-82-6	Sodium Sulfate Anhydrous	9.8 mg/m <sup>3</sup>

### · PAC-2:

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	3300* ppm
--------------	-----------------------------------	-----------

(Contd. on page 4)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

**Trade name: Sulfate Std. 4.0 mg/kg**  
**Soln., Prep to ASTM D 7318-07**

(Contd. of page 3)

CAS: 67-56-1	Methanol	2,100 ppm
CAS: 67-63-0	Isopropanol	2000* ppm
CAS: 7757-82-6	Sodium Sulfate Anhydrous	110 mg/m <sup>3</sup>
<b>· PAC-3:</b>		
CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	15000* ppm
CAS: 67-56-1	Methanol	7200* ppm
CAS: 67-63-0	Isopropanol	12000** ppm
CAS: 7757-82-6	Sodium Sulfate Anhydrous	650 mg/m <sup>3</sup>

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
 Ensure good ventilation/exhaustion at the workplace.  
 Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
 Keep ignition sources away - Do not smoke.  
 Protect against electrostatic charges.  
 Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**  
 Keep receptacle tightly sealed.  
 Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

**CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof**

PEL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

REL Long-term value: 1900 mg/m<sup>3</sup>, 1000 ppm

TLV Short-term value: 1000 ppm

A3

**CAS: 67-56-1 Methanol**

PEL Long-term value: 260 mg/m<sup>3</sup>, 200 ppm

REL Short-term value: 325 mg/m<sup>3</sup>, 250 ppm

Long-term value: 260 mg/m<sup>3</sup>, 200 ppm

Skin

TLV Short-term value: 250 ppm

Long-term value: 200 ppm

Skin; BEI

(Contd. on page 5)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

**Trade name: Sulfate Std. 4.0 mg/kg**  
**Soln., Prep to ASTM D 7318-07**

(Contd. of page 4)

## CAS: 67-63-0 Isopropanol

PEL	Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
REL	Short-term value: 1225 mg/m <sup>3</sup> , 500 ppm Long-term value: 980 mg/m <sup>3</sup> , 400 ppm
TLV	Short-term value: 400 ppm Long-term value: 200 ppm BEI, A4

### · Ingredients with biological limit values:

## CAS: 67-56-1 Methanol

BEI	15 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Methanol (background, nonspecific)
-----	--

## CAS: 67-63-0 Isopropanol

BEI	40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)
-----	--

· **Additional information:** The lists that were valid during the creation were used as basis.

### · Exposure controls

### · Personal protective equipment:

### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.  
 Immediately remove all soiled and contaminated clothing.  
 Wash hands before breaks and at the end of work.

### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

Trade name: Sulfate Std. 4.0 mg/kg  
Soln., Prep to ASTM D 7318-07

(Contd. of page 5)

· **Eye protection:**

Tightly sealed goggles

· **Body protection:** Protective work clothing

## 9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Liquid
Color:	Clear
Odor:	Alcohol
Odor threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	64 °C (147.2 °F)

· **Flash point:** 11 °C (51.8 °F)· **Flammability (solid, gaseous):** Highly flammable.· **Auto igniting:** 425 °C (797 °F)· **Decomposition temperature:** Not determined.· **Ignition temperature:** Product is not selfigniting.· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.· **Explosion limits:**

Lower:	3.5 Vol %
Upper:	19 Vol %

· **Vapor pressure at 20 °C (68 °F):** 59 hPa (44.3 mm Hg)· **Density at 20 °C (68 °F):** 0.7897 g/cm<sup>3</sup> (6.59005 lbs/gal)· **Relative density** Not determined.· **Vapor density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

· **Partition coefficient (n-octanol/water):** Not determined.· **Viscosity:**

Dynamic:	Not determined.
Kinematic:	Not determined.

(Contd. on page 7)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

Trade name: Sulfate Std. 4.0 mg/kg  
Soln., Prep to ASTM D 7318-07

(Contd. of page 6)

· <b>Solvent content:</b>	
Organic solvents:	100.0 %
VOC content:	100.00 %
	789.7 g/l / 6.59 lb/gal
· <b>Solids content:</b>	90.0 %
· <b>Other information</b>	No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

### ATE (Acute Toxicity Estimate)

Oral	LD50	1,994 mg/kg
Dermal	LD50	5,982 mg/kg
Inhalative	LC50/4h	59.8 mg/l

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:  
Harmful

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

CAS: 64-17-5	Ethyl Alcohol, Absolute 200 Proof	1
CAS: 67-63-0	Isopropanol	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 8)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

Trade name: Sulfate Std. 4.0 mg/kg  
Soln., Prep to ASTM D 7318-07

(Contd. of page 7)


## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**  
Water hazard class 1 (Self-assessment): slightly hazardous for water  
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

## 14 Transport information

- |   |   |
|---|---|
| · <b>UN-Number</b>  | UN1993  |
| · <b>DOT, IMDG, IATA</b>  |   |
| · <b>UN proper shipping name</b>  | Flammable liquids, n.o.s. (Ethanol, Methanol, Isopropanol ) |
| · <b>DOT</b>  |   |
| · <b>IMDG, IATA</b>   | FLAMMABLE LIQUID, N.O.S. (Ethanol, Methanol, Isopropanol )  |
| · <b>Transport hazard class(es)</b>   |   |
| · <b>DOT</b>  |   |
|  |   |
| · <b>Class</b>  | 3 Flammable liquids   |
| · <b>Label</b>  | 3   |

(Contd. on page 9)

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

Trade name: Sulfate Std. 4.0 mg/kg  
Soln., Prep to ASTM D 7318-07

(Contd. of page 8)

· **IMDG, IATA**

· **Class** 3 Flammable liquids  
· **Label** 3

· **Packing group**  
· **DOT, IMDG, IATA** II

· **Environmental hazards:** Not applicable.

· **Special precautions for user** Warning: Flammable liquids  
· **Hazard identification number (Kemler code):** 33  
· **EMS Number:** F-E, S-E  
· **Stowage Category** B

· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.

· **UN "Model Regulation":** UN 1993 FLAMMABLE LIQUID, N.O.S. (ETHANOL, METHANOL, ISOPROPANOL), 3, II

## 15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**  
No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

CAS: 67-56-1 Methanol

CAS: 67-63-0 Isopropanol

· **TSCA (Toxic Substances Control Act):**

Ethyl Alcohol, Absolute 200 Proof ACTIVE

Methanol ACTIVE

Isopropanol ACTIVE

Sodium Sulfate Anhydrous ACTIVE

· **Hazardous Air Pollutants**

CAS: 67-56-1 Methanol

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

(Contd. on page 10)

# Safety Data Sheet

## acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

**Trade name:** Sulfate Std. 4.0 mg/kg  
Soln., Prep to ASTM D 7318-07

(Contd. of page 9)

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

CAS: 67-56-1 Methanol

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

CAS: 64-17-5 Ethyl Alcohol, Absolute 200 Proof

A3

CAS: 67-63-0 Isopropanol

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** Danger

· **Hazard-determining components of labeling:**

Methanol

· **Hazard statements**

Highly flammable liquid and vapor.

Harmful if swallowed.

May cause damage to the central nervous system and the visual organs.

· **Precautionary statements**

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Call a poison center/doctor if you feel unwell.

Rinse mouth.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF exposed or concerned: Call a poison center/doctor.

In case of fire: Use CO2, powder or water spray to extinguish.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 11)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 05/30/2024

Reviewed on 05/30/2024

**Trade name:** Sulfate Std. 4.0 mg/kg  
Soln., Prep to ASTM D 7318-07

(Contd. of page 10)

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\*

## 16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.*

· **Department issuing SDS:** Environment protection department.

· **Contact:**

*Date of Preparation / Last Revision:*

· **Date of preparation / last revision**

*Revision 1.2, 05/30/2024: Reviewed SDS for accuracy. MH/STN*

*Revision 0.0, 11-05-2015: creation date for SDS. STN*

*05/30/2024*

· **Abbreviations and acronyms:**

*IMDG: International Maritime Code for Dangerous Goods*

*DOT: US Department of Transportation*

*IATA: International Air Transport Association*

*EINECS: European Inventory of Existing Commercial Chemical Substances*

*ELINCS: European List of Notified Chemical Substances*

*CAS: Chemical Abstracts Service (division of the American Chemical Society)*

*NFPA: National Fire Protection Association (USA)*

*HMIS: Hazardous Materials Identification System (USA)*

*VOC: Volatile Organic Compounds (USA, EU)*

*LC50: Lethal concentration, 50 percent*

*LD50: Lethal dose, 50 percent*

*PBT: Persistent, Bioaccumulative and Toxic*

*vPvB: very Persistent and very Bioaccumulative*

*NIOSH: National Institute for Occupational Safety*

*OSHA: Occupational Safety & Health*

*TLV: Threshold Limit Value*

*PEL: Permissible Exposure Limit*

*REL: Recommended Exposure Limit*

*BEI: Biological Exposure Limit*

*Flammable Liquids 2: Flammable liquids – Category 2*

*Acute Toxicity - Oral 4: Acute toxicity – Category 4*

*Specific Target Organ Toxicity - Single Exposure 2: Specific target organ toxicity (single exposure) – Category 2*

· **\* Data compared to the previous version altered.**

US