Printing date 08/06/2018

Reviewed on 08/06/2018

1 Identification

- · Product identifier
- Trade name: <u>Naphthalene 1.00% w/v</u> in Iso-Octane (PRF) Certified Standard
- · Article number: ND564
- Details of the supplier of the safety data sheet • Manufacturer/Supplier:

Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

- Information department: Technical Coordinator Sherman Nelson sherman@aquasolutions.org • Emergency telephone number:
- *Chemtrec:* 800-424-9300 *Canutec:* 613-996-6666

2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Carc. 2 H351 Suspected of causing cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.

GHS07

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling:* 2,2,4-*Trimethylpentane (Iso-Octane)* Naphthalene

(Contd. on page 2)



[–] US

Printing date 08/06/2018

Reviewed on 08/06/2018

Trade name: Naphthalene 1.00% w/v in Iso-Octane (PRF) Certified Standard

	(Contd. of page 1)
· Hazard statements	
Highly flammable liquid and vapor.	
Causes skin irritation.	
Suspected of causing cancer.	
May cause drowsiness or dizziness.	
May be fatal if swallowed and enters airways.	
· Precautionary statements	
Obtain special instructions before use.	
Do not handle until all safety precautions have been read and understood.	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/showe	r.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
IF exposed or concerned: Get medical advice/attention.	
Call a poison center/doctor if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	ns
· Classification system:	115.
· NFPA ratings (scale 0 - 4)	
Health = 1	
Fire = 3	
1 Reactivity = 0	
· HMIS-ratings (scale 0 - 4)	
\square	
FIRE 3 $Fire = 3$	
REACTIVITY \bigcirc <i>Reactivity</i> = 0	
· Other hazards	
· Results of PBT and vPvB assessment	
• PBT : Not applicable.	
• vPvB : Not applicable.	
11 1D. 1101 approacted.	

(Contd. on page 3)

Printing date 08/06/2018

Reviewed on 08/06/2018

Trade name: Naphthalene 1.00% w/v in Iso-Octane (PRF) Certified Standard

(Contd. of page 2)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

 Dangerous 	components:
-------------------------------	-------------

8	1	
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	98.563%
CAS: 91-20-3	Naphthalene	1.437%

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- \cdot Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- Dispose contaminated material as waste according to item 13.
- Ensure adequate ventilation.
- **Reference to other sections** See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	230 ppm
CAS: 91-20-3	Naphthalene	15 ppm
		(Contd. on page 4)

Printing date 08/06/2018

Reviewed on 08/06/2018

Trade name: Naphthalene 1.00% w/v in Iso-Octane (PRF) Certified Standard

		(Contd. of page 3)
· PAC-2:		
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	830 ppm
CAS: 91-20-3	Naphthalene	83 ppm
· PAC-3:		
CAS: 540-84-1	2,2,4-Trimethylpentane (Iso-Octane)	5000* ppm
CAS: 91-20-3	Naphthalene	500 ppm

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.

 \cdot Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- Additional information about design of technical systems: No further data; see item 7.
- · Control parameters

· Com	ponents with limit values that require monitoring at the workplace:
CAS:	: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)
	Long-term value: 2350 mg/m ³ , 500 ppm n-Octane only
TLV	Long-term value: 1401 mg/m³, 300 ppm
CAS:	91-20-3 Naphthalene

- PEL Long-term value: 50 mg/m³, 10 ppm
- REL Short-term value: 75 mg/m³, 15 ppm
 - Long-term value: 50 mg/m³, 10 ppm
- TLV Long-term value: 52 mg/m³, 10 ppm Skin; BEI

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

US

Printing date 08/06/2018

· Exposure controls

· Personal protective equipment:

Reviewed on 08/06/2018

Trade name: Naphthalene 1.00% w/v in Iso-Octane (PRF) Certified Standard

(Contd. of page 4)

· General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

Information on basic physical and General Information	chemical properties	
Appearance:		
Form:	Liquid	
Color:	Colorless	
Odor:	Sweetish	
Odor threshold:	Not determined.	
pH-value:	Not determined.	
Change in condition		
Melting point/Melting range:	-107 °C (-160.6 °F)	
Boiling point/Boiling range:	98-99 °C (208.4-210.2 °F)	

Printing date 08/06/2018

Reviewed on 08/06/2018

Trade name:	Naphthalene 1.00% w/v
	in Iso-Octane (PRF) Certified Standard

	(Contd. of page 5
· Flash point:	-12 °C (10.4 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	410 °C (770 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	6 Vol %
· Vapor pressure at 20 °C (68 °F):	15 hPa (11.3 mm Hg)
· Density at 20 °C (68 °F):	0.69348 g/cm ³ (5.78709 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
\cdot Evaporation rate	Not determined.
\cdot Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	er): Not determined.
· Viscosity:	
Dynamic at 20 °C (68 °F):	0.51 mPas
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	98.6 %
VOC content:	98.56 %
	683.5 g/l / 5.70 lb/gal
Solids content:	0.3 %
• Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

· Conditions to avoid No further relevant information available.

• *Incompatible materials:* No further relevant information available.

· Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

Printing date 08/06/2018

Reviewed on 08/06/2018

Trade name: Naphthalene 1.00% w/v in Iso-Octane (PRF) Certified Standard

(Contd. of page 6)

	<u> </u>	formation icological effects
\cdot Acute tox		
· LD/LC50	values tha	at are relevant for classification:
ATE (Acu	te Toxicity	y Estimate)
Oral	LD50	34,101 mg/kg (rat)
Dermal	LD50	>2,518 mg/kg (rat)
Inhalative	LC50/4h	38 mg/l (rat)
CAS: 91-2	20-3 Naph	thalene
Oral	LD50	500 mg/kg (ATE)
· Additiona	ion: No sei I toxicolog	nsitizing effects known. nsitizing effects known. g ical information: he following dangers according to internally approved calculation methods for preparations:
· Carcinog	U	
,		Agency for Research on Cancer)
CAS: 91-2	20-3 Naph	athalene 2B
		icology Program)
CAS: 91-2	20-3 Naph	nthalene R
· OSHA-Ca	ı (Occupat	tional Safety & Health Administration)

12 Ecological information

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.
- Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

(Contd. on page 8)

Printing date 08/06/2018

Reviewed on 08/06/2018

Trade name: Naphthalene 1.00% w/v in Iso-Octane (PRF) Certified Standard

(Contd. of page 7)

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- *Recommendation: Disposal must be made according to official regulations.*

UN-Number	
DOT, IMDG, IATA	UN1993
UN proper shipping name	
DOT	Flammable liquids, n.o.s. (Octanes)
IMDG	FLAMMABLE LIQUID, N.O.S. (OCTANES, NAPHTHALEN CRUDE), MARINE POLLUTANT
IATA	FLAMMABLE LIQUID, N.O.S. (OCTANES)
Transport hazard class(es)	
DOT	
CRAMABLE LODO	
3	
Class	3 Flammable liquids
Label	3
IMDG	
Class	3 Flammable liquids
Label	3
IATA	
Class	3 Flammable liquids
Label	3
Packing group	
DOT, IMDG, IATA	II
Environmental hazards:	Product contains environmentally hazardous substances: 2,2 Trimethylpentane (Iso-Octane)
Marine pollutant:	Symbol (fish and tree)
Special precautions for user	Warning: Flammable liquids

Printing date 08/06/2018

Reviewed on 08/06/2018

Trade name: Naphthalene 1.00% w/v in Iso-Octane (PRF) Certified Standard

	(Contd. of pa
Danger code (Kemler):	33
EMS Number:	F- E , S - E
· Stowage Category	B
• Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
• Transport/Additional information:	
DOT	
• Quantity limitations	On passenger aircraft/rail: 5 L
2	On cargo aircraft only: 60 L
· IMDG	
· Limited quantities (LQ)	1L
\cdot Excepted quantities ($\widetilde{E}Q$)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1993 FLAMMABLE LIQUIDS, N.O.S. (OCTANES), 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):	
None of the ingredients is listed.	
· Section 313 (Specific toxic chemical listings):	
CAS: 91-20-3 Naphthalene	
· TSCA (Toxic Substances Control Act):	
2,2,4-Trimethylpentane (Iso-Octane)	
Naphthalene	
· Proposition 65	
· Chemicals known to cause cancer:	
CAS: 91-20-3 Naphthalene	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
· Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
CAS: 540-84-1 2,2,4-Trimethylpentane (Iso-Octane)	II
CAS: 91-20-3 Naphthalene	C, CBD
· TLV (Threshold Limit Value established by ACGIH)	
CAS: 91-20-3 Naphthalene	A4
(Co	ntd. on page 10)

Printing date 08/06/2018

Reviewed on 08/06/2018

Trade name: Naphthalene 1.00% w/v in Iso-Octane (PRF) Certified Standard

(Contd. of page 9) · NIOSH-Ca (National Institute for Occupational Safety and Health) None of the ingredients is listed. • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS02 GHS07 GHS08 · Signal word Danger · Hazard-determining components of labeling: 2,2,4-Trimethylpentane (Iso-Octane) Naphthalene · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF exposed or concerned: Get medical advice/attention. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

(Contd. on page 11)

Printing date 08/06/2018

Reviewed on 08/06/2018

Trade name: Naphthalene 1.00% w/v in Iso-Octane (PRF) Certified Standard

(Contd. of page 10)

16 Other information This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. · Department issuing SDS: Environment protection department. · Contact: · Date of preparation / last revision Revsion 0.1, 08/06/2018: Creation date for SDS. STN 08/06/2018 / -· Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 Asp. Tox. 1: Aspiration hazard – Category 1