Printing date 07/17/2019 Reviewed on 09/27/2018

1 Identification

· Product identifier

· Trade name: <u>Buffer Solution pH 4.5 +- 0.2</u>

Hach EZ 2306

· Article number: ND579

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA

800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number:

Chemtrec: 800-424-9300 Canutec: 613-996-6666



2 Hazard(s) identification

· Classification of the substance or mixture



 $GHS02\ Flame$

Flam. Liq. 3 H226 Flammable liquid and vapor.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

Acetic Acid

· Hazard statements

Flammable liquid and vapor.

Causes severe skin burns and eye damage.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

(Contd. on page 2)

Printing date 07/17/2019 Reviewed on 09/27/2018

Trade name: Buffer Solution pH 4.5 +- 0.2

Hach EZ 2306

(Contd. of page 1)

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Classification system:
- · NFPA ratings (scale 0 4)



Health = 3Fire = 2Reactivity = 0

· HMIS-ratings (scale 0 - 4)



3 Health = 3Fire = 2

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- · Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
CAS: 64-19-7 Acetic Acid 35.612%			
· Table of Nonhaz	ardous Ingredients		
CAS: 631-61-8	Ammonium Acetate	24.157%	
CAS: 7732-18-5	Water	40.231%	

4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Printing date 07/17/2019 Reviewed on 09/27/2018

Trade name: Buffer Solution pH 4.5 +- 0.2

Hach EZ 2306

(Contd. of page 2)

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · Special hazards arising from the substance or mixture
- During heating or in case of fire poisonous gases are produced.
- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/surface or ground water.

· Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralizing agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· Protective Action Criteria for Chemicals

· PAC-1:		
CAS: 64-19-7	Acetic Acid	5 ppm
CAS: 631-61-8	Ammonium Acetate	3.8 mg/m^3
· PAC-2:		
CAS: 64-19-7	Acetic Acid	35 ppm
CAS: 631-61-8	Ammonium Acetate	42 mg/m ³
· PAC-3:		
CAS: 64-19-7	Acetic Acid	250 ppm
CAS: 631-61-8	Ammonium Acetate	250 mg/m ³

US

Printing date 07/17/2019 Reviewed on 09/27/2018

Trade name: Buffer Solution pH 4.5 +- 0.2

Hach EZ 2306

(Contd. of page 3)

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- · Components with limit values that require monitoring at the workplace:

CAS: 64-19-7 Acetic Acid

PEL Long-term value: 25 mg/m³, 10 ppm
REL Short-term value: 37 mg/m³, 15 ppm
Long-term value: 25 mg/m³, 10 ppm
TLV Short-term value: 37 mg/m³, 15 ppm
Long-term value: 25 mg/m³, 10 ppm

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Printing date 07/17/2019 Reviewed on 09/27/2018

Trade name: Buffer Solution pH 4.5 +- 0.2

Hach EZ 2306

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties
· Information on basic physical and chemical properties

· General Information · Appearance:

Form: Liquid Color: Clear

Odor: Acetic Acid OdorOdor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined. **Boiling point/Boiling range:** 100 °C (212 °F)

• Flash point: $40 \, ^{\circ}C \, (104 \, ^{\circ}F)$

· Flammability (solid, gaseous): Not applicable.

• Ignition temperature: $485 \, ^{\circ}C \, (905 \, ^{\circ}F)$

• **Decomposition temperature:** Not determined.

· Auto igniting: Product is not selfigniting.

Danger of explosion: Product is not explosive. However, formation of explosive air/vapor

mixtures are possible.

· Explosion limits:

 Lower:
 4 Vol %

 Upper:
 17 Vol %

• Vapor pressure at 20 °C (68 °F): 23 hPa (17.3 mm Hg)

• Density at 20 °C (68 °F): 1.03578 g/cm³ (8.64358 lbs/gal)

• Relative density
• Vapor density
• Vapor density
• Not determined.
• Not determined.

· Evaporation rate Not determined.

(Contd. on page 6)

Printing date 07/17/2019 Reviewed on 09/27/2018

Trade name: Buffer Solution pH 4.5 +- 0.2

Hach EZ 2306

		(Contd. of page
· Solubility in / Miscibility with		
Water:	Fully miscible.	
Partition coefficient (n-octan	ol/water): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	35.6 %	
Water:	40.2 %	
VOC content:	35.61 %	
	368.9 g/l / 3.08 lb/gal	
Solids content:	24.2 %	
· Other information	No further relevant information available.	

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are relevant for classification:
--

ATE (Acute Toxicity Estimate)

 Oral
 LD50
 9,295 mg/kg (rat)

 Dermal
 LD50
 2,977 mg/kg (rabbit)

CAS: 64-19-7 Acetic Acid

Dermal LD50 1,100 mg/kg (ATE)

- · Primary irritant effect:
- · on the skin: Caustic effect on skin and mucous membranes.
- · on the eye:

Strong caustic effect.

Strong irritant with the danger of severe eye injury.

- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

 $\label{thm:condition} \textit{The product shows the following dangers according to internally approved calculation methods for preparations:}$

Corrosive

Irritant

(Contd. on page 7)

Printing date 07/17/2019 Reviewed on 09/27/2018

Trade name: Buffer Solution pH 4.5 +- 0.2

Hach EZ 2306

(Contd. of page 6)

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

1 4 7	T				, •
141	Trans	port	ınto	rma	tion

· UN-Number · DOT, IMDG, IATA	UN3265
· UN proper shipping name	Corrosive liquid, acidic, organic, n.o.s. (Acetic acid, glacial)
· DOT	CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S. (ACETIC ACID,
· IMDG, IATA	GLACIAL)

(Contd. on page 8)

Printing date 07/17/2019 Reviewed on 09/27/2018

Trade name: Buffer Solution pH 4.5 +- 0.2

Hach EZ 2306

(Contd. of page 7)

		Trans	port	hazard	class	(es)
--	--	-------	------	--------	-------	-----	---

 $\cdot DOT$



· Class 8 Corrosive substances

· Label

· IMDG, IATA



· Class 8 Corrosive substances · Label

· Packing group

· DOT, IMDG, IATA III

· Environmental hazards: Not applicable.

Warning: Corrosive substances · Special precautions for user

· Danger code (Kemler): 80 · EMS Number: F-A,S-B· Segregation groups Acids · Stowage Category

· Stowage Code SW2 Clear of living quarters.

· Transport in bulk according to Annex II of

MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

 $\cdot DOT$

· Quantity limitations On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L

· IMDG

· Limited quantities (LQ) 5L

Code: E1 · Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· UN "Model Regulation": UN 3265 CORROSIVE LIQUID, ACIDIC, ORGANIC, N.O.S.

(ACETIC ACID, GLACIAL), 8, III

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

(Contd. on page 9)

Printing date 07/17/2019 Reviewed on 09/27/2018

Trade name: Buffer Solution pH 4.5 +- 0.2

Hach EZ 2306

	(Contd. of pa
· Section 313 (Specific toxic chemical listings):	
None of the ingredients is listed.	
· TSCA (Toxic Substances Control Act):	
Acetic Acid	ACTI
Ammonium Acetate	ACTI
Water	ACTI
· Hazardous Air Pollutants	·
None of the ingredients is listed.	
Proposition 65	
Chemicals known to cause cancer:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
Chemicals known to cause developmental toxicity:	
None of the ingredients is listed.	
· Carcinogenic categories	
EPA (Environmental Protection Agency)	
CAS: 631-61-8 Ammonium Acetate	
TLV (Threshold Limit Value established by ACGIH)	
None of the ingredients is listed.	
NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms





GHS02

GHS05

- · Signal word Danger
- · Hazard-determining components of labeling:

Acetic Acid

· Hazard statements

Flammable liquid and vapor.

Causes severe skin burns and eye damage.

· Precautionary statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Keep container tightly closed.

Ground/bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dusts or mists.

Printing date 07/17/2019 Reviewed on 09/27/2018

Trade name: Buffer Solution pH 4.5 +- 0.2

Hach EZ 2306

(Contd. of page 9)

Wash thoroughly after handling.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Rinse mouth. Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a poison center/doctor.

Specific treatment (see on this label).

Wash contaminated clothing before reuse.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revision 0.1, 07-17-2017: updated description. STN

07/17/2019 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 3: Flammable liquids – Category 3

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

HC