Printing date 04/11/2019

Reviewed on 04/11/2019

Identification	
Product identifier	
Trade name: <u>Calibration Standard D</u> ASTM D6591-18	
Article number: HOU048	
Details of the supplier of the safety data sheet Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586	AQUA
Information department: Technical Coordinator Sherman Nelson sherman@aquasolutions.org Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666	
Hazard(s) identification	
Classification of the substance or mixture GHS02 Flame	
Flam. Liq. 2 H225 Highly flammable liquid and vapor. GHS08 Health hazard	
Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.	
GHS07	
Skin Irrit. 2 H315 Causes skin irritation. STOT SE 3 H336 May cause drowsiness or dizziness.	
Label elements GHS label elements The product is classified and labeled according Hazard pictograms	g to the Globally Harmonized System (GHS).
GHS02 GHS07 GHS08	
Signal word Danger	
Hazard-determining components of labeling:	
n-Heptane	
Cyclohexane	(Contd. on page

Printing date 04/11/2019

Reviewed on 04/11/2019

#### Trade name: Calibration Standard D ASTM D6591-18

Hazard statements	(Contd. of page
Highly flammable liquid and vapor.	
Causes skin irritation.	
May cause drowsiness or dizziness.	
May be fatal if swallowed and enters airways.	
Precautionary statements	
Keep away from heat/sparks/open flames/hot surfaces No smoking.	
Ground/bond container and receiving equipment.	
Use explosion-proof electrical/ventilating/lighting/equipment.	
Use only non-sparking tools.	
Take precautionary measures against static discharge.	
Avoid breathing dust/fume/gas/mist/vapors/spray	
Wash thoroughly after handling.	
Use only outdoors or in a well-ventilated area.	
Wear protective gloves/protective clothing/eye protection/face protection.	
If swallowed: Immediately call a poison center/doctor.	
Specific treatment (see on this label).	
Do NOT induce vomiting.	
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/showe	? <b>r.</b>
IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
Call a poison center/doctor if you feel unwell.	
Take off contaminated clothing and wash it before reuse.	
If skin irritation occurs: Get medical advice/attention.	
In case of fire: Use for extinction: CO2, powder or water spray.	
Store in a well-ventilated place. Keep container tightly closed.	
Store in a well-ventilated place. Keep cool.	
Store locked up.	
Dispose of contents/container in accordance with local/regional/national/international regulation	ons.
Classification system:	
NFPA ratings (scale 0 - 4)	
Health = 1	
Fire = $3$	
1 <i>Q Reactivity</i> = 0	
HMIS-ratings (scale 0 - 4)	
FIRE 3 $Fire = 3$	
<b>REACTIVITY O</b> $Reactivity = 0$	
Other hazards	
Results of PBT and vPvB assessment	
PBT: Not applicable.	
vPvB: Not applicable.	
* *	

· Chemical characterization: Mixtures

• Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

CAS: 142-82-5 *n*-Heptane

(Contd. on page 3)

99.739%

Printing date 04/11/2019

Reviewed on 04/11/2019

Trade name: Calibration Standard D ASTM D6591-18

		(Contd. of page 2)
· Table of Nonhazardous Ingredients		
CAS: 110-82-7	Cyclohexane	0.147%
CAS: 95-47-6	o-Xylene	0.0735%
CAS: 90-12-0	1-methylnaphthalene	0.0294%
	Phenanthrene, 98%	0.0107%

#### **4 First-aid measures**

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### **5** Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam. • For safety reasons unsuitable extinguishing agents: Water with full jet

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### **6** Accidental release measures

e equipment. Keep unprotected persons away.	
precautions: Do not allow to enter sewers/ surface or ground water.	
uid-binding material (sand, diatomite, acid binders, universal binders, sawdust).	
vinated material as waste according to item 13.	
e ventilation.	
her sections	
r information on safe handling.	
for disposal information.	
on Criteria for Chemicals	
n-Heptane	500 ppm
Cyclohexane	300 ppm
1-methylnaphthalene	20 mg/m <sup>3</sup>
	precautions: Do not allow to enter sewers/ surface or ground water. paterial for containment and cleaning up: uid-binding material (sand, diatomite, acid binders, universal binders, sawdust). ninated material as waste according to item 13. te ventilation. her sections or information on safe handling. or information on personal protection equipment. for disposal information. on Criteria for Chemicals n-Heptane Cyclohexane

Printing date 04/11/2019

Reviewed on 04/11/2019

#### Trade name: Calibration Standard D ASTM D6591-18

		(Contd. of page 3)
	Phenanthrene, 98%	$5.4 mg/m^3$
· PAC-2:		
CAS: 142-82-5	<u>^</u>	830 ppm
CAS: 110-82-7	Cyclohexane	1700* ppm
CAS: 90-12-0	1-methylnaphthalene	61 mg/m <sup>3</sup>
	Phenanthrene, 98%	59 mg/m <sup>3</sup>
· PAC-3:		
CAS: 142-82-5	n-Heptane	5000* ppm
CAS: 110-82-7	Cyclohexane	10000** ppm
CAS: 90-12-0	1-methylnaphthalene	360 mg/m <sup>3</sup>
	Phenanthrene, 98%	360 mg/m <sup>3</sup>

### 7 Handling and storage

#### · Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- $\cdot$  Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

CAS: 142-82-5 n-Heptane

- PEL Long-term value: 2000 mg/m<sup>3</sup>, 500 ppm
- REL Long-term value: 350 mg/m<sup>3</sup>, 85 ppm Ceiling limit value: 1800\* mg/m<sup>3</sup>, 440\* ppm \*15-min
- TLV Short-term value: 2050 mg/m<sup>3</sup>, 500 ppm Long-term value: 1640 mg/m<sup>3</sup>, 400 ppm

• Additional information: The lists that were valid during the creation were used as basis.

(Contd. on page 5)

US -

*Printing date 04/11/2019* 

Reviewed on 04/11/2019

#### Trade name: Calibration Standard D ASTM D6591-18

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the skin. Avoid contact with the eyes and skin.
- · Breathing equipment:
- In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

<ul> <li>Information on basic physical and</li> <li>General Information</li> </ul>	chemical properties	
· Appearance:		
Form:	Liquid	
Color:	Colorless	
· Odor:	Gasoline-like	
· Odor threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition		
Melting point/Melting range:	-90.5 °C (-130.9 °F)	
<b>Boiling point/Boiling range:</b>	98 °C (208.4 °F)	
· Flash point:	-4 °C (24.8 °F)	

Printing date 04/11/2019

Reviewed on 04/11/2019

#### Trade name: Calibration Standard D ASTM D6591-18

	(Contd. of page 5
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	215 °C (419 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
Explosion limits:	
Lower:	1.1 Vol %
Upper:	6.7 Vol %
Vapor pressure at 20 $^{\circ}C$ (68 $^{\circ}F$ ):	48 hPa (36 mm Hg)
Density at 20 °C (68 °F):	0.68043 g/cm <sup>3</sup> (5.67819 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water at 20 •C (68 •F):	0.05 g/l
Partition coefficient (n-octanol/wate	p <b>r):</b> Not determined.
Viscosity:	
<i>Dynamic at 20 •C (68 •F):</i>	0.4 mPas
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC content:	99.96 %
	680.2 g/l / 5.68 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

## **10 Stability and reactivity**

• *Reactivity* No further relevant information available.

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### **11 Toxicological information**

- · Information on toxicological effects
- · Acute toxicity:
- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: No irritating effect.

(Contd. on page 7)

US

Printing date 04/11/2019

Reviewed on 04/11/2019

#### Trade name: Calibration Standard D ASTM D6591-18

(Contd. of page 6)

3

3

R

· Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

#### · Carcinogenic categories

· IARC (International Agency)	for Research on Cancer)
-------------------------------	-------------------------

CAS: 95-47-6 o-Xylene

Phenanthrene, 98%

### · NTP (National Toxicology Program)

Phenanthrene, 98%

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- *Mobility in soil* No further relevant information available.
- $\cdot$  Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### **13 Disposal considerations**

- · Waste treatment methods
- *Recommendation: Must not be disposed of together with household garbage. Do not allow product to reach sewage system.*
- · Uncleaned packagings:
- Recommendation: Disposal must be made according to official regulations.

· UN-Number		
DOT, IMDG, IATA	UN1993	
· UN proper shipping name		
$\cdot DOT$	Flammable liquids, n.o.s. (Heptanes)	

Printing date 04/11/2019

Reviewed on 04/11/2019

Trade name:	Calibration Standard D
	ASTM D6591-18

	(Contd. of page
·IMDG	FLAMMABLE LIQUID, N.O.S. (HEPTANES), MARIN POLLUTANT
·IATA	FLAMMABLE LIQUID, N.O.S. (HEPTANES)
· Transport hazard class(es)	
·DOT	
RAMABLE LODO	
· Class	3 Flammable liquids
· Label	3
· IMDG	
· Class · Label	3 Flammable liquids 3
	5
·IATA	
· Class	3 Flammable liquids
· Label	3 Flammable liquids 3
· Packing group · DOT, IMDG, IATA	II
· Environmental hazards: · Marine pollutant:	Product contains environmentally hazardous substances: n-Heptand Symbol (fish and tree)
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Stowage Category	В
• Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	II of Not applicable.
• Transport/Additional information:	
·DOT	
• Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
·IMDG	
· Limited quantities (LQ)	5L
$\cdot$ Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

Printing date 04/11/2019

Reviewed on 04/11/2019

Trade name: Calibration Standard D ASTM D6591-18

(Contd. of page 8)

· UN ''Model Regulation'':

UN 1993 FLAMMABLE LIQUID, N.O.S. (HEPTANES), 3, II

## **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

,	tremely hazardous substances):	
None of the ing	redients is listed.	
Section 313 (Sp	pecific toxic chemical listings):	
CAS: 110-82-7	Cyclohexane	
CAS: 95-47-6	o-Xylene	
	Phenanthrene, 98%	
TSCA (Toxic Si	ubstances Control Act):	
n-Heptane		ACTIVE
Cyclohexane		ACTIVE
o-Xylene		ACTIVE
1-methylnaphth	alene	ACTIVE
Phenanthrene,	98%	ACTIVE
Hazardous Air	Pollutants	· · · · · ·
CAS: 95-47-6	p-Xylene	
1	Phenanthrene, 98%	
Proposition 65		
	wn to cause cancer:	
None of the ing	redients is listed.	
Chemicals know	wn to cause reproductive toxicity for females:	
None of the ing	redients is listed.	
Chemicals know	wn to cause reproductive toxicity for males:	
None of the ing	redients is listed.	
Chemicals know	wn to cause developmental toxicity:	
None of the ing	redients is listed.	
Carcinogenic c	ategories	
EPA (Environn	nental Protection Agency)	
CAS: 142-82-5	n-Heptane	D
CAS: 110-82-7	Cyclohexane	Ι
CAS: 95-47-6	o-Xylene	Ι
	Phenanthrene, 98%	D
TLV (Threshold	d Limit Value established by ACGIH)	
CAS: 95-47-6	p-Xylene	A4
CAS: 90-12-0	1-methylnaphthalene	A4
	•	

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

(Contd. on page 10)

US

Printing date 04/11/2019

Reviewed on 04/11/2019

Trade name: Calibration Standard D ASTM D6591-18

(Contd. of page 9) • GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). · Hazard pictograms GHS07 GHS02 GHS08 · Signal word Danger · Hazard-determining components of labeling: *n*-*Heptane* Cyclohexane · Hazard statements Highly flammable liquid and vapor. Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways. · Precautionary statements Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Avoid breathing dust/fume/gas/mist/vapors/spray Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Immediately call a poison center/doctor. Specific treatment (see on this label). Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention. In case of fire: Use for extinction: CO2, powder or water spray. Store in a well-ventilated place. Keep container tightly closed. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of preparation / last revision Revsion 0.0, 04-11-2019: Creation date for SDS. STN 04/11/2019 / -

(Contd. on page 11)

Printing date 04/11/2019

Reviewed on 04/11/2019

#### Trade name: Calibration Standard D ASTM D6591-18

	(Contd. of page 10)
Abbreviations and acronyms:	
IMDG: International Maritime Code for Dangerous Goods	
DOT: US Department of Transportation	
IATA: International Air Transport Association	
ACGIH: American Conference of Governmental Industrial Hygienists	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)	
NFPA: National Fire Protection Association (USA)	
HMIS: Hazardous Materials Identification System (USA)	
VOC: Volatile Organic Compounds (USA, EU)	
PBT: Persistent, Bioaccumulative and Toxic	
vPvB: very Persistent and very Bioaccumulative	
VIOSH: National Institute for Occupational Safety	
OSHA: Occupational Safety & Health	
TLV: Threshold Limit Value	
PEL: Permissible Exposure Limit	
REL: Recommended Exposure Limit	
Flam. Liq. 2: Flammable liquids – Category 2	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Asp. Tox. 1: Aspiration hazard – Category 1	