Printing date 04/03/2019 Reviewed on 04/03/2019

### 1 Identification

· Product identifier

· Trade name: Toluene/IPA/Acetone 1:1:1 v/v

· Article number: ND595

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586

· Information department:

Technical Coordinator

Sherman Nelson sherman@aquasolutions.org

· Emergency telephone number: Chemtrec: 800-424-9300 Canutec: 613-996-6666



## 2 Hazard(s) identification

· Classification of the substance or mixture



GHS02 Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

(Contd. of page 1)

#### · Hazard-determining components of labeling:

**Toluene** 

Acetone

Isopropanol

#### · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

*Ground/bond container and receiving equipment.* 

Use explosion-proof electrical/ventilating/lighting/equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Classification system:

#### · NFPA ratings (scale 0 - 4)



Health = 2 Fire = 3Reactivity = 0

#### · HMIS-ratings (scale 0 - 4)



Health = 2

Fire = 3

Reactivity = 0

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

(Contd. of page 2)

- · Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## 3 Composition/information on ingredients

- · Chemical characterization: Mixtures
- Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous con	ponents:	
CAS: 108-88-3	Toluene	35.456%
CAS: 67-64-1	Acetone	32.374%
CAS: 67-63-0	Isopropanol	32.171%

#### 4 First-aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- $\cdot$  After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

- · Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.

### 6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· Environmental precautions: Do not allow to enter sewers/ surface or ground water.

(Contd. on page 4)

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

(Contd. of page 3)

#### · Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

#### · Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

#### · Protective Action Criteria for Chemicals

	c. we will get entermine			
· <b>PAC-1</b> :				
CAS: 108-88-3	Toluene	67 ppm		
CAS: 67-64-1	Acetone	200 ppm		
CAS: 67-63-0	Isopropanol	400 ppm		
· PAC-2:				
CAS: 108-88-3	Toluene	560 ppm		
CAS: 67-64-1	Acetone	3200* ppm		
CAS: 67-63-0	Isopropanol	2000* ppm		
· PAC-3:				
CAS: 108-88-3	Toluene	8700* ppm		
CAS: 67-64-1		5700* ppm		
CAS: 67-63-0	Isopropanol	!2000** ppm		

### 7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

 $\cdot$  *Specific end use*(s) *No further relevant information available.* 

#### 8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

(Contd. of page 4) · Control parameters · Components with limit values that require monitoring at the workplace: CAS: 108-88-3 Toluene PEL Long-term value: 200 ppm Ceiling limit value: 300; 500\* ppm \*10-min peak per 8-hr shift REL Short-term value: 560 mg/m<sup>3</sup>, 150 ppm Long-term value: 375 mg/m³, 100 ppm TLV Long-term value: 75 mg/m³, 20 ppm BEICAS: 67-64-1 Acetone PEL Long-term value: 2400 mg/m³, 1000 ppm REL Long-term value: 590 mg/m<sup>3</sup>, 250 ppm TLV Short-term value: 1187 mg/m<sup>3</sup>, 500 ppm Long-term value: 594 mg/m<sup>3</sup>, 250 ppm BEICAS: 67-63-0 Isopropanol PEL Long-term value: 980 mg/m³, 400 ppm REL Short-term value: 1225 mg/m³, 500 ppm Long-term value: 980 mg/m³, 400 ppm TLV Short-term value: 984 mg/m<sup>3</sup>, 400 ppm Long-term value: 492 mg/m<sup>3</sup>, 200 ppm BEI· Ingredients with biological limit values: CAS: 108-88-3 Toluene BEI 0.02 mg/L LD50 Intraperitoneal: blood Time: prior to last shift of workweek LD50: Toluene  $0.03 \, mg/L$ LD50 Intraperitoneal: urine Time: end of shift LD50: Toluene 0.3 mg/g creatinine LD50 Intraperitoneal: urine Time: end of shift LD50: o-Cresol with hydrolysis (background) CAS: 67-64-1 Acetone BEI 50 mg/L LD50 Intraperitoneal: urine Time: end of shift LD50: Acetone (nonspecific) CAS: 67-63-0 Isopropanol BEI 40 mg/L LD50 Intraperitoneal: urine Time: end of shift at end of workweek LD50: Acetone (background, nonspecific)

(Contd. on page 6)

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

(Contd. of page 5)

- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

#### · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



#### Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

#### 9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Liquid
Color: Clear
Odor: Alcohol-like
Odor threshold: Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range: Undetermined.

**Boiling point/Boiling range:** 55.8-56.6 °C (132.4-133.9 °F)

• Flash point: <-18 °C (<-0.4 °F)

(Contd. on page 7)

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

	(Contd. of page
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	425 °C (797 °F)
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	1.2 Vol %
Upper:	13 Vol %
Vapor pressure at 20 °C (68 °F):	233 hPa (174.8 mm Hg)
Density at 20 °C (68 °F):	0.81413 g/cm³ (6.79391 lbs/gal)
Relative density	Not determined.
Vapor density	Not determined.
Evaporation rate	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/water	e <b>r):</b> Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC content:	67.63 %
	550.6 g/l / 4.59 lb/gal
Solids content:	0.0 %
Other information	No further relevant information available.

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values tha	t are relevant	for cla	ssification:
----------------------	----------------	---------	--------------

ATE (Acute Toxicity Estimate)

Oral LD50 14,102 mg/kg (rat)

(Contd. on page 8)

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

Inhalative | LC50/4h | 93.3 mg/l (rat) (Contd. of page 7)

· Primary irritant effect:

- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)			
CAS: 108-88-3	Toluene	3	
CAS: 67-63-0	Isopropanol	3	
· NTP (National Toxicology Program)			
None of the ingredients is listed.			
· OSHA-Ca (Occupational Safety & Health Administration)			
None of the ingredients is listed.			

## 12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

### 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

TIC

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

(Contd. of page 8)

Transport information	
UN-Number DOT, IMDG, IATA	UN1993
UN proper shipping name DOT IMDG, IATA	Flammable liquids, n.o.s. (Toluene, Isopropanol, Acetone) FLAMMABLE LIQUID, N.O.S. (TOLUENE, Isopropano ACETONE)
Transport hazard class(es)	
DOT	
R AMMARE LOUIS	
Class Label	3 Flammable liquids 3
· IMDG, IATA	
3	
Class Label	3 Flammable liquids 3
Packing group DOT, IMDG, IATA	II
Environmental hazards:	Not applicable.
Special precautions for user Danger code (Kemler): EMS Number: Stowage Category	Warning: Flammable liquids 33 F-E,S-D B
Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	<b>II of</b> Not applicable.
Transport/Additional information:	
DOT Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
IMDG Limited quantities (LQ) Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN 1993 FLAMMABLE LIQUID, N.O.S. (TOLUEN) ISOPROPANOL, ACETONE), 3, II

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

(Contd. of page 9)

### 15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara

· Section 355 (extremely hazardous substances)	· Section 355	(extremely	hazardous	substances	١:
--	---------------	------------	-----------	------------	----

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

CAS: 108-88-3 Toluene

CAS: 67-63-0 Isopropanol

· TSCA (Toxic Substances Control Act):

Toluene ACTIVE
Acetone ACTIVE
Isopropanol ACTIVE

### · Hazardous Air Pollutants

CAS: 108-88-3 Toluene

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

CAS: 108-88-3 Toluene

· Carcinogenic categories

· EPA (Environn	nental Protection Agency)	
CAS: 108-88-3	Toluene	II
CAS: 67-64-1	Acetone	Ι

## · TLV (Threshold Limit Value established by ACGIH)

1LV (Threshold Limit Value established by ACOIII)		
CAS: 108-88-3	Toluene	A4
CAS: 67-64-1	Acetone	A4
CAS: 67-63-0	Isopropanol	A4

#### · NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms







GHS02 GHS0

GHS07

- · Signal word Danger
- · Hazard-determining components of labeling: Toluene

(Contd. on page 11)

Printing date 04/03/2019 Reviewed on 04/03/2019

Trade name: Toluene/IPA/Acetone 1:1:1 v/v

(Contd. of page 10)

Acetone

Isopropanol

### · Hazard statements

Highly flammable liquid and vapor.

Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

May be fatal if swallowed and enters airways.

#### · Precautionary statements

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/bond container and receiving equipment.

*Use explosion-proof electrical/ventilating/lighting/equipment.* 

Use only non-sparking tools.

Take precautionary measures against static discharge.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

If swallowed: Immediately call a poison center/doctor.

Specific treatment (see on this label).

Do NOT induce vomiting.

If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Call a poison center/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Take off contaminated clothing and wash it before reuse.

If skin irritation occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

In case of fire: Use for extinction: CO2, powder or water spray.

Store in a well-ventilated place. Keep container tightly closed.

Store in a well-ventilated place. Keep cool.

Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- · Date of preparation / last revision

Revsion 0.0, 04-03-2019: Creation date for SDS. STN 04/03/2019 / -

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

(Contd. on page 12)

(Contd. of page 11)

## Safety Data Sheet acc. to OSHA HCS

Printing date 04/03/2019 Reviewed on 04/03/2019

#### Trade name: Toluene/IPA/Acetone 1:1:1 v/v

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit

BEI: Biological Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1