Printing date 06/07/2024

*

Reviewed on 06/07/2024

| Product identifier | | |
|---|--|-------------------|
| Trade name: <u>Copper 8500</u> in 57% w/w l | ppm + Vanadium 1,000 ppm w/w Nitric Acid | |
| Article number: SPX757 | | |
| Details of the supplier of the Manufacturer/Supplier: Aqua Solutions, Inc. 6913 Highway 225 DEER PARK, TX 77536 USA 800-256-2586 | ne safety data sheet | AQUA SOLUTIONS |
| Information department: Technical Coordinator Sherman Nelson shermann Emergency telephone num Chemtrec: 800-424-9300 Canutec: 613-996-6666 | | |
| | | |
| Hazard(s) identification | n | |
| Hazard(s) identification Classification of the substa | | |
| | nce or mixture | |
| Classification of the substa | nce or mixture | |
| Classification of the substa | nce or mixture ver circle H272 May intensify fire; oxidizer. | |
| Classification of the substa | nce or mixture ver circle H272 May intensify fire; oxidizer. I crossbones | |
| Classification of the substa GHS03 Flame of Oxidizing Liquids 3 GHS06 Skull and | nce or mixture ver circle H272 May intensify fire; oxidizer. I crossbones | |
| Classification of the substa GHS03 Flame of Oxidizing Liquids 3 GHS06 Skull and | nce or mixture ver circle H272 May intensify fire; oxidizer. I crossbones 3 H331 Toxic if inhaled. | |
| Classification of the substa GHS03 Flame or Oxidizing Liquids 3 GHS06 Skull and Acute Toxicity - Inhalation | nce or mixture ver circle H272 May intensify fire; oxidizer. I crossbones 3 H331 Toxic if inhaled. | |
| Classification of the substa GHS03 Flame or Oxidizing Liquids 3 GHS06 Skull and Acute Toxicity - Inhalation | er circle H272 May intensify fire; oxidizer. I crossbones 3 H331 Toxic if inhaled. azard | ne unborn child. |
| Classification of the substa GHS03 Flame of Oxidizing Liquids 3 GHS06 Skull and Acute Toxicity - Inhalation GHS08 Health h Carcinogenicity 2 | nce or mixture ver circle H272 May intensify fire; oxidizer. I crossbones 3 H331 Toxic if inhaled. azard H351 Suspected of causing cancer. H361 Suspected of damaging fertility or th | te unborn child. |
| Classification of the substa GHS03 Flame or Oxidizing Liquids 3 GHS06 Skull and Acute Toxicity - Inhalation Carcinogenicity 2 Toxic to Reproduction 2 GHS05 Corrosic | nce or mixture ver circle H272 May intensify fire; oxidizer. I crossbones 3 H331 Toxic if inhaled. azard H351 Suspected of causing cancer. H361 Suspected of damaging fertility or th | |
| Classification of the substa GHS03 Flame or Oxidizing Liquids 3 GHS06 Skull and Acute Toxicity - Inhalation GHS08 Health h Carcinogenicity 2 Toxic to Reproduction 2 | nce or mixture ver circle H272 May intensify fire; oxidizer. I crossbones 3 H331 Toxic if inhaled. azard H351 Suspected of causing cancer. H361 Suspected of damaging fertility or th | |

Printing date 06/07/2024

Reviewed on 06/07/2024

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid



The substance possesses oxidizing properties.

(Contd. on page 3)

US

Printing date 06/07/2024

Reviewed on 06/07/2024

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid

(Contd. of page 2)

· HMIS-ratings (scale 0 - 4)

· Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

| Dangerous compo | onents: | |
|-------------------------------------|----------------------------|---------|
| CAS: 7697-37-2 | Nitric Acid 8 | 81.319% |
| CAS: 19004-19-4 | Cupric Nitrate Hydrate | 3.108% |
| CAS: 1314-62-1 | Vanadium Pentoxide Reagent | 0.178% |
| • Table of Nonhaza | urdous Ingredients | |
| CAS: 7732-18-5 | Water i | 15.395% |

4 First-aid measures

• Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

Remove breathing apparatus only after contaminated clothing have been completely removed.

In case of irregular breathing or respiratory arrest provide artificial respiration.

• After inhalation:

Supply fresh air or oxygen; call for doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- \cdot Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

(Contd. on page 4)

US -

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 06/07/2024

Reviewed on 06/07/2024

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid

· Advice for firefighters

· Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

| | ons, protective equipment and emergency procedures | |
|-----------------------------|---|----------------------|
| Mount respiratory | | |
| | uipment. Keep unprotected persons away. | |
| • Environmental pr | | |
| Dilute with plenty | | |
| | ter sewers/ surface or ground water. | |
| | erial for containment and cleaning up: | |
| | l-binding material (sand, diatomite, acid binders, universal binders, sawdust). | |
| Use neutralizing a | gent. ated material as waste according to section 13. | |
| Ensure adequate v | 8 | |
| · Reference to other | | |
| | nformation on safe handling. | |
| | nformation on safe nanating. nformation on personal protection equipment. | |
| | disposal information. | |
| | Criteria for Chemicals | |
| • PAC-1: | | |
| CAS: 7697-37-2 | Nitric Acid | 0.16 ppm |
| CAS: 19004-19-4 | Cupric Nitrate Hydrate | 42 mg/m ³ |
| CAS: 1314-62-1 | Vanadium Pentoxide Reagent | 0.64 mg/m |
| · PAC-2: | | · |
| CAS: 7697-37-2 | Nitric Acid | 24 ppm |
| CAS: 19004-19-4 | Cupric Nitrate Hydrate | 150 mg/m |
| CAS: 1314-62-1 | Vanadium Pentoxide Reagent | 7 mg/m ³ |
| · PAC-3: | | |
| CAS: 7697-37-2 | Nitric Acid | 92 ppm |
| CAS: 19004-19-4 | Cupric Nitrate Hydrate | 240 mg/m |
| | | 70 mg/m ³ |

7 Handling and storage

· Handling:

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

· Information about protection against explosions and fires: Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

· Storage:

• Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 5)

Printing date 06/07/2024

Reviewed on 06/07/2024

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid

(Contd. of page 4)

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see section 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

PEL Long-term value: 5 mg/m³, 2 ppm

REL Short-term value: 10 mg/m³, 4 ppm Long-term value: 5 mg/m³, 2 ppm

TLV Short-term value: (4) NIC-0.025* ppm Long-term value: (2) ppm *inh. fraction + vapor, NIC-A4

CAS: 19004-19-4 Cupric Nitrate Hydrate

NIOS Short-term value: 1mg/m³ mg/m³

• Additional information: The lists that were valid during the creation were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation \cdot **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

[–] ÚS

Printing date 06/07/2024

Reviewed on 06/07/2024

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid

(Contd. of page 5)

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

| Information on basic physical and c | hemical properties | |
|---|---|--|
| General Information | | |
| Appearance: | | |
| Form: | Liquid | |
| Color: • Odor: | Blue Odorless | |
| · Odor: · Odor threshold: | Not determined. | |
| pH-value at 20 °C (68 °F): | <2 | |
| | | |
| • Change in condition Melting point/Melting range: | Undetermined. | |
| Boiling point/Boiling range: | 83 °C (181.4 °F) | |
| · Flash point: | Not applicable. | |
| · Flammability (solid, gaseous): | Not applicable. | |
| Decomposition temperature: | Not determined. | |
| Ignition temperature: | Product is not selfigniting. | |
| Danger of explosion: | Product does not present an explosion hazard. | |
| Explosion limits: | | |
| Lower: | Not determined. | |
| Upper: | Not determined. | |
| · Vapor pressure at 20 °C (68 °F): | 23 hPa (17.3 mm Hg) | |
| · Density at 20 °C (68 °F): | 1.45425 g/cm³ (12.13572 lbs/gal) | |
| · Relative density | Not determined. | |
| · Vapor density | Not determined. | |
| Evaporation rate | Not determined. | |
| · Solubility in / Miscibility with | | |
| Water: | Fully miscible. | |
| Partition coefficient (n-octanol/wate | r): Not determined. | |
| · Viscosity: | | |
| Dynamic: | Not determined. | |
| Kinematic: | Not determined. | |
| Solvent content: | | |
| Water: | 15.4 % | |
| VOC content: | 0.00 % 0.0 g/l / 0.00 lb/gal | |

Printing date 06/07/2024

Reviewed on 06/07/2024

(Contd. of page 6)

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid

Solids content:

3.3 %

• Other information

No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

ATE (Acute Toxicity Estimate)

Oral LD50 21,164 mg/kg

Inhalative LC50/4h 3.26 mg/l

· Primary irritant effect:

- on the skin: Strong caustic effect on skin and mucous membranes.
- \cdot on the eye:
- Strong caustic effect.

Strong irritant with the danger of severe eye injury.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Toxic

Corrosive

Irritant

Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.

· Carcinogenic categories

| · IARC (International Agency for Research on Cancer) | |
|---|------|
| CAS: 1314-62-1 Vanadium Pentoxide Reagent | 2B |
| · NTP (National Toxicology Program) | |
| None of the ingredients is listed. | |
| · OSHA-Ca (Occupational Safety & Health Administration) | |
| None of the ingredients is listed. | |
| | US - |

(Contd. on page 8)

Printing date 06/07/2024

Reviewed on 06/07/2024

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid

(Contd. of page 7)

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Must not reach bodies of water or drainage ditch undiluted or unneutralized.

Rinse off of bigger amounts into drains or the aquatic environment may lead to decreased pH-values. A low pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably increased, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agent: Water, if necessary with cleansing agents.

14 Transport information

| · UN-Number · DOT, IMDG, IATA | UN3264 |
|--|---|
| · UN proper shipping name · DOT · IMDG, IATA | Corrosive liquid, acidic, inorganic, n.o.s. (Nitric Acid) CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric Acid) |
| · Transport hazard class(es) | |
| ·DOT | |
| CORROSIVE 8 | |
| · Class | 8 Corrosive substances |
| | (Contd. on page 9 |

Printing date 06/07/2024

Reviewed on 06/07/2024

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid

| | (Contd. of page |
|---|--|
| Label | 8 |
| · IMDG, IATA | |
| | |
| | |
| | |
| V | |
| Class | 8 Corrosive substances |
| Label | 8 |
| Packing group | |
| DOT, IMDG, IATA | II |
| Environmental hazards: | Not applicable. |
| Special precautions for user | Warning: Corrosive substances |
| Hazard identification number (Kemler code): | |
| EMS Number: | F-A,S-B |
| Segregation groups | (SGG1) Acids |
| Stowage Category | В |
| Stowage Code | SW2 Clear of living quarters. |
| Transport in bulk according to Annex II of | |
| MARPOL73/78 and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| DOT | |
| Quantity limitations | On passenger aircraft/rail: 1 L |
| | On cargo aircraft only: 30 L |
| IMDG | |
| Limited quantities (LQ) | 1L |
| Excepted quantities $(\widetilde{E}Q)$ | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| UN "Model Regulation": | UN 3264 CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S |
| 5 | (NITRIC ACID), 8, II |

15 Regulatory information

• Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.

• Sara

· Section 355 (extremely hazardous substances):

CAS: 7697-37-2 Nitric Acid

CAS: 1314-62-1 Vanadium Pentoxide Reagent

• Section 313 (Specific toxic chemical listings):

CAS: 7697-37-2 Nitric Acid

CAS: 1314-62-1 Vanadium Pentoxide Reagent

· TSCA (Toxic Substances Control Act):

Nitric Acid

ACTIVE

(Contd. on page 10)

[•] US

Printing date 06/07/2024

Reviewed on 06/07/2024

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid

| | (Contd. of page 9) |
|------------------------------------|--------------------|
| Water | ACTIVE |
| Vanadium Pentoxide Reagent | ACTIVE |
| · Hazardous Air Pollutants | |
| None of the ingredients is listed. | |
| · Proposition 65 | |
| · Chemicals known to cause cancer: | |

CAS: 1314-62-1 Vanadium Pentoxide Reagent

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value)

CAS: 1314-62-1 Vanadium Pentoxide Reagent

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

| | Hazard-determining components of labeling: |
|---|---|
| | Nitric Acid |
| | Vanadium Pentoxide Reagent |
| | Cupric Nitrate Hydrate |
| • | Hazard statements |
| | May intensify fire; oxidizer. |
| | Toxic if inhaled. |
| | Causes severe skin burns and eye damage. |
| | Suspected of causing cancer. |
| | Suspected of damaging fertility or the unborn child. |
| • | Precautionary statements |
| | Obtain special instructions before use. |
| | Do not handle until all safety precautions have been read and understood. |
| | Keep away from heat. |
| | Keep/Store away from clothing/combustible materials. |
| | Take any precaution to avoid mixing with combustibles. |
| | Do not breathe dusts or mists. |
| | Wash thoroughly after handling. |
| | |

(Contd. on page 11)

AЗ

Printing date 06/07/2024

Reviewed on 06/07/2024

Trade name: Copper 8500 ppm + Vanadium 1,000 ppm w/w in 57% w/w Nitric Acid

(Contd. of page 10) Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protection/face protection. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. IF INHALED: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. IF exposed or concerned: Get medical advice/attention. Specific treatment (see on this label). Wash contaminated clothing before reuse. In case of fire: Use CO2, powder or water spray to extinguish. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container in accordance with local/regional/national/international regulations. · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Environment protection department.
- · Contact:
- Date of Preparation / Last Revision:
- Date of preparation / last revision Revision 1.2, 06/05/2024: Reviewed SDS for accuracy. MH/STN Revision 0.0, 05-29-2024: Creation date for SDS. STN 06/07/2024

· Abbreviations and acronyms: IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit **REL:** Recommended Exposure Limit Oxidizing Liquids 3: Oxidizing liquids - Category 3 Acute Toxicity - Inhalation 3: Acute toxicity - Category 3 Skin Corrosion 1A: Skin corrosion/irritation - Category 1A Eye Damage 1: Serious eye damage/eye irritation - Category 1 Carcinogenicity 2: Carcinogenicity – Category 2 Toxic to Reproduction 2: Reproductive toxicity - Category 2 \cdot * Data compared to the previous version altered.